The original and first copy of this report are to be The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON Within 30 days from the date of well completion.

STATE ENGINEER SALEM, OREGON STATE ENGINEER ST

	One District Control of the Control	
(1) OWNER:	(10) LOCATION OF WELL:	
Name Ronald Jones Estate % Ronald Jones Jr.	County Marion Driller's well number 1842	
Address 6705 Continental Circle SE	14 Section 29 T. 6S R. 2W W.M.	
Salem, Oregon 97302	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well ₩ Deepening Reconditioning Abandon		· · · · · · · · · · · · · · · · · · ·
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed wel	1.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 34 ft.	
Rotary Driven Domestic Industrial Municipal		face. Date 6-26-74
Cable	Artesian pressure lbs. per square	
CASING INSTALLED: Threaded □ Welded ☑ 8 " Diam. fromtopft. toft. Gage250 ft. Gage	(12) WELL LOG: Diameter of well below casing Depth drilled 100 ft. Depth of completed well 100 ft. Formation: Describe color, texture, grain size and structure of materials;	
PERFORATIONS: Perforated? W Yes No.	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
Type of perforator used Mills	MATERIAL	From To SWL
Size of perforations 3/8 in. by 2 in.	Peat	0 12
760 perforations from 40 ft. to 92 ft.	Brown silty clay	12 34
perforations from ft. to ft.	Brown silty sand	34 36
perforations from	Brown sand and gravel	36 91
(7) SCREENS: Well screen installed? To Yes 77 No.	Black sand and gravel	91 97
(7) SCREENS: Well screen installed? ☐ Yes ☑ No Manufacturer's Name	Blue gravelly clay	97 100
Type Model No,		
Diam. Slot size Set from ft. to ft.		
Diam, Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? Yes No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		·
Pump Test will be made by Stettlers "		
" Supply " " "		
Bailer test gal./min. with ft. drawdown after hrs.	·	
Artesian flow g.p.m.	1	
perature of water Depth artesian flow encountered ft.	Work started Type 70 19 77 Completed	Tune 26 1974
(9) CONSTRUCTION:	Work started June 18, 19 74 Completed June 26, 1974 Date well drilling machine moved off of well June 26, 1974	
	Drilling Machine Operator's Certification:	<u>e ev, 1574</u>
Well seal—Material used <u>Cement</u> Well sealed from land surface to <u>20</u> ft. Diameter of well bore to bottom of seal <u>12</u> in.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.	
Diameter of well bore below seal8in. Number of sacks of cement used in well seal8	[Signed] Date 7-1-74, 19 Date 7-1-74, 19	
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No752	
Brand name of bentonite		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used? 🔯 Yes 📋 No Plugs Size: location ft.		
Did any strata contain unusable water? 🗌 Yes 🛭 No	Name VIIIAMETTE DRILLING COMPANY (Type or print)	
Type of water? depth of strata	Address 7641 35th Ave. NE Salem, Oregon 97303	
Method of sealing strata off	8' - 110 P	
Was well gravel packed? [] Yes 🛨 No Size of gravel:	[Signed] (Water Well Contract	or)
Gravel placed from ft. to ft.	Contractor's License No. 2 Date Jul	y 1, 1974 19