NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON MAY 24 1977 State

STATE OF OREGON MAY 24 1977

(Please type or print ATER RESOURCES DEPT.

(Do not write above this line) SALEM, OREGON ate Permit No. 67567

(1) OWNER:	(10) LOCATION OF WELL:	
Name Herman A. Hahn	County Marion Driller's well num	ber 2038
Address 3680 Perkins Rd. NE	14 14 Section 30 T. 6S R.	. 2W w.m.
Sukm Brooks, Oregon 97305	Bearing and distance from section or subdivision	corner
(2) TYPE OF WORK (check):		
New Well 🖔 Deepening 🛘 Reconditioning 🖂 Abandon 🗖		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed wel	ī.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 60 ft.	
Rotary Driven Domestic Industrial Municipal		face. Date 5/12/77
Cable		
	Artesian pressure lbs. per square i	men. Date
CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: Diameter of well below casing	
10." Diam. fromtop ft. to140 ft. Gage250	Depth drilled 140 ft. Depth of completed well 140 ft.	
ft. dage ft. Gage	Formation: Describe color, texture, grain size and structure of materials;	
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,	
PERFORATIONS: Perforated? [3] Yes [7] No.	with at least one entry for each change of formation position of Static Water Level and indicate princip	
X III Z III		From To SWL
i i i i i i i i i i i i i i i i i i i		0 2
Size of perforations       3/8       in. by       2 3/4       in.         610       perforations from       98       ft. to       135       ft.	Topsoil Brown Clay	2 60
	Brown Sand, Clay	60 74
perforations from	Brown Sandy gravel	74 78
perforations from ft. to ft.	Cemented Brown Sand and Gravel	84 90
(7) SCREENS: Well screen installed?   Yes   No	Brown Sand and Gravel	90 137
Manufacturer's Name		137 140
Type Model No		
Diam Slot size Set from ft. to ft.		
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? 🛣 Yes 🗌 No If yes, by whom?driller		
yield: 500 gal./min. with 6 ft. drawdown after 1 hrs.		
" " "		
" " " "		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
		- I / 10 / 77 · · ·
perature of water Depth artesian flow encountered ft.	Work started 5/7/77 19 Completed	5/12/77 19 5/12/77 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3/12/// <sub>19</sub>
Well seal—Material used <b>KK</b> Portland Cament	Drilling Machine Operator's Certification:	
Well sealed from land surface to ft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my	
Diameter of well bore to bottom of seal17 in.	best knowledge and belief.	
Diameter of well bore below sealin.	[Signed] Lolla D. A. Cles Date .5/13/77, 19	
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No. 75	
How was cement grout placed? poured in from the top	Drining Wachine Operator's License No. 2.1	
	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used? 🕻 Yes 🗌 No Plugs Size: location ft.	Name Willamette Drilling Co. (Person, firm or corporation) (Type or print)	
Did any strata contain unusable water? 🗌 Yes 🔏 No		
Type of water? depth of strata	Address 1450 Barnick Rd. NE Salem, Oregon 97303	
Method of sealing strata off	reigned Dallas Lagaria	
Was well gravel packed? ☐ Yes Z No Size of gravel:	[Signed] Callas & dy Contractor)	
Gravel placed from ft. to ft.	Contractor's License No. 36 June 25/	13/77 , 19
	- · ·	•