

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED STATE OF OREGON (Please type or print) (Do not write above this line) MARI 18 1968

WATER WELL REPORT

MARI... 4569

State Well No. 6/24-308

State Permit No. G-4293

owner's well # 2 STATE ENGINEER SALEM OREGON

(1) OWNER:

Name EUGENE PETROFF Address 1225 N.E. 107 PLACE PORTLAND ORE.

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [X] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [X] Municipal [] Irrigation [X] Test Well [] Other []

(5) CASING INSTALLED:

10" Diam. from 0 ft. to 153' ft. Gage 4'

PERFORATIONS:

Perforated? [X] Yes [] No. Type of perforator used MILLS Size of perforations 3/8 in. by 2 1/2 in. 870 perforations from 94' ft. to 150 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 37'6" ft. below land surface Date 11.30.67 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [X] Yes [] No If yes, by whom?

Bailer test 75 gal./min. with 3 ft. drawdown after 1 hrs.

Artesian flow g.p.m. Date Temperature of water 51° Was a chemical analysis made? [] Yes [X] No

(10) CONSTRUCTION:

Well seal-Material used BENTONITE. Depth of seal 50' ft. Diameter of well bore to bottom of seal 13 1/2 in. Were any loose strata cemented off? [] Yes [X] No Depth Was a drive shoe used? [X] Yes [] No Did any strata contain unusable water? [X] Yes [] No Type of water? SANDY depth of strata 55' to 59' Method of sealing strata off CASED. Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County MARION Driller's well number 1/4 Section 30 T. 6S R. 2W W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 10" Depth drilled 153' ft. Depth of completed well 153' ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with 4 columns: MATERIAL, From, To, SWL. Rows include TOPSOIL, CLAY YELLOW COLOR, SAND-BLACK-FINE GRAIN, SAND BROWN-MED, CLAY BLUE COLOR, CONGLOMERATE-BLUE, CLAY YELLOW COLOR, GRAVEL-MUDDY YELLOW, CONGLOMERATE-YELLOW, GRAVEL-3"-W.B., CONGLOMERATE-YELLOW, GRAVEL & SAND 3"-, CONGLOMERATE YELLOW, GRAVEL-BLUE, CONGLOMERATE BLUE.

Work started 11-23-1967 Completed 11-30-1967 Date well drilling machine moved off of well 11-30-1967

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] B.F. Sneed Date 11-30, 1967 (Drilling Machine Operator)

Drilling Machine Operator's License No. 187

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. NAME J.A. SNEED & SONS. (Person, firm or corporation) (Type or print) Address 3910 SILVERTON RD. N.E. SALEM ORE. 97363 [Signed] B.F. Sneed (Water Well Contractor) Contractor's License No. 6 Date 11-30, 1967