NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPOR

3 WELL

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON State Well No. 6/26-30 F

(Please type or print TATE ENGINEER

(Do not write above this line) ALE ORESTS Permit No.

Owners well #3	G-4293
(1) OWNER:	(11) LOCATION OF WELL:
Name EUGENE PETROFF	County MARION Driller's well number
Address 1225 N.E 107 PLACE PORTLAND OPE.	14 14 Section 30 T. 65 R. 2 W. W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well 🔀 Deepening 🗌 Reconditioning 🗀 Abandon 🖂	
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well below casing 15.
Rotary Driven Domestic Industrial Municipal	Depth drilled 180' ft. Depth of completed well 180' ft.
Dug 🗌 Bored 🗌 Irrigation 🕱 Test Well 🗌 Other 📋	Formation: Describe color, texture, grain size and structure of materials;
(5) CASING INSTALLED: Threaded Welded S	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.
	MATERIAL From To SWL
". Diam. from ft. to ft. Gage	TOPSOR 0 2
PERFORATIONS: Perforated? Yes No.	CLAY YELLOW STIERY 2 52
Type of perforator used MILLS.	SAND- BRUWN - 71NE 52 62 37
Size of perforations 3, in. by 2, in.	CLAY BLUE STIERY 62 68
180 perforations from 165 ft. to 176 ft.	CLAYSTONIE BLUE-SOFT 68 74
876 perforations from 86 ft. to /37 ft.	CONGLOPIERATE BLUE 74 84 BRAVEL - TIGHT- 84 86
perforations fromft. toft.	CONGLOMERATE W.B. 86 90 42'
perforations from ft. to ft.	GRAVEL COARSE - W.B 90 93 42
perforations fromft. toft.	CONBLOMERATE W.B. 93 130
(7) SCREENS: Well screen installed? Ti Yes XNo	GRAVEL 21"- W.B. 130 136 42"
(7) SCREENS: Well screen installed? Yes No	CLAY BLUE STICKY 136 140
TypeModel No.	CLAY BLUE SAHDY 140 148
Diam. Slot size Set from ft. to ft.	CERY BLUE STICKY 148 151
Diam. Slot size Set from ft. to ft.	CONGLUMERATE BLUE 151 156
	GRAVEL 12" - W.B 156 157 42"
(8) WATER LEVEL: Completed well.	CONGROMERATE BLUE 157 175 GRAVEL 1"- W.B. 175 176 421
To botton and burieto Dutto V	CONGAC MORATE 176 180
Artesian pressure lbs. per square inch Date	20/10000 75 750
(9) WELL TESTS: Drawdown is amount water level is lowered below static level 5.72712eR	
Was a pump test made? Yes No If yes, by whom?	
: 620 gal./min. with 35 ft. drawdown after Z hrs.	Work started 12.15- 1967 Completed 12.27 1967
1000 " 63 " / "	Date well drilling machine moved off of well /2.27 1967
" " " "	Drilling Machine Operator's Certification:
Bailer test 75 gal./min. with 2 ft. drawdown after / hrs.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best
Artesian flow g.p.m. Date	knowledge and belief
Temperature of water 57 Was a chemical analysis made? Yes	[Signed] B4 Sweed Date 12.27, 1967
	(Drilling Machine Operator)
(10) CONSTRUCTION: Well seal-Material used BENTONITE	Drilling Machine Operator's License No.
Well seal—Material used Devices of the Depth of seal 65 th.	Water Wall Control Contidents
Diameter of well bore to bottom of sealin,	Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is
Were any loose strata cemented off? Yes No Depth	true to the best of my knowledge and belief.
Was a drive shoe used? Yes No	NAME JA. SNEED & SONS.
Did any strata contain unusable water? 🗹 Yes 🗌 No	(Person, firm or corporation) (Type or print) Address 3910 SILVERTON RD SILVER CR-
Type of water? SAMDY MUDD hepth of strata 52' TU 62'	Address 3710 \$1100 1100 1100 1100 Officer Ch.
Method of sealing strata off CASEP.	B. I Second 71303
	[Signed] (Water Well Contractor)
Was well gravel packed? ☐ Yes ZNo Size of gravel:	
Gravel placed from ft. to ft.	Contractor's License No. Date 12.27, 1967