NOTICE TO WATER WELL CONTRACTOR 2 1966

The original and first copy of this report are to be filed with the 1 ATE ENGINEEWATER WELL REPORT

State Well No. 6/2W-30+

STATE ENGINEER, SALEM, OREGON 97310 CROON within 30 days from the date	5

STATE OF OREGON (Please type or print)

State Permit No.

of well completion.	G 3712	
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water lowered below static level	Jewa is
W L MANCOY	Was a pump test made? Yes \sum No If yes, by whom?	Thethers
Name Address Addres	Yield: 200 gal,/min, with 25 ft. drawdown after	
Salem Oregon	" " " " "	"
	" "	,,
(2) LOCATION OF WELL:	Bailer test gal./min, with ft. drawdown a	after hrs.
County // O.Y. O. Driller's well number		11101
1/4 1/4 Section 30 T. (S R. 2 W W.	5//	No. IVes IV
Bearing and distance from section or subdivision corner	Temperature of water 27 Was a chemical analysis made	? Yeş No
25-curing with displayed 21-curing about of building and a second of bu	(12) WELL LOG: Diameter of well below casing	
	Depth drilled 7/1 ft. Depth of completed well	70 ft.
		structure, and
and the second s	Formation: Describe by color, character, size of material and show thickness of aquifers and the kind and nature of the m stratum penetrated, with at least one entry for each change	laterial in each
(a) MYYDE OF WODE (I I I)	MATERIAL FR	OM TO
(3) TYPE OF WORK (check):	100 2014	2 5
Well ∠ Deepening □ Reconditioning □ Abandon □	BHOWN C/24 3	23
If abandonment, describe material and procedure in Item 12.	Brown Sand 2.	5 30
(4) PROPOSED USE (check): (5) TYPE OF WELL:	B/40 C/24 30	0 40
Rotary C Driven C	Cray Sand 4	0 50
Domestic Industrial Municipal Cable Ietted	Gravel-Coarse 5	0 70
Irrigation Test Well Other Dug Bored	r	
(6), CASING INSTALLED: Threaded Welded		
	-	
"Diam. fromft. toft. Gage :2.30		
ft. to		
ft. Gageft. Gage		
(7) PERFORATIONS: , Perforated? Yes \(\subseteq \) No		
Type of perforator used		
Size of perforations 2 % in. by 3/d in.		
LOO perforations from 55 oft. to 68 ft.		
perforations fromft. toft.		
perforations from ft. to ft.		
perforations fromft. toft.		
perforations fromft. toft.		
(8) SCREENS: Well screen installed? ☐ Yes ☐ No		
Manufacturer's Name		
Model No	7 . / // 7	, , /
Diam Slot size Set from ft. to ft.	Work started HOril 2 1966 Completed HPY	18 1966
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well	18 19
(0) CONSTRUCTION:		
(9) CONSTRUCTION:	(13) PUMP:	
Well seal—Material used in seal	Manufacturer's Name	
Depth of seal	Type: H.P.	***************************************
Diameter of well bore to bottom of seal		
Were any loose strata cemented off? Yes Depth	Water Well Contractor's Certification:	
Was a drive shoe used? ✓ Yes □ No	This well was drilled under my jurisdiction and	this report is
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	true to the best of my knowledge and belief.	. •
Gravel placed from	NIABER John Mannen Hillon	
	NAME John Truman Miller (Person, firm or corporation) (Type or	print)
Did any strata contain unusable water? Yes No	Address P O Box 42 Hubbard, Or	egon
Type of water? depth of strata	17	'9
Method of sealing strata off	Drilling Machine Operator's License No.	<i>[</i>
(10) WATER LEVELS:	Holand has let	
Static level 20 ft. below land surface Date #Py 86	[Signed] (Water Well Contractor)	.2
	'I // ' EUI /	66
Artesian pressure lbs. per square inch Date /	Contractor's License No. Date April 9	, 19 66