BIVE TO ARI.

(10) WATER LEVELS:

Name

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

filed with the	F OREGON State Well No.	/2W	-30 1
STATE ENGINEER, SALEM, OREGON 9/310 STATE OF within 30 days from the date STATE. ENGINEEPRase ty of well completion.	pe or print) G-4468 State Permit No		•
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
TIDT TN C DACE	Was a pump test made? XYes \(\text{INO} \) No If yes, by whom? DRILLER		
Name ORLIN S. FAGE Address 495 LINCOLN S. SALEM, OREGON	Yield: 500 gal./min. with T4 ft. drawdow		4 hrs.
Address 400 Hillioum D. Stilling Orling	" 450 " I2 "	n arter	重
(2) LOCATION OF WELL:	" 400 " 8 "		4 "
` '	XPENET XXXX 270 gal./min. with 7 ft. drawdor	wn after	4 hrs.
County MARION Driller's well number 932	Artesian flow g.p.m. Date		
14 14 Section S 30-31. T 6S R. 2 W W.M.	Temperature of water Was a chemical analysis n	nade? 🔲 Y	es 🗆 No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below ca	sing	
		- 00	
	Depth drilled 90 ft. Depth of completed we		
	Formation: Describe by color, character, size of materia show thickness of aquifiers and the kind and nature of i stratum penetrated, with at least one entry for each of	the materi	al in each
	stratum penetratea, with at teast one entry for each ci	tange of f	ormanon.
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	TOP SOIL	0	IO
New Well	CLAY	IO	25
andonment, describe material and procedure in Item 12.	SAND	25	32
PROPOSED USE (check): (5) TYPE OF WELL:	GRAVEL	32	60
Rotary [7] Driven [7]	SAND	60_	_65
Domestic Industrial Municipal Cable Jetted	GRAVEL	65	90
rrigation X Test Well Other Dug Bored		ļ	
(6) CASING INSTALLED: Threaded □ Welded ₩			
8 " Diam. from TOP ft. to 90 ft. Gage 250			
(7) PERFORATIONS: Perforated? T Yes No	,		
Type of perforator used MITLS Size of perforations 3/8 in. by 2 in.			
of periorations -, - m. wy	·		
perforations from			
perforations from ft. to ft.	,		
perforations from ft. to ft.			-
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? ☐ Yes \ No			
Manufacturer's Name			,
Type Model No			
Slot size Set from ft. to ft.	Work started JUNE 24 1964. Completed JU	NE 29	1964
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well JUNE	29	1964
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal CEMENT & PUTTLE CLAY			
Well seal—Material used in seal STANDARY OF THE SEAL O	Manufacturer's Name		
Diameter of well bore to bottom of seal in.	Type: H.P.		
	Water Well Contractor's Certification:		
Were any loose strata cemented off? Yes No Depth	milia anali anna datii da anada anad	amal 41-1	manart to
Was a drive shoe used? □ Yes □ No Was well gravel packed? □ Yes □ XNo Size of gravel:	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	and this	report is
Gravel placed from ft. to ft.			
	NAME WILLAMETTE DRILLING CO. (Person, firm or corporation) (Type or print)		
Did any strata contain unusuable water? ☐ Yes ☐ No Type of water? depth of strata	Address RT. 2 BOX 276 SALEM, OREGON		
Method of sealing strata off	•		***************************************
incurred or scaring strawa our	Drilling Machine Operator's License No	79	

Contractor's License No. 2 Date 6/80/64 , 19

[Signed]