

TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

not write above this line)

STATE ENGINEER, SALEM, OREGON 97301 within 30 days from the date of well completion.

RECEIVED JUN 16 1969 STATE ENGINEER SALEM OREGON

4594 MAR 1969

State Well No. 42W-31

State Permit No.

(1) OWNER: Name Robert Genc Address 5422 Portland Road NE Salem, Oregon

(2) TYPE OF WORK (check): New Well [x] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check): Rotary [] Driven [] Domestic [x] Industrial [] Municipal [] Cable [] Jetted [] Irrigation [] Test Well [] Other [] Dug [] Bored []

CASING INSTALLED: Threaded [] Welded [x] 8" Diam. from top ft. to 140 ft. Gage 250

PERFORATIONS: Perforated? [x] Yes [] No. Type of perforator used Mills Size of perforations 3/8 in. by 2 in. 128 perforations from 100 ft. to 115 ft. 88 perforations from 130 ft. to 140 ft.

(7) SCREENS: Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well. Static level 50 ft. below land surface Date 6-9-69 Artesian pressure lbs. per square inch Date

(9) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? [x] Yes [] No If yes, by whom? Driller Yield: 225 gal./min. with 17 ft. drawdown after 4 hrs. Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date Temperature of water Was a chemical analysis made? [] Yes [] No

(10) CONSTRUCTION: Well seal—Material used Drill cuttings Puddle Clay Depth of seal 20 ft. Diameter of well bore to bottom of seal 10 in. Were any loose strata cemented off? [] Yes [x] No Depth Was a drive shoe used? [x] Yes [] No Did any strata contain unusable water? [] Yes [] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL: County Marion Driller's well number 1403 1/4 Section 31 T. 6 R. 2W W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG: Diameter of well below casing Depth drilled 140 ft. Depth of completed well 140 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Top Soil, Yellow Clay, Brown Clay, Brown sand, Brown sand and gravel, Red Clay, gravel, Cemented brown sand & gravel, Black sand and gravel.

Work started May 29, 1969 Completed June 10, 1969 Date well drilling machine moved off of well June 10, 1969

Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Harold A. Wagner Date June 10, 1969 (Drilling Machine Operator)

Drilling Machine Operator's License No. 474

Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME WILLAMETTE DRILLING COMPANY (Person, firm or corporation) (Type or print) Address 7641 35th Ave. NE Salem, Oregon 97303 [Signed] Emil O. Beier (Water Well Contractor) Contractor's License No. 2 Date June 10, 1969

Trailer count listed on card