

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT
STATE OF OREGON
APR 15 1985
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 65/2W-326
State Permit No. G-1046

(1) OWNER:

Name Cletus L. Woods
Address 3950 Hazelgreen Rd. N.E.
Salem, Oregon 97305

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

10 " Diam. from +1 ft. to 160 ft. Gage .250
" Diam. from _____ ft. to _____ ft. Gage _____
" Diam. from _____ ft. to _____ ft. Gage _____

PERFORATIONS:

Perforated? Yes No.
Type of perforator used Mills Knife
Size of perforations 1/2 in. by 2 1/2 in.
740 perforations from 90 ft. to 146 ft.
60 perforations from 155 ft. to 159 ft.
perforations from _____ ft. to _____ ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name _____
Type _____ Model No. _____
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? driller
Yield: 500 gal./min. with 46 ft. drawdown after 3 1/2 hrs.
" " " "
" " " "
Bailer test _____ gal./min. with _____ ft. drawdown after _____ hrs.
Artesian flow _____ g.p.m.
Temperature of water _____ Depth artesian flow encountered _____ ft.

(9) CONSTRUCTION:

Well seal—Material used Dry Granulated Bentonite
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 14 in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal 0 sacks
How was cement grout placed? approxiametely 850 pounds
of bentonite placed inot dry annulus during
construction
Was a drive shoe used? Yes No Plugs _____ Size: location _____ ft.
Did any strata contain unusable water? Yes No
Type of water? _____ depth of strata _____
Method of sealing strata off _____
Was well gravel packed? Yes No Size of gravel: _____
Gravel placed from _____ ft. to _____ ft.

(10) LOCATION OF WELL:

County Marion Driller's well number 2538
NW 1/4 SW 1/4 Section 32 T. 6S R. 2W W.M.
Bearing and distance from section or subdivision corner _____

(11) WATER LEVEL: Completed well.

Depth at which water was first found 78 ft.
Static level 44 ft. below land surface. Date 4/3/85
Artesian pressure _____ lbs. per square inch. Date _____

(12) WELL LOG:

Diameter of well below casing _____
Depth drilled 160 ft. Depth of completed well 160 ft.
Formation: Describe color, texture, grain size and structure of materials, and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Topsoil	0	2	
Brown Clay	2	74	
Sandy Brown Clay	74	78	
Cemented Brown Sand and Gravel	78	146	
Gray Clay	146	152	
Cemented Balck Sand and Gravel	152	160	

Work started 1/7/85 19 Completed 4/3/85 19
Date well drilling machine moved off of well 4/4/85 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Mark D. Beis Date 4/4/85, 19_____
(Drilling Machine Operator)
Drilling Machine Operator's License No. 811

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name WILLAMETTE DRILING CO. (Type or print)
Address 7365 O'Neil Rd. N.E. Salem, Oregon 97303
[Signed] Mark D. Beis (Water Well Contractor)
Contractor's License No. 753 Date 4/4/85, 19____