

The original and first copy of this report are to be filed with the

WATER WELL REPORT

RECEIVED

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON (Please type or print)

MAY 14 1974

State Well No. 65/2W-36 Permit No. G-5547-G-10286

4766 MARI

(1) OWNER:

Name Robert Hapi Address Rt. 2 Box Silverton, Oregon 97381

(2) TYPE OF WORK (check):

New Well [] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

(5) CASING INSTALLED:

10" Diam. from 1+ ft. to 175 ft. Gage 250

PERFORATIONS:

Type of perforator used Mills Knife Size of perforations 3/8 in. by 3 in. 302 perforations from 87 ft. to 124 ft. 208 perforations from 144 ft. to 169 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [x] Yes [] No If yes, by whom? Stadeli Yield: 200 gal./min. with 35 ft. drawdown after 4 hrs. 300 " 50 " 2 " 500 " 77 " 1/2 "

(9) CONSTRUCTION:

Cement at 26 ft. Well seal—Material used Bentonite Well sealed from land surface to 26 ft. Diameter of well bore to bottom of seal 14 in. Diameter of well bore below seal 10 in. Number of sacks of cement used in well seal 1 sacks Number of sacks of bentonite used in well seal 4 sacks Brand name of bentonite National Number of pounds of bentonite per 100 gallons of water 50 lbs./100 gals. Was a drive shoe used? [x] Yes [] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [x] No Type of water? XX depth of strata XX Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number S.E 1/4 N.W 1/4 Section 36 T. 65 R. 2W W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 15 ft. Static level 25 ft. below land surface. Date 4/17/74 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0 ft. Depth drilled 190 ft. Depth of completed well 169 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with 4 columns: MATERIAL, From, To, SWL. Rows include Top Soil dark brown, Fine sandy clay brown, Fine sandy clay grey, Clay grey sticky, Clay sandy brown, Mod. conglom brown, Sand and gravel, Mod. conglom brown, Sand and gravel, Mod. conglom brown, Sand and gravel, Sand fine brown, Sand and gravel, Mod. conglom brown, Sand and gravel brown, Mod. conglom brown, Sand and gravel brown, Mod. conglom black, Clay dark grey.

Work started 3/19 1974 Completed 4/18 1974 Date well drilling machine moved off of well 4/19/74 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] WA [Signature] Date 5/9, 1974 (Drilling Machine Operator)

Drilling Machine Operator's License No. 491

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name R. Stadeli & Sons, Inc. (Person, firm or corporation) (Type or print)

Address Rt e.3, Box 169, Silverton, Oregon 97381

[Signed] Paul R. Stadeli (Water Well Contractor)

Contractor's License No. 296 Date 5/9/74, 19

