NOTICE TO WATER WELL CONTRACTOR.

The original and first copy of this report are to be filed with the state Engineer, SALEM 10, OREGON Within 30 days from the date

STATE OF OREGON Within 30 days from the date

ep. Hå.			. /	a _t
State	Well	No.	6/34	-2
		1.0	/	

of well completion.	State Permit No.		
(1) OWNER: Name JOE RYAN	(11) WELL TESTS: Drawdown is amount water level is lowered below static level lowered below static level. Was a pump test made? Yes Drawdown is amount water level is lowered below static level. Drawdown? DRILLER		
Address RT.I BOX IO4	Yield: 600 gal./min. with I5 ft. drawdown after 5 hrs.		
GERVAIS, OREGON.	_" 550 " I3 " 5 "		
(O) TOOLETTON ON THE PERSON OF	" 450 " 8 " 5 "		
(2) LOCATION OF WELL: County MARION Driller's well number 826	Bailer test gal./min, with ft. drawdown after hrs.		
	Artesian flow g.p.m. Date		
½ ½ Section T. 6 R. S R 3 _{W.M.}	Temperature of water Was a chemical analysis made? ☐ Yes ☐ No		
Bearing and distance from section or subdivision corner	The state of the s		
	(12) WELL LOG: Diameter of well below casing		
	Depth drilled 40 ft. Depth of completed well 40 ft.		
41	Formation: Describe by color, character, size of material and structure, and show thickness of aquifiers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.		
(3) TYPE OF WORK (check):	MATERIAL FROM TO		
Well ■ Deepening □ Reconditioning □ Abandon □	TOP SOIL 0 4 SANDY SILTY 4 12		
abandonment, describe material and procedure in Item 12.			
	SAND & GRAVEL I2 40		
(4) PROPOSED USE (check): (5) TYPE OF WELL:	BAL. OF PUMPING ON WELL		
Domestic Industrial Municipal Rotary Driven			
Irrigation Test Well Other Cable Jetted Dug Bored	400 G.P.M. 7 D.D. 5 HRS.		
	330 G.P.M. 4 D.D. 5 HRS.		
(6) CASING INSTALLED: Threaded □ Welded □			
"Diam, from ft. to ft. Gage	and the second of the second o		
TO Diam. from TOP ft. to 40 ft. Gage			
"Diam. from	and the second section of the section of		
(7) PERFORATIONS: Perforated? X Yes \(\square\) No			
Type of perforator used MILLS	the state of the s		
Size of perforations in. by in.			
230 perforations from 16 ft. to 39 ft.			
perforations from ft. to ft.	45.5		
perforations from ft. to ft.	A STATE OF THE STA		
perforations fromft. toft.	The state of the s		
perforations fromft. toft.			
(O) CODETING	219 Aug 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
(8) SCREENS: Well screen installed? ☐ Yes ♣No			
Manufacturer's Name	and the second s		
e Model No.	T. T. E. T.		
am. Slot size Set from ft. to ft.	Work started MAY IL 22 19 63 Completed MAY I5 1963		
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well MAY I5 1963		
(9) CONSTRUCTION:			
Well seal-Material used in seal CEMENT & PUTTLE CLAY	(13) PUMP:		
Depth of seal 18 ft. Was a packer used?	Manufacturer's Name		
Diameter of well bore to bottom of in.	Type: H.P.		
	Water Wall Contact of the Contact of		
* .	Water Well Contractor's Certification:		
Was a drive shoe used? Yes □ No	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was well gravel packed? Yes No Size of gravel:	and belief of my knowledge and belief.		
Gravel placed fromft_toft	NAME WILLAMETTE DRILLING CO.		
Did any strata contain unusable water?	(Person, firm or corporation) (Type or print)		
Type of water? Depth dstrata	Address RT. 2 BOX 276 SALEM, OREGON.		
Method of sealing strata off	Drilling Machine Operator's License No. 141		
(10) WATER LEVELS:	A CONTRACTOR S LICENSE No. 1771		
To **	[Signed] Child (), Belly		
outed 10702	(Water Well Contractor) Contractor's License No. 2 MAY 15 63		
	Date 10.		
(USE ADDITIONAL SH	EETS IF NECESSARY)		