

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED FEB 28 1969 STATE ENGINEER SALEM, OREGON

WATER WELL REPORT

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion (Please type or print) Do not write above this line)

State Well No. 6/3W-10

State Permit No.

(1) OWNER:

Name George Landrith
Address 1013 Simon Street N. Salem, Ore. 97303

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven []
Cable [X] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal []
Irrigation [X] Test Well [] Other []

CASING INSTALLED:

Threaded [] Welded [X]
12" Diam. from top ft. to 94 ft. Gage 250

(5) PERFORATIONS:

Perforated? [X] Yes [] No.

Type of perforator used Mills
Size of perforations 1/4 in. by 2 1/8 in.
912 perforations from 25 ft. to 92 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 17 ft. below land surface Date 2-24-69
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [X] Yes [] No If yes, by whom? Driller
Yield: 500 gal./min. with 1 ft. drawdown after 4 hrs.
600 " " 2 " " 4 "
700 " " 3 " " 4 "
Baller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? [] Yes [] No

(10) CONSTRUCTION:

Well seal—Material used Drill cuttings, Puddle Clay
Depth of seal 20 ft.
Diameter of well bore to bottom of seal 14 in.
Were any loose strata cemented off? [] Yes [X] No Depth
Was a drive shoe used? [X] Yes [] No
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Marion Driller's well number 1370
1/4 Section 10 T. 6S R. 3W W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing

Depth drilled 94 ft. Depth of completed well 94 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Top Soil, Yellow Clay, Gravel.

Work started 2-15-69 19 Completed 2-24-69 19
Date well drilling machine moved off of well 2-24-69 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Ronald W. Norton Date 2-24-69, 19
(Drilling Machine Operator)

Drilling Machine Operator's License No. 536

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME WILLAMETTE DRILLING COMPANY
(Person, firm or corporation) (Type or print)

Address 7641 35th Ave. NE (Rt. 2) Salem, Ore. 97303

[Signed] Emil O. Reiser
(Water Well Contractor)

Contractor's License No. 2 Date 2-24-69, 19