NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 9731
within 30 days from the date
of well completion.

STATE OF OREGON AUG 2 1973 State Well No. 65/3W-/4

(Do not write above this find LEM OREGGIA Permit No. .

(1) OWNER:	(10) LOCATION OF WELL:
Name Kenneth Moisan	County Marion Driller's well number 1756
Address 9155 Wheatland Road NE	14 14 Section 14 T. 6S R. 3W W.M.
Salem, Oragon 97303	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well → Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 19 ft.
Rotary Driven Domestic Industrial Municipal	4.1.1.1.1.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.
Cable Detted Detted Definestic Difficulties Detted	
□ Bored □ Irrigation ☑ Test Well □ Other □	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded □ Welded ☑	(12) WELL LOG: Diameter of well below casing
10" Diam. fromtop ft. to	Depth drilled 40 ft. Depth of completed well 40 ft.
	Formation: Describe color, texture, grain size and structure of materials;
"Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
(C) PEDEOD AUTONS.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
(6) PERFORATIONS: Perforated? Ex Yes \(\subseteq \text{No.} \)	
Type of perforator used Mills	
Size of perforations 7/66 in. by 2 3/4 in.	BLOWII, COP BOLL
200 perforations from 24 ft. to 40 ft.	DEOWII STEEY OZGY
perforations from ft. to ft.	Di Own Edday Serie
perforations from ft. to ft.	Brown sand and gravel 19 40
(7) SCREENS: Well screen installed? ☐ Yes ₺ No	
Manufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS. Drawdown is amount water level is	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ☑ No If yes, by whom?	
gal./min. with ft. drawdown after hrs.	
n n n	
n n n	
Bailer test 20 gal./min. with 6 ft. drawdown after hrs.	
dian flow g.p.m.	
Temperature of water Depth artesian flow encountered ft.	Work started July 27, 19 73 Completed July 30, 7319
	Date well drilling machine moved off of well July 30. 1973 19
(9) CONSTRUCTION:	
Well seal—Material used <u>Cement</u>	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Well sealed from land surface to ft.	Materials used and information reported above are true to my
Diameter of well bore to bottom of seal14 in.	best knowledge and belief.
Diameter of well bore below seal10. in.	[Signed] Date 7-31-73, 19
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No
Number of sacks of bentonite used in well sealsacks	
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	Name WILLAMETTE DRILTING COMPANY (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 7641 35th Ave. NE Salem, Oregon
- T	8 ON Rias
Method of sealing strata off	[Signed] (Water Well Contractor)
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	Contractor's License No. 2 Date 7-31-73 19
Gravel placed from	Contractor's License No Date/19 19