NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the WATER WELL REPORT OF OREGON 97310 WILLIAM 30 days from the date TATE ENGINEER, SALEM, OREGON 97310 William 30 days from the date TATE ENGINEER type or print)

15M 6/3w-₹

of well completion. SIAIE ENGINEER	G3167 State Fermit No.	
(1) OWNER: SALEM OREGON	(11) WELL TESTS: Drawdown is amount water level lowered below static level	vel is
Name CAPITOL FARMS INC.	Was a pump test made? X Yes \( \subseteq \text{No If yes, by whom? DR} \)	T.T.WP
Address RT. 2 BOX III	Yield: 600 gal./min. with 18 ft. drawdown after	
SALEM, OREGON	" <b>5</b> 00 " 8 "	20 "
(2) LOCATION OF WELL:	" "	"
	Bailer test gal./min. with ft. drawdown afte	er hrs.
County MARION Driller's well number 1022	Artesian flow g.p.m. Date	
1/4 1/4 Section 16 T. 6 S R. 3 W W.M.	Temperature of water Was a chemical analysis made?	Yes No
Bearing and distance from section or subdivision corner	(12) WELL LOG: Diameter of well below casing	
•		
		00 ft.
	Formation: Describe by color, character, size of material and si show thickness of aquifiers and the kind and nature of the mat stratum penetrated, with at least one entry for each change of	ructure, and erial in each
	stratum penetrated, with at least one entry for each change of	of formation.
	MATERIAL FROM	OT I
(3) TYPE OF WORK (check):	TOP SOIL 0	3
Well Deepening Reconditioning Abandon	BROWN CLAY 5	20
andonment, describe material and procedure in Item 12.	BROWN SAND & GRAVEL 20	25
(4) PROPOSED USE (check): (5) TYPE OF WELL:	BLACK SAND &FEW ROCKS & WOOD 25	80
(4) PROPOSED USE (check): (5) TYPE OF WELL:	BLUE CLAY 80	IOO
Domestic   Industrial   Municipal   Cable   Jetted		
Irrigation  ☐ Test Well ☐ Other ☐ Dug ☐ Bored ☐		
(6) CASING INSTALLED: Threaded ☐ Welded 🏋		
• • •		
TO Diam. from TOP ft. to TOO ft. Gage 250		
"Diam. from ft. to ft. Gage		
(7) PERFORATIONS: Perforated? XYes \( \square\) No		
Type of perforator used MILLS		
Size of perforations 2 in. by 3/8 in.		
perforations from 25 ft. to 95 ft.		
perforations from ft. to 95 ft.		
perforations fromft. toft.		
perforations fromft. toft.		
perforations from ft. to ft.		
(8) SCREENS: Well screen installed? ☐ Yes ▼ No		
Manufacturer's Name		
Model No.		
Diam. Slot size Set from ft. to ft. to ft. to ft.	Work started MAY I 19 65 Completed MAY I2	
	Date well drilling machine moved off of well MAY 12	<u>.965 <sup>19</sup> </u>
(9) CONSTRUCTION:	(13) PUMP:	
Well seal-Material used in seal CHMENT & PUDDLE CLA	Manufacturer's Name	
Depth of sealft. Was a packer used?	Type: H.P.	
Diameter of well bore to bottom of seal in.		
Were any loose strata cemented off? ☐ Yes ☐ No Depth	Water Well Contractor's Certification:	
Was a drive shoe used? → Yes □ No	This well was drilled under my jurisdiction and this report is	
Was well gravel packed?	true to the best of my knowledge and belief.	
Gravel placed fromft. toft.	NAME WILLAMETTE DRILLING CO	
Did any strata contain unusuable water? ☐ Yes ☐ No	(Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address RT. 2 BOX 276 SALEM, OREGON	
Method of sealing strata off	TET	=======================================
(10) WATER LEVELS:	Drilling Machine Operator's License No	
	[Signed] Comel O. Beier	
Static level 20 ft. below land surface Date 5/12/6	<b>4  </b>	
Artesian pressure lbs. per square inch Date	Contractor's License No. 2 Date MAY 12	<b>.96,5</b> <sub>19</sub>