STATE OF OREGON WATER WELL REPORT

OCT 2 0 1994

75	12w	/150	T.
TART CARD! #	68683	Da	_

	SOURCES DEPT. (START CARD) #	∠
(1) OWNER: Well Number SALEI		_
Name DAK-G -ARMS	County MHR 101 Latitude Longitude	
Address 3074 LANCASIER DR. NE #129	Township 75 N or S. Range ZW E or W. W.	
City SALEM State OR, Zip 97305	Section 15 SE 4 SE 4	1.
(2) TYPE OF WORK: New Well Deepen Recondition Abouter	Tax Lot 100 Lot Block Cultivity	
New Well Deepen Recondition Abandon (3) DRILL METHOD:	Street Address of Well (or nearest address) 7343 Sunayview A	īΕ
	97305	_
☐ Rotary Air ☐ Rotary Mud ☐ Cable ☐ Other	(10) STATIC WATER LEVEL:	<u> </u>
(4) PROPOSED USE:	ft. below land surface. Date 9-19-5	<u>)4</u>
Domestic Community Industrial Irrigation	Artesian pressure lb. per square inch. Date	
☐ Thermal ☐ Injection ☐ Other	(11) WATER BEARING ZONES:	
(5) BORE HOLE CONSTRUCTION:	Depth at which water was first found	
Special Construction approval Yes No Depth of Completed Well 229 ft.	The state of the s	
Explosives used Yes No Type Amount	From To Estimated Flow Rate SWI	
HOLE SEAL Amount	110' 190' 60+ CPM 55	77
Diameter From To Material From To sacks or pounds 14" 0' 36' CEMENT 0' 36' 25 SACKS		ı
14" 0 SG CEMENT 0' 36' 25 SACKS		\Box
	(12) WELL LOG:	_
How was seal placed: Method A B C C D D E	Ground elevation	
☐ Other	Material From To Curr	
Backfill placed from ft. to 6 ft. Material	BROWN CLAY 0' 29'	\dashv
Gravel placed from ft. to ft. Size of gravel	-Blue CLAY -DENSE 29' 34'	\dashv
(6) CASING/LINER:	LIGHT-BROWN SILTY CLAY 341 421	╛
Diameter From To Gauge Steel Plastic Welded Threaded Casing: 10° +2 229 250	BROWN CLAY - DENSE 42'52'	ヿ
Casing: 10 72 1250 12 11 12	- BROWN SILTY CLAY 52' 58'	
	- BROWN CLAY + BRANEL 581 661]
		4
Liner:	- (Day St.) Al 200	\mathbf{A}
	- BROWN SANDY CLAY 117' 118'	\dashv
Final location of shoe(s) Z29 ¹	-GRAVEL -CLAY 116' 120'	1
(7) PERFORATIONS/SCREENS: Perforations Method MILLS KNIÈE	- BROWN CLAY RO' 172'	1
	-GRANGL W/CLAY 1721 1821	1
Widecial	5 BROWN CLAY 137 136]
Slot Tele/pipe From To Stize Number Diameter size Casing Liner	-GRAVEL WICLAY GRAVES]
110' 190' 14x2' 1272 I	LARGE -SMALL SOME BROKEN	Н
	- BROWN CLAY W/ GRAVE 169' 171'	4
	-SMALL LRG, GRAVEL WY	┨
	BROWN CLAY	┨
	- GRAVEL SAND WLESSCLAN 181' 187' 55'	1
(8) WELL TESTS: Minimum testing time is 1 hour		1
_ Flowing	Date started HUG. 23, 94 Completed SEPT. 21, 94	_
☐ Pump ☐ Bailer ☐ Air ☐ Artesian	(unbonded) Water Well Constructor Certification:	=
Yield gal/min Drawdown Drill stem at Time	I certify that the work I performed on the construction, alteration, or abandon ment of this well in the construction of this well in the construction of the construction of the construction.	-
60GPM 4' 1 hr.	ment of this well Because State Ordiling (Inoc tion standards. Material used and informations of the property	S
	Keizer Orogon Ozagoniera	
	Kelzer, Oregon 97303 wwc Number	-
	(bonded) Water Well Constructor Certification:	:
Deput Artesian Flow Found	I accept responsibility for the construction, alteration, or abandonment work ac-	
to the solid this well during the construction dates reported above. All work newform		
Did any strata contain water not suitable for intended use? Too little	is true to the best of my knowledge and belief.	
Depth of ctmta:	WWC Number	ر
ODYGUNAY A FIRST COMMON TO THE COMMON THE COMMON TO THE CO	Signed William / Thoys Spor Date 9-25-94	•
SECONI	COPY - CONSTRUCTOR THIRD COPY - CUSTOMER 9809C 10/91	

OCT 201994

STATE OF OREGON

WATER WELL REPORTWATER RESOURCES DEP SALEM, OREGON (as required by ORS 537.765) SALEM9) QREGATION OF WELL by legal description: (1) OWNER: Well Number Name Bar - G County Latitude _Longitude N or S. Range, E or W. WM. Zip State City Section . ¼ _ 14 (2) TYPE OF WORK: Block Tax Lot Lot Subdivision. ☐ New Well ☐ Deepen Recondition Street Address of Well (or nearest address)_ Abandon (3) DRILL METHOD: (10) STATIC WATER LEVEL: ☐ Cable Rotary Mud Rotary Air Other _ ft. below land surface. (4) PROPOSED USE: Artesian pressure _ _ lb. per square inch. Date. (11) WATER BEARING ZONES: ☐ Domestic Community Industrial Irrigation ☐ Injection Other_ ☐ Thermal (5) BORE HOLE CONSTRUCTION: Depth at which water was first found Special Construction approval Yes No Depth of Completed Well_ Estimated Flow Rate SWL Explosives used Yes No Type_ From Amount_ HOLE Amount Material Diameter From To sacks or pounds (12) WELL LOG: Ground elevation How was seal placed: Method A □в \Box c Other _ GRAVE CL Backfill placed from ft. to ft. Material BROWN AY WISOME GRAN Gravel placed from_ ft. to_ Size of gravel 971204 (6) CASING/LINER: ROWN SOME SMALL GRAVEL Z04 Casing 2101 214 BROWN GRAY CLAY 214' 2191 22.9 BLUE CLAY Liner: Final location of shoe(s) (7) PERFORATIONS/SCREENS: ☐ Perforations Method ☐ Screens Material Туре Diam Line (8) WELL TESTS: Minimum testing time is 1 hour Date started Completed Flowing Artesian Bailer ☐ Pump ☐ Air (unbonded) Water Well Constructor Certification: I certify that the work I performed on the construction, alteration, or abandon-ment of this well is in contributed the construction, alteration, or abandon-Yield gal/min Drawdown Drill stem at Time used and informal 865 Women into the belief. 1 hr. Keizer, Oregon 97303 wwc Number Signed . Date (bonded) Water Well Constructor Certification: Depth Artesian Flow Found I accept responsibility for the construction, alteration, or abandonment work per-formed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon well construction standards. This report Did any strata contain water not suitable for intended use?

Too little is true to the less of my knowledge and belief. wwc Number_1273 Salty Muddy Odor Colored Other Signed Little Depth of strata: