WATER WELL REPORT STATE OF OREGON



REGEIVED

OCT 2 3 1984 Well No.

WATER RESOURCES PRETTO SALITA, OREGON

los	13w-	-aL	aa
6	942		

(1) OWNER:	(10) LOCATION OF WELL:	
Name Gordon Zielinski	County Marion Driller's well number 239	2
Address 1301 Mandarin St. N.E.	NE 1/4 NE 1/4 Section 24 T. 6S R. 3W	W.M.
City Salem, Oregon 97303 State	Tax Lot # Lot Blk Subdivi	
(2) TYPE OF WORK (check):	Address at well location: 8298 River Rd. N.E. Sa	lem
New Well X Deepening □ Reconditioning □ Abandon □ If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
	Depth at which water was first found 57	ft.
TYPE OF WELL: (4) PROPOSED USE (check):	Static level 41 ft. below land surface. Da	
ry Air 🔯 Driven 🗀 Domestic 💢 Industrial 🗆 Municipal 🗆 Rotary Mud 🗎 Dug 🖂 Irrigation 🖼 Test Well 🖂 Other	Artesian pressure lbs. per square inch. I	
Rotary Mud Dug	(12) WELL LOG: Diameter of well below casing	
(E) CIACIDIC INCOMIT FOR	(12) WELL LOG: Diameter of well below casing	110 _{ft.}
(5) CASING INSTALLED: Steel	Formation: Describe color, texture, grain size and structure of mater thickness and nature of each stratum and aquifer penetrated, with at for each change of formation. Report each change in position of Stat and indicate principal water-bearing strata.	rials; and show least one entry
LINER INSTALLED:	MATERIAL From To	SWL
	Topsoil 0	2
		26
(6) PERFORATIONS: Perforated? Ä Yes □ No Type of perforator used □ Torch		39
Type of perforation used Torch Size of perforations 1/2 in. by 6 in.		57
		99
		10
perforations fromft. toftperforations fromft. toft.		
(7) SCREENS: Well screen installed? Yes No		
Manufacturer's Name		
Type Model No		
Diam. Slot Size Set from ft. to ft.		
Diam. Slot Size Set from ft. to ft.		
WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? □ Yes ☒ No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		
test 150 gal./min. with drill stem at 105ft. 1 hrs.		
gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
Temperature of water Depth artesian flow encountered ft.	Work started 9/12/81 19 Completed 9/12/8	1 19
(9) CONSTRUCTION: Special standards: Yes □ No 🕅	Date well drilling machine moved off of well 9/12/81	19
Well seal—Material used Portland Cementand 5% bentonite	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct supervision. M	
Diameter of well bore to bottom of seal10 in.	and information reported above are true to my best knowledge	
Diameter of well bore below seal	[Signed]	.2/819
Number of sacks of cement used in well seal	Drilling Machine Operator's License No	
How was cement grout placed? Pumped in thru conductor pipe		·
	Water Well Contractor's Certification: This well was drilled under my jurisdiction and this rep	
Was pump installed? Type HP Depth ft.	the best of my knowledge and belief.	
Was a drive shoe used? ☐ No Plugs	Name WILLAMETTE DRILLING CO. (Ty)	• • • • • • • • • • • • • • • • • • • •
was a drive snoe used?	(Person, firm or corporation) (Ty	pe or print)
Type of Water? depth of strata	Address .7365. O'Neil Rd. N.E. Salem, Oreg	on9/30
Method of sealing strata off	[Signed] Lillad Lillage (Water Well Contractor)	
Was well gravel packed? ☐ Yes X No Size of gravel:	(Water Well Contractor)	
Cravel placed from	Contractor's License No561Date9/12/81	, 19



x-1