M (R1.5148

6/3W-24 State Well No.

State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount we lowered below static level	ater level is	
Name ROBERT ZIELINSKI	Was a pump test made? ▼ Yes □ No If yes, by whom?		
Address RT.I BOX ZFG 59	Yield: 450 gal./min. with 83 ft. drawdown	after 🛕 hrs.	
GERVAIS, OREGON.	<u>" 400 " 74 "</u>	4 "	
(2) LOCATION OF WELL:	<u>" 370 " 69 "</u>	4 "	
County MARION Driller's well number II46	Bailer test gal./min. with ft. drawdow	vn after hrs.	
14 14 Section 24 T. 6 R 5 R. 3 W W.M.	Artesian flow g.p.m. Date	-d-0 C X C N-	
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis ma		
WELL DRILLED AT RT.2 BOX 270	(12) WELL LOG: Diameter of well below casi	_	
SALEM, OREGON.	Depth drilled I34 - IOTDepth of completed well		
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of th stratum penetrated, with at least one entry for each cha	and structure, and e material in each inge of formation.	
	MATERIAL	FROM TO	
(3) TYPE OF WORK (check):	TOP SOIL	0 3	
Yew Well Deepening □ Reconditioning □ Abandon □	YELLOW CLAY	3 20	
bandonment, describe material and procedure in Item 12.	SILTY YELLOW CLAY	20 45	
(4) PROPOSED USE (check): (5) TYPE OF WELL:	BROWN FINE SAND	45 60	
Domestic Industrial Municipal Rotary Driven	BROWN SAND SMALL PEA GRAVEL	60 65	
rrigation Test Well Other Cable To Jetted	A LETTLE LARGER GRAVEL & SAND	65 80	
Dug 📙 Bored 📙		CARREST X	
(6) CASING INSTALLED: Threaded Welded	BLACK WASHED GRAVEL & SAND LOO		
"Diam from	BROWN TIGHT SAND & GRAVEL LOCAL BROWN SAND & GRAVEL BROWN &		
Diam. fromft. toft. Gage	BROWN SAND & CRAVEL LOOSE BLACK SHALE	115 134 134-10"	
" Diam. from ft. to ft. Gage	Distoit Official	104-10	
(7) PERFORATIONS: Perforated? XYes \(\square\) No			
Type of perforator used MILLS			
Size of perforations 3/8 in. by 2 in.			
580 perforations from 70 ft. to BOTTOM ft.			
ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? ☐ Yes To No			
Manufacturer's Name			
Model No.		1	
n Slot size Set from ft. to ft.	Work started MAY 17 1966 Completed JUN	E II 1966	
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well JUNE	_	
(9) CONSTRUCTION: DRLLL	(13) PUMP:		
CUTTING	(10) 1 01111.		
Well seal—Material used in seal PUTTLE CLAY &	Manufacturer's Name		
Depth of seal ft. Was a packer used? Diameter of well bore to bottom of seal IO in.	Type: H.P.		
Were any loose strata cemented off? \(\sigma\) Yes \(\sigma\) No \(\text{Depth}\) Depth	Water Well Contractor's Certification:		
Was a drive shoe used? Yes □ No Depth Was a drive shoe used? Yes □ No	This well was drilled under my jurisdiction a	nd this renort is	
Was well gravel packed? ☐ Yes Mo Size of gravel:	true to the best of my knowledge and belief.	.ic with report to	
Gravel placed from ft. to ft.	NAME WILLAMETTE DRILLING CO.		
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address RT.2 BOX 276 SALEM, OREGON.		
Method of sealing strata off	Drilling Washing Operator's License No. 7	4	
(10) WATER LEVELS:	Drilling Machine Operator's License No.		
	[Signed] Comel U. Bell	2	
Static level 36 ft. below land surface Date 6/II/66	(Water Well Contractor)	I. 1066	
Artesian pressure lbs. per square inch Date	Contractor's License No. Date	19.00	