

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

RECEIVED
WATER WELL REPORT

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

STATE OF OREGON MAY 24 1977 State Well No. 65/NW-25

(Please type or print)

WATER RESOURCES DEPT.
SALEM, OREGON State Permit No. _____

(1) OWNER:

Name Fred and Genevieve Hug
Address Rt. 1 Box 108
Mt. Angel, Oregon 97362

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
8" Diam. from top ft. to 141 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.
Type of perforator used Mills Knife
Size of perforations 3/8 in. by 2 3/4 in.
896 perforations from 90 ft. to 139 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name _____
Type _____ Model No. _____
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.
Diam. _____ Slot size _____ Set from _____ ft. to _____ ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? driller
Yield: 500 gal./min. with 9 ft. drawdown after 2 hrs.
" " " " "
" " " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.

Temperature of water 53° Depth artesian flow encountered _____ ft.

(9) CONSTRUCTION:

Well seal—Material used Portland Cement
Well sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 11 sacks
How was cement grout placed? Poured in from the Top

Was a drive shoe used? Yes No Plugs _____ Size: location _____ ft.
Did any strata contain unusable water? Yes No
Type of water? _____ depth of strata _____
Method of sealing strata off _____
Was well gravel packed? Yes No Size of gravel: _____
Gravel placed from _____ ft. to _____ ft.

(10) LOCATION OF WELL:

County Marion Driller's well number 2036
1/4 1/4 Section 25 T. 6S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 60 ft.
Static level 43 ft. below land surface. Date 5/6/77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing _____
Depth drilled 141 ft. Depth of completed well 141 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Topsoil	0	2	
Brown Clay	2	60	
Brown Sand	60	73	
Brown Sandy Gravel	73	85	
Brown Sand and Gravel	85	141	

Work started 5/3/77 19 Completed 5/6/77 19
Date well drilling machine moved off of well 5/6/77 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Dallas L. Davis Date 5/7/77, 19____
(Drilling Machine Operator)
Drilling Machine Operator's License No. 752

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Willamette Drilling Co. (Type or print)
(Person, firm or corporation)
Address 1450 Barnick Rd. NE Salem, Oregon 97303
[Signed] Dallas L. Davis (Water Well Contractor)
Contractor's License No. 561 Date 5/7/77, 19____