The original and first copy with of this report are to be filed with the	L REPORTEGEIVED	65/34	v-25
state engineer, salem, oregon 97310 \ D 35th Aug (Please type within 30 days from the date - par Harold (Do not write at of well completion)	OREGON MAR 15 1976 State Well No.	. 6-68	96
of well completion, harold (Do not write at	ove this line SALEM, OREGON	V	***************************************
TWIND CICISICAL ATTV "101"	OTOS TALLIN, CIRECON		
(1) OWNER: 5/94	(10) LOCATION OF WELL:		,
Name Gary Hollin	County Marton Driller's well nu		6
Address 3815 Quinaby Rd. NE		R. 3W	W.M.
Datom, Vickori 7, No.	Bearing and distance from section or subdivision corner		
New Well Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 55 ft.		
Rotary □ Driven □ Domestic □ Industrial □ Municipal □	Static level 29 ft. below land surface. Date 3/1/76		
Cable 😿 Jetted 🗆 Irrigation 🛣 Test Well 🗆 Other	Artesian pressure lbs. per squar		
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well is	oelow casing	
10	Depth drilled 126 ft. Depth of completed well 126 ft.		
ft. Gage ft. Gage	Formation: Describe color, texture, grain size		
ft. Gage	and show thickness and nature of each stratus	m and aquife	r penetrated
PERFORATIONS: Perforated? My Yes I No.	with at least one entry for each change of forma position of Static Water Level and indicate prin		
	MATERIAL		ro SWL
		 	
Size of perforations 7/16 in. by 2 3/4 in.	Top soil		2
210 perforations from 60 ft. to 75 ft. 546 perforations from 85 ft. to 124 ft.	Brown silty clay	2 5	
2010/2010/2010	Brown sand and Gravel, clay Brown sandy clay	55 7 76 8	
perforations from ft. to ft.	Brown sand and gravel	82 10	
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	Brown gravelly clay (water)	106 12	
Manufacturer's Name	Brown graverry Cray, (water)	100 12	9
Type Model No		 	
Diam, Slot size Set from ft, to ft.		1	
Diam Slot size Set from ft. to ft.	,	<u> </u>	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes ☐ No If yes, by whom? Driller			
Yield: 300 gal./min. with 18 ft. drawdown after 1 hrs.			
500 " 53 " 1 "			
" 650 " 75 " 1 "			
· · · · · · · · · · · · · · · · · · ·			
Bailer test gal./min. with ft. drawdown after hrs.		 	
Artesian flow g.p.m.			
nperature of water 53 Depth artesian flow encountered ft.	Work started 2/17/76 19 Complet	$\frac{3}{1}$	6 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3/1/7	6 19
	Drilling Machine Operator's Certification:		
Well seal—Material used Portland Cement	This well was constructed under my		pervision
Well sealed from land surface toft.	Materials used and information reported best knowledge and belief.	above are	true to my
Diameter of well bore to bottom of seal14 in.			
Diameter of well bore below seal	(Drilling Machine Operator)		
Number of sacks of cement used in well seal sacks Number of sacks of bentonite used in well seal	Drilling Machine Operator's License No. 75.2		
			.
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons of water	This well was drilled under my jurisdiction and this report is		
of water lbs./100 gals. Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water? Yes No	Name Willamette Drilling Co. (Person, firm or corporation) (Type or print)		
	Address 1450 Barnick rd. NE Salem, Oregon 97303		
	011.00-		essessatededicted
Method of sealing strata off	[Signed] Dellas L Dellas		••••
Was well gravel packed? Tyes My No Size of gravel:	(Water Well Contr		
Gravel placed from ft. to ft.	Contractor's License No. 561 Date	2/1/76	, 19