NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 STATE O within 30 days from the date of well completion.	F OREGON pe or print) G-3928 State Permit No
(1) OWNER: CALEM. UREGON	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Name ARNOLD NICOLET	lowered below static level
Address 21319 WARD DRIVE M.F.	Was a pump test made? ☐ Yes ☐ No If yes, by whom?  Yield: 400 gal./min. with /6 ft. drawdown after / h
SALEM ORC.	" 600 " 21.
(2) LOCATION OF WELL:	" " "
1100	Bailer test gal./min. with ft. drawdown after h
County MIRICH Driller's well number  4 Section 36 T. 65 R. 360 W.M.	Artesian flow g.p.m. Date
Bearing and distance from section or subdivision corner	Temperature of water 500 Was a chemical analysis made?  Yes
	(12) WELL LOG: Diameter of well below casing
	Depth drilled /Cf' ft. Depth of completed well
	Formation: Describe by color, character, size of material and structure, a
75/0	Formation: Describe by color, character, size of material and structure, a show thickness of aquifers and the kind and nature of the material in eastratum penetrated, with at least one entry for each change of formation
	MATERIAL FROM TO
(3) TYPE OF WORK (check):	TOPS016 0 2
Well Deepening Reconditioning Abandon	CLAY BLUE STICKY 2 7
endonment, describe material and procedure in Item 12.	CLAY YELLOW 7/17
(4) PROPOSED USE (check): (5) TYPE OF WELL:	SAND BROWN- FINE BRAIN 17 22
Domestic □ Industrial □ Municipal □ Rotary □ Driven □	SAMO + CRAVEL 60% SAMO 22 38
Irrigation X Test Well   Other   Cable Z Jetted	ERAVEL 8"- +(SAND.10%) WB 38 50
Dug Dug Bored	CONGLONERATE 50 60
(6) CASING INSTALLED: Threaded  Welded	CLAY YELLOW SANDYWB. 60 65 CONGLAMPENTE
	CONGLOMERATE 65 68 CRAVEL Z"- 68 78
"Diam. from ft. to ft. Gage ft	CONGLOMERATE 78 96
"Diam. from ft. to ft. Gage ft. Gage ft. To ft. Gage ft. Gage	GRAVEL 2"- 96 100
(7) PERFORATIONS: Perforated? Yes \( \square\) No	
Type of perforator used MILLS	
Size of perforations in. by 2 2. in.	
350 perforations from 42- ft. to 58 ft.	
perforations from ft. to ft	
perforations from ft, to ft.	
(0) CODEENS.	
wen screen histaned? [] Tes [] No	
Manufacturer's Name	
1 Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	Work started 4-15- 1967 Completed 4-20- 196
(9) CONSTRUCTION:	Date well drilling machine moved off of well 19
	(13) PUMP:
Well seal-Material used in seal Benrumire	Manufacturer's Name
Depth of seal 25 ft. Was a packer used?	Type:
Diameter of well bore to bottom of seal	Water Well Contractor's Certification:
Were any loose strata cemented off? ☐ Yes 🖪 No Depth	
Was well gravel packed?  Yes No Size of gravel:	This well was drilled under my jurisdiction and this report true to the best of my knowledge and belief.
Gravel placed fromft.	
Did any strata contain unusable water? ZYes  No	NAME J. A. S.N. E. E. J. SONS (Person, firm or corporation) (Type or print) Address 3910 SIL URETOH RD, SALON OR
Type of water? SHHUY depth of strata &C'TC &S'	Address 5910 SILVERTON RD, SALON OR
Method of sealing strata off	Drilling Machine Onewstow's Times No. 187
(10) WATER LEVELS:	Drilling Machine Operator's License No.
	[Signed]
Static level / ft. below land surface Date 4-20-67	(Water Well Contractor)
Artesian pressure lbs. per square inch Date	Contractor's License No. 6 Date 4-95-, 19.6