File Original and First Copy with the STATE ENGINEER, SALEM, OREGON



WATER WELL REPORT STATE OF OREGON (954

State Permit No. 6814

(1) OWNER: Name Wilmon G. Peterson Address Troute 4 Box 62		(11) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? Yes No If yes, by whom?			
		Yield: gal./min. with ft. drawdow			
Salem. ORegon		, gaz,/min.	, , ,	rai dator	**
		» »	- , **		,,
(2) LOCATION OF WELL:		Bailer test 35 gal./min.	with 2 ft. drawdow	n after	2 hrs.
County Marion Owner's number, is NE 34 NE 34 Section 26 T. 65	0 707	Artesian flow	g.p.m. Date		
		Temperature of water 57	Was a chemical analysis m	ade? 🗌 Y	es □ X o
Bearing and distance from section or subdivision corn		(40) ******** * 0.0		6	
North 89 deg. 55' West 300 f 80 feet from the NE corner of		. ,	Diameter of well		
26 in T.6 S.; Range 3 West	of Willemott		ft. Depth of completed v		ft.
Teridian in Marion County,	Oregon	snow tnickness of aquifers ar	r, character, size of materi id the kind and nature of	ai ana stru the mater	icture, and ial in each
mentoran in maintain country	, <u>01.68.011</u>	stratum penetrated, with at	least one entry for each	1	jormation.
Part I was a second of the sec		MATER		FROM	TO
(3) TYPE OF WORK (check):		Top So		0	2
New Well 🛣 Deepening 🗌 Reconditioning		r clay	2	48	
reabandonment, describe material and procedure in I	tem 11.	Brown	sand & clay	48	70
PROPOSED USE (sheets). (5) W	VDE OF WELL.	Brown	sand & Grave:	1 70	110
	YPE OF WELL:		· · · · · · · · · · · · · · · · · · ·	-	
Domestic Industrial Municipal Cable	· · · · · · · · · · · · · · · · · · ·				
Irrigation Test Well Other Dug	☐ Bored ☐	-			
(A) CACTNG INCHALLED.					
(-/	□ Welded □			-	-
6 "Diam. from Top ft. to 109! -				_	
" Diam, from ft, to	***			_	<u> </u>
" Diam. from ft. to	. ft. Gage			_	
(7) PERFORATIONS: Perforated	l? 🛮 Yes 🗆 No			-	
Type of perforator used Mills	_		CEIMBE .	·	
SIZE of perforations in. by 1	in.			il	
140 perforations from 75 ft	to 108 ft.	U	311 [34-195 8] E		
perforations from ft			-	<u> </u>	
perforations fromft	to ft.			-	-
perforations from ft					
perforations from ft.		-			
			······································	_	
(8) SCREENS: Well screen installed	. □ Yes □ X Yo			_	
Manufacturer's Name				-	
Type Model I	¥o			 	
Slot size Set from	ft. to ft.			<u> </u>	
Dan, Slot size Set from	ft. to ft.	Work started June 3	1958. Completed	June S	9 <u>, 19 5</u> 8
(a) CONCEDICEION.		/19\ DIIMD.			
(9) CONSTRUCTION:	nya] ı	(13) PUMP:			
Was well gravel packed? Yes Size of gravel:		Manufacturer's Name	· · · · · · · · · · · · · · · · · · ·		
Gravel placed fromft. toft. Was a surface seal provided? X Yes \(\sum \) No To what depth?ft.		Type:		H.P	
Material used in seal— Puddled Clay	Well Driller's Statement:	•			
Did any strata contain unusable water? Yes	Ö	1	under my jurisdiction	and this	roport is
Type of water? Depth of strata		true to the best of my kno		and uns	report is
Method of sealing strata off		Rm47	O. Beier		
		INAME		Type or pri	int)
(10) WATER LEVELS:		Address 7555 O'Neil Road Salem, Oregon			
Static level 38 ft. below land surface Date 6-9-58		· ·			
Artesian pressure lbs. per square inc	h Date	Driller's well number	421		
I og Acconted by:		5 .	m R:		
Log Accepted by:	me 1/ 1955	[Signed]	(Well Driller)		
[Signed H Gran Ille lessone s	V 89	•	1-58	10	
(Owner)		License No	Date	~ <u>~</u> ~≎0\$, 19