The original and first copy of this report are to be filed with the MAY 29 1970 FATE OF OREGON (Please type or print) within 30 days from the date of well completion.

MARI...34 State Permit No.

(1) OWNER:	(11) LOCATION OF WELL:			
Name (I) ARREN GRIM	County MARION Driller's well number 40			
Address R4 1 Box 70 L WOOdBORN, DRE	14 14 Section / 5 T. 45 R. /// W.M.			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well   Deepening □ Reconditioning □ Abandon □	-			
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):				
Rotary G Driven G	(12) WELL LOG: Diameter of well below casing			
Cable Jetted Domestic Industrial Municipal	Depth drilled 195 ft. Depth of completed well 147 ft.			
Dug	Formation: Describe color, texture, grain size and structure of materials;			
CASING INSTALLED: Threaded  Welded	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change			
8 " Diam. from 0 ft. to 147 ft. Gage 250	in position of Static Water Level as drilling pro			
ft. Gage ft. Gage	MATERIAL	From	То	SWL
" Diam. from ft. to ft. Gage	BROWN TOP SOIL	0	1	
PERFORATIONS: Perforated? For I No.	BROWN CLAY	1	24	*
	BROWN SANDY CLAY	26	54	
	BLUE CLAY	54	91	
Size of perforations 3/8 in. by 3/4 in.	BLACK SAND & GRACEL	91	92	
24 perforations from 1.23/2 ft. to 1.25 ft.	BLUE CLAY	92	90	
perforations from ft. to ft.	BLACK SANCE	00	101	
perforations from ft. to ft.	BING CLAY	101	109	
perforations from ft. to ft.	FINE BLACK SAND AND	100	111	
perforations from ft. to ft.	GRAUGL	1.62		<del>,</del>
(E) CODETING	BLUE GLAY	111	111	
(7) SCREENS: Well screen installed?   Yes The No	BLACK SAND + FINE	115	123	4.7
Manufacturer's Name	GRAVEL	773	Z = 4-3	<u> </u>
Type Model No.	GRAVEL MED.	mall	سے در	<del>-</del>
Diam Slot size Set from ft. to ft.		113/1	190	
Diam. Slot size Set from ft. to ft.	BLACK CLAY	190	195	
(8) WATER LEVEL: Completed well.	E)CHILED & COTT	770	770	<del></del>
Static level 42 ft. below land surface Date 5/20/70				
tesian pressure lbs. per square inch Date				
(9) WELL TESTS: Drawdown is amount water level is				
lowered below static level	,			
Was a pump test made? Yes \( \subseteq No \) If yes, by whom?	Work started 5/17 1970 Complet		5/20	10
eld: 100 gal./min. with 40 ft. drawdown after 4 hrs.			<del>,                                     </del>	1970
n n	Date well drilling machine moved off of well	3/6	20	19 76
" " "	Drilling Machine Operator's Certification:			
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my directed and information reported above	rect sup	ervision.	Mate-
Artesian flow g.p.m. Date	knowledge and belief			113 5050
Temperature of water 540 Was a chemical analysis made?   Yes No	[Signed] Welleand Montagate 5120, 1970			
(10) CONSTRUCTION:	(Drilling Machine Operator)		<b>~</b> ~	
Well seal-Material used BENGINIEC CLASS + ORILL CU	Drilling Machine Operator's License No.	<b>.</b>	رياب	
56	Water Well Contractor's Certification:			
10				
Diameter of well bore to bottom of sealin,	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Were any loose strata cemented off?  Yes No Depth	NAME WILLIAM D Christenson			
Was a drive shoe used? FYes I No	(Person, firm or corporation) (Type or print)			
Did any strata contain unusable water?   Yes PNo	Address P.O. BOX 343 Habbared &			
Type of water? depth of strata				
Method of sealing strata off	[Signed] William & Wick Dans			
Was well gravel packed?  Yes No Size of gravel:	(Water Well Contract	tor)		······································
Gravel placed from ft. to ft.	Contractor's License No. 511. Date	5/2	0	19.70