ORIGINAL File Original and	LL REPORT 5349 State Well No. 6/3W - 28M(3)
Duplicate with the STATE ENGINEER, SALEM, OREGON	
(1) OWNER: STATE ENGINEER	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Name Mr. B.E.Stratton ON	lowered below static level Was a pump test made? Yes No If yes, by whom?
Address Route 2.Box 55	Yield: gal./min. with ft. drawdown after hrs.
Salem, Oregon	j n n n
(2) LOCATION OF WELL: 7	" " " " " " " " " " " " " " " " " " "
County Marion Owner's number, if any—	Bailer test gal./min. with ft. drawdown after hrs.
NW 1/4 SW 1/4 Section 28 T. 6 S. R. 3 W. W.M.	Artesian flow g.p.m. Date
Bearing and distance from section or subdivision corner	Temperature of water 57 Was a chemical analysis made? Yes No
2547.7 ft. North and 436.9 ft. East	(12) WELL LOG: Diameter of wellinches.
from the SW. corner of Section 28,	Depth drilled 28 ft. Depth of completed well 28 ft.
I.6 S. ,R.3 West. in Marion County, Orego	A Formation: Describe by color, character, size of material and structure, and show thickness of aguifers and the kind and nature of the material in each
	stratum penetrated, with at least one entry for each change of formation.
	MATERIAL FROM TO
TYPE OF WORK (check):	
New Well	Sandy Loam 0 7
If abandonment, describe material and procedure in Item 11.	Brown Sand & Gravel 7 28
(4) PROPOSED USE (check): (5) TYPE OF WELL:	
nestic Industrial Municipal Rotary Driven	
Test Well □ Other □ Dug □ Bored □	
A	
(6) CASING INSTALLED: Threaded □ Welded	
12" Diam. from	·
"Diam from ft. to 28 ft. Gage	
"Diam. from ft. to ft. Gage	
(7) PERFORATIONS: Perforated? X Yes \square No	
Type of perforator used Acet. Torch	
SIZE of perforations 1/2 in. by 6 in.	
perforations from ft. to ft.	
120 perforations from 17 ft. to 27 ft.	
perforations fromft. toft.	
perforations fromft. toft. perforations fromft. toft.	
perforations from	
SCREENS: Well screen installed Yes No	
anufacturer's Name	
Type Model No.	
Diam. Slot size Set from ft. to ft.	Work started May 29 1957. Completed June 4 1957
Diam. Slot size Set from ft. to ft.	Work started May 29 1957. Completed June 4 1957
CONSTRUCTION:	(13) PUMP:
Was well gravel packed? Yes No Size of gravel:	Manufacturer's Name
Gravel placed from ft. to ft.	Type: H.P.
Was a surface seal provided? Yes No To what depth?	
Material used in seal— Did any strata contain unusable water? ☐ Yes 🛣 No	Well Driller's Statement:
Type of water? Depth of strata	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Method of sealing strata off	No. 10 Telescope and 10
	NAME Wymore (Person, firm, or corporation) (Type or print)
(10) WATER LEVELS: Static level 4 ft below land surface Data 6/4/57	Address Rt.2 Salem, Oregon
Static level ft. below land surface Date Artesian pressure lbs. per square inch Date	
ins. per square men Date	Driller's well number 345
Log Accepted by:	[Signed] // / Wymor
[Signed] Byon L. Stretton Date June 10 , 1987	(Well Driller)
(Owner)	License No. 24 Date June 5,19579
· (USE ADDITIONAL S	HEETS IF NECESSARY)