## **RECEIVED**

MARIA 53919

STATE OF OREGON 5 2

APR 0 8 1999

WELL I.D. #L 27832 START CARD # 1/8488

| (as required by ORS 537.765)  MATER RESOUR  Instructions for completing this report are on the last page of bisforms. OR | CES DEPT. START CARD # _//8488  |
|--|---|
|  |   |
| (1) OWNER: Name Family Head Start  | (9) LOCATION OF WELL by legal description:  County Mario M Latitude Longitude   |
| Address 2455 Franzen Street NE   | Township 6-S N or S Range 3-W E or W. WM.   |
| City Solem State OR Zip 9730   | Section 2 4 NW 1/4 NE 1/4   |
| (2) TYPE OF WORK   |   |
| New Well Deepening Alteration (repair/recondition) Abandonment   | Tax Lot 1700 Lot Block Subdivision  Street Address of Well (or nearest address) 8485 River Rd   |
| (3) DRILL METHOD:  | NE Keizer OR 97303  |
| Rotary Air Rotary Mud Cable Auger  | (10) STATIC WATER LEVEL:  |
| Other  | 24 ft. below land surface. Date $2-19-90$   |
| (4) PROPOSED USE:  | Artesian pressure lb. per square inch. Date   |
| Domestic  Community  Industrial  Irrigation  | (11) WATER BEARING ZONES:   |
| Thermal Injection Livestock Other  | 13  |
| (5) BORE HOLE CONSTRUCTION:  | Depth at which water was first found/3  |
| Special Construction approval Yes No Depth of Completed Well 139 ft.   | To Estimated Flow Date (SMT)  |
| Explosives used Yes No Type Amount  HOLE SEAL  | From To Estimated Flow Rate SWL   |
|  |   |
| Diameter From To Material From To Sacks or pounds 10 0 42 Cement 0 42 34+ bent   |   |
| 10 0 12 CEVILENT O 12 STYLES   | 48 139 100 + 24   |
| 6 42 139   |   |
|  | (12) WELLLOC.   |
| How was seal placed: Method A B C D E  | (12) WELL LOG: Ground Elevation   |
| Other  |   |
| Backfill placed from ft. to ft. Material   | Material From To SWL  |
| Gravel placed from ft. to ft. Size of gravel   | Fill Material 0 1   |
| (6) CASING/LINER:  | Brown Clay 1 13   |
| Diameter From To Gauge Steel Plastic Welded Threaded   | Silty brown Clay 13 36  |
| Casing: 6; n 7.5 /39 .25 \ \( \bar{2} \)                         | Brown Clay with   |
|  | trace of grave 36 48  |
|  | Black runny Sand 48 73  |
|  | Black Sand + gravel 73 105  |
| Liner:   | Brown Sand + grave  |
| Final location of shoe(s)  | Clau 105 /22  |
|  |   |
| (7) PERFORATIONS/SCREENS:  | Brown Sand + grave (  |
| Perforations Method  | Loose grave brown   |
| Slot Tele/pipe   | and black 135 139   |
| From To size Number Diameter RECEIVED Liner  | and black 135 139   |
|  |   |
|  |   |
| JUN 7 1999   |   |
| WATER RESOURCES DEPT   |   |
| SALEM, OREGON  |   |
| (8) WELL TESTS: Minimum testing time is 1 hour   | Date started $2-16-99$ Completed $2-19-99$  |
| Flowing  | (unbonded) Water Well Constructor Certification:  |
| ∏Pump ☐Bailer ☒Air ☐Artesian   | I certify that the work I performed on the construction, alteration, or abandonment   |
| Yield gal/min Drawdown Drill stem at Time  | of this well is in compliance with Oregon water supply well construction standards.  Materials used and information reported above are true to the best of my knowledge |
| 100 t 13.5 1hr.  | and belief.   |
|  | WWC Number 1703   |
|  | Signed Date 2-28-99   |
| Temperature of water Depth Artesian Flow Found   | (bonded) Water Well Constructor Certification:  |
| Was a water analysis done? Yes By whom  Did you state a patric water act suitable for intended was?  Too little          | I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. All work             |
| Did any strata contain water not suitable for intended use? Too little   | performed during this time is in compliance with Oregon water supply well   |
| Salty Muddy Odor Colored Other   | construction standards. This report is true to the best of my knowledge and belief.   |