NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

filed with the STATE ENGINEER, SALEM, OREGON 97411 within 30 days from the date of well completion.

WATER WELL REPORT GEIVE

STATE OF OREGON JUL 261973 State Well No. 653W-34

(Please type or print) TATE ENGINEEP

Do not write above this line). (Please type or print) TATE ENGINEER

(Do not write above this lime) ALEM OREGON Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name MENARY OAKS TRAILER VILLA	County MARION Driller's well number 5448
Address 53.55 RIVER ROAD NORTH	NE 1/4 SE 1/4 Section 34 T. 65 R. 3 W W.M.
SALEM ORE.	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	bearing and distance from section of subdivision corner
New Well M Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	(44) TVI TVI
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
	Depth at which water was first found 83 ft.
Rotary Driven Domestic Mindustrial Municipal Domestic	Static level 30 ft. below land surface. Date 7//7/73
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	
· · · · · · · · · · · · · · · · · · ·	(12) WELL LOG: Diameter of well below casing
8" Diam from + 2 ft to 130 ft Gage 277	Depth drilled 130 ft. Depth of completed well 130 ft.
"Diam. from	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used STAR	
2/9/1/	MATERIAL From To SWL
Size of perforations 3/8 in. by //4 in.	70P SOIL 03
200 perforations from 85 ft. to 75 ft.	BROWN SANDY (LAY 3 18
380 perforations from $1/c$ ft. to 125 ft.	CLAY AND GRAVEL 18 50
perforations from ft. to ft.	CEMENTED GRAVEL SO 85
(7) SCREENS: Well screen installed? The Well screen installed?	SAND AND GRAVEL (WATER) 85 95
(7) SCREENS: Well screen installed? Yes No Manufacturer's Name	SAND GRAVELAND GAY 95 105
	CEMENTED GRAVEL 105 110
Type Model No.	SAND AND GRAJEL WATER 110 125
Diam. Slot size Set from ft. to ft.	CEMENTED GRAVEL DS 130
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes \(\subseteq No \) If yes, by whom? \(STRASSER \)	
Yield: 7/0 gal./min. with 34 ft. drawdown after 24 hrs.	
n n	
" " " "	
Bailer test gal./min. with ft. drawdown after hrs.	
A-1-1-0	
Artesian flow g.p.m.	
perature of water 54 Depth artesian flow encountered ft.	Work started JULY 2 1973 Completed JULY 20 1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well July 20 1973
15 M 5 77 6 2017	
Wen bear inducting about	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Well sealed from land surface to	Materials used and information reported above are true to my
**</td <td>best knowledge and belief</td>	best knowledge and belief
Diameter of well bore below seal	[Signed]
sacks	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? XYes \(\subseteq \) No Plugs Size: location ft.	Name RISTRASSER DRILLING CO
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 8110 SE SUNSET LAVE PORTLAND ORE.
Method of sealing strata off	PINT
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contractor)
1	
Gravel placed fromft. toft.	Contractor's License No. 10 Date 1025 23, 1973