NOTICE TO WATER WELL CONTRACTOR.

The original and first popy of this report are to be JUL 15 1969 WATER WELL REPORT filed with the STATE OF OREGON STATE ENGINEER, SALEM, OREGON 97810 WILLIAM (Please type of pint) / UG 1 5 1969 within 30 days from the date. IN OREGON (Do not write above this line) of well completion.

Se Well No. 6/3W-340r35

STATE ENGINEER Permit No. ...

	BALLIM WASANGON			<u> </u>
(1) OWNER:	(11) LOCATION OF WELL:			
Name Wallace D. Voigt	County Marion Driller's well n	umber 1	413	
Address 1016 Ventura North Salem, Oregon	¼ ¼ Section34_35 T. 6S			W.M.
TOTAL VEHICULA NOI LIL GATEM, OLEGOR	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):	Dearing and distance from Bootton of Bandariose			
New Well 🕱 Deepening 🗌 Reconditioning 🗍 Abandon 🗍				
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well	below casi	ng	
Cable X Jetted Domestic X Industrial Municipal	Depth drilled 137 ft. Depth of comp	eted well	137	ft.
Dug	Formation: Describe color, texture, grain size	and struct	ure of m	aterials;
CASING INSTALLED: Threaded □ Welded X	and show thickness and nature of each stratu with at least one entry for each change of forn			
	in position of Static Water Level as drilling pr			
ft. to ft. Gage	MATERIAL	From	то	SWL
ft. to ft. Gage	Top Soil	0	1	
PERFORATIONS: Perforated? ☑ Yes ☐ No.	Yellow Clay	2	6	
	Brown clay	6	12	
Type of perforator used Mills	Brown sand and gravel	12	75	
Size of perforations 3/8 in. by 2 in.	Gray clay	75	92	
	Black sand packed	92	98	
perforations from	Black sand gravel , clay	98	137	
perforations from ft. to ft.				
perforations from	Name and the same			
perforations from ft. to ft.				
(7) SCREENS: Well screen installed?   Yes No				
Manufacturer's Name	(p	<del> -</del>		
Type Model No.		+		
Diam Slot size Set from ft. to ft.		<del>   </del>		
Diam. Slot size Set from ft. to ft.				
(8) WATER LEVEL: Completed well.				
Static level 20 ft. below land surface Date 7-10-69				
sian pressure lbs. per square inch Date		<u> </u>		
(9) WELL TESTS: Drawdown is amount water level is	1	<del>                                     </del>		
lowered below static level				
Was a pump test made? ☑ Yes □ No If yes, by whom? Driller	Work started June 12, 1959 Comple	ted Tanlar	70 7	L9 <del>6</del> 9
Yield: 350 gal./min. with 40 ft. drawdown after 6 hrs.	Date well drilling machine moved off of well J			19
400 " 60 " 6 "		TA TO	1909	
	Drilling Machine Operator's Certification: This well was constructed under my d	irect supe	rvision.	. Mate-
Bailer test gal./min. with ft. drawdown after hrs.	rials used and information reported abo knowledge and belief.	ve are tr	ue to n	ny best
Artesian flow g.p.m. Date	٠ ا م م ا	·		-3.00
Temperature of water Was a chemical analysis made? ☐ Yes ☐ No	[Signed] Hours a Wayner (Drilling Machine Operator)	Date Ju	1y10	, 1950.5
(10) CONSTRUCTION:	Drilling Machine Operator's License No.	474		
Well seal-Material used Drill cuttings, Puddle Clay		-		
Depth of seal ft.	Water Well Contractor's Certification:			
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisd true to the best of my knowledge and beli		d this r	eport is
Were any loose strata cemented off?  Yes No Depth			-	
Was a drive shoe used? ☐ Yes ☐ No	NAME WILLAMETTE DRILLING COM (Person, firm or corporation)	(Type	or print)	
Did any strata contain unusable water?   Yes No	Address 7641 35th Ave. NE Sale	em. Ore	gon	
Type of water? depth of strata	0-00-0	i	`	
Method of sealing strata off	[Signed] (MU) ()	UR	<i>)</i>	•••••
Was well gravel packed? ☐ Yes 😿 No Size of gravel:	(Water Well Contra			•
Gravel placed from ft. to ft.	Contractor's License No2 Date	July 11	<b>,</b> 1969	₹9