

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON
(Please type or print)

(Do not write above this line)

State Well No. 65/3W-35dd

State Permit No.

(1) OWNER:

Name Homer Parks
Address 978 Lawnview N.
Salem, Oregon 97303

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☒
6" Diam. from 41 ft. to 70 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations	in. by	in.
perforations from	ft. to	ft.
perforations from	ft. to	ft.
perforations from	ft. to	ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☐ No If yes, by whom?

Flow	gal./min. with	ft. drawdown after	hrs.
"	"	"	"
"	"	"	"

Bailer test 32 gal./min. with 1 ft. drawdown after 1 hrs.
Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used portland cement
Well sealed from land surface to 23 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 15 sacks
How was cement grout placed? air grout pump

Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number
SE 1/4 SE 1/4 Section 35 T.6S R. 3W W.M.

Bearing and distance from section or subdivision corner well
at same address

(11) WATER LEVEL: Completed well.

Depth at which water was first found 40 ft.

Static level 28 ft. below land surface. Date 2-18-80

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0"

Depth drilled 70 ft. Depth of completed well 70 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Brown topsoil w/ fill gravel	0'	4'	
Brown sandy clay	4'	23'	
Brown fine-coarse sand			
+ small-medium gravel	23'	70'	28'

RECEIVED

FEB 23 1980

WATER RESOURCES DEPT
SALEM, OREGON

Work started Feb. 14 1980 Completed Feb. 20 1980

Date well drilling machine moved off of well Feb. 23 1980

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Michael Waldrop Date Feb. 24, 1980
(Drilling Machine Operator)

Drilling Machine Operator's License No. 873

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name MILLER + WEST DRILLING
(Person, firm or corporation) (Type or print)

Address 5875 GAFFIN RD. SE

[Signed] Michael Waldrop
(Water Well Contractor)

Contractor's License No. 633 Date Feb. 24, 1980