

Amended 3-23-26

STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765)

WELL I.D. # L 41193 41301 START CARD # 128539

Instructions for completing this report are on the last page of this form.

(1) OWNER: Well Number BUTSCH BROTHERS LLC Name 15486 UNION SCHOOL RD. NE City WOODBURN State OR Zip 97071

(9) LOCATION OF WELL by legal description: County MARION Latitude Longitude Township 5S N or S Range 1W E or W. WM. Section 15 NE 1/4 NW 1/4 Tax Lot 800 Lot Block Subdivision Street Address of Well (or nearest address) SAME

(2) TYPE OF WORK [X] New Well [ ] Deepening [ ] Alteration (repair/recondition) [ ] Abandonment

(10) STATIC WATER LEVEL: 31 ft. below land surface. Date 4-27-00 Artesian pressure lb. per square inch. Date

(3) DRILL METHOD: [ ] Rotary Air [ ] Rotary Mud [X] Cable [ ] Auger [ ] Other

(11) WATER BEARING ZONES: Depth at which water was first found 72

(4) PROPOSED USE: [ ] Domestic [ ] Community [ ] Industrial [X] Irrigation [ ] Thermal [ ] Injection [ ] Livestock [ ] Other

(5) BORE HOLE CONSTRUCTION: Special Construction approval [ ] Yes [X] No Depth of Completed Well 179 ft. Explosives used [ ] Yes [X] No Type Amount

Table with 4 columns: From, To, Estimated Flow Rate, SWL. Row 1: 108, 169, 800, 31

Table with 7 columns: Diameter, From, To, Material, From, To, Sacks or pounds. Rows for CEMENT and BENT.

How was seal placed: Method [ ] A [ ] B [X] C [ ] D [ ] E [X] Other BENT. POURED DRY Backfill placed from 180 ft. to 179 ft. Material 3/8 PFA Gravel placed from 179 ft. to 60 ft. Size of gravel 3/8 & 6/8

(12) WELL LOG: Ground Elevation

Table with 8 columns: Diameter, From, To, Gauge, Steel, Plastic, Welded, Threaded. Rows for Casing and Liner.

Table with 4 columns: Material, From, To, SWL. Rows for TOPSOIL, CLAYEY SILT BRN, SANDY SILT BRN, SANDY SILT GREY, SANDY CLAY GREY, GRAVEL W/CLAY, CLAY GREY, GRAVEL W/CLAY, CLAY GREY, SAND GREY FINE LOOSLY, CEMENTED W/LAYERS OF SILT, GREY, SAND & GRVLS TO 3" LOOSE, SAND GREY COURSE, SAND & GRAVEL TO 3" LOOSE, GRAVEL W/CLAY CMTD CRSE, CLAY GREY SILTY, CLAY BRN, CLAY BLUE GREY

Final location of shoe(s) 180

(7) PERFORATIONS/SCREENS: [ ] Perforations Method SCREEN [X] Screens Type V-WIRE Material SS

(8) WELL TESTS: Minimum testing time is 1 hour JUL 07 2000 [X] Pump [ ] Bailer [ ] Air [ ] Artesian Yield gal/min Drawdown Time

Date started 2-12-00 Completed 6-2-00 (unbonded) Water Well Constructor Certification:

I certify that the work I performed on the construction, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to the best of my knowledge and belief.

Signed (bond) I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief. Signed Steve N. Stachli WWC Number 688 Date 6-29-00