STATE ENGINEER Salem, Oregon



| STATE | WELL | NO. | 6/3W-36P(2) |
|----------|------|-----|-------------|
| COUNT | Υ | | Marion |
| A PPT TO | | | |

| | | | 111011 110 | |
|--|----------------------|---------------------------|----------------|--------|
| OWNER: C. E. Howell | MAILING ADDRESS: | | | |
| LOCATION OF WELL: Owner's No | CITY AND | | | |
| HOCATION OF WELLE, Owner's No. | STATE: | | | |
| | , W.M. | | | |
| Bearing and distance from section or subdivision | | | | |
| corner | | | | |
| | | | | |
| | ********* | | | |
| | | | | |
| Altitude at well165 | | ! | | |
| TYPE OF WELL:Drilled. Date Constructed19 | 256 | * | | |
| Depth drilled78 | | Section | | |
| CASING RECORD: | | - | | |
| 8 inch | | | | |
| | | | | |
| | | | | |
| FINISH: | | | | |
| Casing perforated 47 to 77 | | | | |
| perference if on it | | | | |
| AQUIFERS: | | | | |
| Gravel and sand from 45 to 78 | | | | |
| | | | | |
| WATER LEVEL: 28 feet below land surface, June,] | 956 | | | |
| 20 1000 Bozow Zana Barraco, Fano, 1 | -//- | | | |
| PUMPING EQUIPMENT: Type | ******************** | ************************* | H.P. | |
| Capacity | | | | |
| WELL TESTS: | | | | ····· |
| Drawdown ft. after | hours | | | G.P.M. |
| Drawdown ft. after | hours | | | G.P.M. |
| USE OF WATER Irrigation | Temp | °F | | , 19 |
| SOURCE OF INFORMATION USGS DRILLER or DIGGER | ********** | | | |
| ADDITIONAL DATA: | | | | |
| LogX Water Level Measurements | . Chemical Ana | alysis | . Aquifer Test | |
| REMARKS: | | | 1 | |

Temperature 55° F.

STATE ENGINEER Salem, Oregon

| State Well No. | 6/3W-36P(2) |
|-----------------|-------------|
| County | Marion |
| Application No. | |

Well Log

| Owner: C. E. Howell | Ov | vner's No | | |
|--|-----------------|-----------|------------------|--|
| Driller: | | | | |
| CHARACTER OF MATERIAL | (Feet below lar | | Thickness (feet) | |
| Top soil | 0 | 3 | 3 | |
| Clay, yellow | 3 | 15 | 12 | |
| Clay, yellow, sandy | 15 | 45 | 30 | |
| Gravel, tight and hard, water-bearing | 45 | 77 | 32 | |
| Gravel, loose, and sand, water-bearing | 77 | 78 | 1 | |
| Casing: 8-inch to 78 feet; perforated | | | | |
| from 47 to 77 feet. | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| · | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |