STATE OF OREGON DEC 2 1 ZUUU			457	80	
WATER SUPPLY WELL REPORT (as required by ORS 537.765) WATER RESOURCES DEPT		WELL I.D. # I START CARD	<u> 73 /</u>	09	
(as required by ORS 537.765) Instructions for completing this report are on the last page of this form.		SIARI CARD	#_ <u></u> #		
(1) LAND OWNER Well Number / Test	(9) LOCATION O	F WELL by legal	description:		
(1) LAND OWNER Name Salem Development Inc. Address PO Box 335	County Haria	Latitude	L	ongitude	
Address PD B of 335	Township 7-	Latitude N or S Range	e 3 - W	E or W.	WM.
City Salem State OR Zip 97301		NE 1/4			
(2) TYPE OF WORK		LotBloo		Subdivision _	
New Well Deepening Alteration (repair/recondition) Abandonment	Street Address of	Well (or nearest address	s) None		
(3) DRILL METHOD:					
Rotary Air Rotary Mud Cable Auger	(10) STATIC WAT			Data 12	-4-0
Other	Artesian pressurelb. per square inch Date				
(4) PROPOSED USE:	l		square men	Date	
☑ Domestic ☑ Community ☐ Industrial ☐ Irrigation ☐ Thermal ☐ Injection ☐ Livestock ☐ Other	(11) WATER BEA	RING ZUNES:	2 2		
(5) BORE HOLE CONSTRUCTION:	Depth at which water	was first found	32		
Special Construction approval Yes No Depth of Completed Well 6.	From To Estimated Flow Rate SWI			SWL	
Explosives used Yes No Type Amount	32	32 45		20+	
HOLE SEAL					25
Diameter From To Material From To Sacroor pounds					
18 0 18 Bentomite 0 10 13					ļ
6 18 50			<u> </u>		
	(12) WELL LOG:				
How was seal placed: Method $\Box A \Box B \Box C \Box D \Box E$	Gro	ound Elevation			
Backfill placed fromft. toft. Material	Mate	erial	From	То	SWL
Backfill placed fromft. toft. Material Gravel placed fromft. toft. Size of gravel	Fill		0	1	
(6) CASING/LINER:	Gray Clay	with de		d	
Diameter From To Gauge Steel Plastic Welded Threaded	Veadatio	n		3	
Casing: $6-in+2$ 50 .250 \square	Semi pack	ed brown			
	Sand		3	18	
	loose fine	e brown		\	
	Sand de	. 1	18	21	-
Liner:	loose brow	in gravel	21	24	
Drive Shoe used Inside Outside None	dry Semi tight	brown s		127	+
Final location of shoe(s) 50 ft O Dex Shoe	and grave	1- dua	7 U	32	
(7) PERFORATIONS/SCREENS:	Brown San	d + aravel	- med.	1 -	1
Perforations Method		brown	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	<u> </u>	
☐ Screens Type Material Slot Tele/pipe	binder		32	43	25
From To size Number Diameter size Casing Liner	Gray Clay	stone wit	4		
	gravel		43	45	
	Dark gran	Clay5Tone	45	50	
		,		 	}
		<u> </u>	npleted 12	1 - 0	<u> </u>
(8) WELL TESTS: Minimum testing time is 1 hour Flowing	Date started 12 -			-6-0	<u> </u>
☐ Pump ☐ Bailer 🎛 Air ☐ Artesian	(unbonded) Water We			arotian ar oh	andon
Yield gal/min Drawdown Drill stem at Time	ment of this well is in c	ork I performed on the compliance with Orego			
20 + 48 I hr.	standards. Materials use knowledge and belief.	ed and information rep			•
	knowledge and bellet.	ر مد	WWC Nu	mber <u>16 2</u> Date <u>12 - 4</u>	29
	Signed			Date <u>12-</u>	18-00
Temperature of water Depth Artesian Flow Found	(bonder) Water Well		ition:	•	
Was a water analysis done?		ity for the construction			
Did any strata contain water not suitable for intended use?	performed on this well performed during this t	ime is in compliance v	vith Oregon wate	er supply well	i
☐ Salty ☐ Muddy ☐ Odor ☐ Colored ☐ Other	construction standards.	This report is true to t	he best of my kn	owledge and	belief.
Depth of strata:	Signed Flour	9/ Singe) wwc.Nu	mber 12	