

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

RECEIVED
WATER WELL REPORT

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date of well completion.

STATE OF OREGON
(Please type or print)

State Well No. 651E-6CC

(Do not write above this line)

State Permit No. 6-10542

(1) OWNER:

Name Goschie Farms Inc.
Address 7365 Meridian Rd N.E.
Silverton, Oreg

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
8" Diam. from +1 ft. to 189 ft. Gage 250
" Diam. from " ft. to " ft. Gage " "
" Diam. from " ft. to " ft. Gage " "

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom? Stettler Supply
Yield: 300 gal./min. with 120 ft. drawdown after 8 hrs.
" " " " " "
" " " " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite & Puddled Clay
Well sealed from land surface to 60 ft.
Diameter of well bore to bottom of seal 12" to 20" 189 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 6 bentonite sacks
How was cement grout placed?

Was a drive shoe used? Yes No Plugs Size: location ft.

Did any strata contain unusable water? Yes No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? Yes No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number
SW 1/4 SW 1/4 Section 6 T. 6S R. 1E. W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 58 ft.
Static level 45 ft. below land surface. Date 7/15/77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8
Depth drilled 235 ft. Depth of completed well 215 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil brn.	0	2	
Clay brn.	2	23	
Clay & coarse cobbles brn.	23	47	
Clay grey	47	58	
Course Conglomerate	58	77	
Clay sandy grey	77	93	
Sand & few gravels Blk.	93	98	W.B.
Clay & Wood grey	98	125	W.B.
Clay grey sticky	125	184	
Hard Basalt Blk.	184	205	W.B.
Clay grey	205	235	

Work started 3/30/77 19 Completed 7/15/77 19
Date well drilling machine moved off of well 7/15/77 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Charles E. Stadel Date 9/1/77, 19...
(Drilling Machine Operator) 84

Drilling Machine Operator's License No.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Stadeli Drilling Co.
(Person, firm or corporation) (Type or print)

Address Rt Mt Angel, Oreg.

[Signed] Charles E. Stadel
(Water Well Contractor)

Contractor's License No. 519 Date 9/1/77, 19...