- STATE OF OREGON

WATER SUPPLY WELL REPORT

(as required by ORS 537.765)

47151 WELL I.D. # L_ START CARD # 14037 |

Instructions for completing this report are on the last page of this form.	
(1) LAND OWNER Well Number 2 (c 2 8	(9) LOCATION OF WELL by legal description:
Name Jun Heater	County Marian Latitude Longitude
Address 4602 Drift Creek Rd. SE.	Township N or Range E oww.
City Sublimity State Cregan Zip 97385	Section 14 NE 1/4 NW 1/4
(2) TYPE OF WORK	Tax Lot 1000 Lot Block Subdivision
New Well ☐ Deepening ☐ Alteration (repair/recondition) ☐ Abandonment	Street Address of Well (or nearest address) Huy 214 - 34 mile East of Cascace Huy, Sublimity, OR
(3) DRILL METHOD:	TOST OF COSCOCO FLOW, SEPARATELY, OR
	(10) STATIC WATER LEVEL: ft. below land surface. Date
	Artesian pressurelb. per square inch Date
(4) PROPOSED USE: ☐ Domestic ☐ Community ☐ Industrial ☐	(11) WATER BEARING ZONES:
☐ Thermal ☐ Injection ☐ Livestock ☐ Other	
(5) BORE HOLE CONSTRUCTION:	Depth at which water was first found
Special Construction approval Yes No Depth of Completed Well 414 ft.	From To Estimated Flow Rate SWL
Explosives used Yes No Type Amount Amount	160 214 2500 gpm 41
HOLE SEAL Diameter From To Material From To Sacks or pounds	J'
18 0 3 (ement 0 3 12 cocks	2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
16 3 79 (ement 3 79 65 500)	\$ \$\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
12 79 214 Bore	
How was seal placed: Method	(12) WELL LOG: 3748 12 14 17 17 17 17 17 17 17 17 17 17 17 17 17
Other	Ground Elevation
Backfill placed fromft. Material	Material From To SWL
Gravel placed fromft. toft. Size of gravel	Brain Clay 0 20
(6) CASING/LINER:	Drown Humite Clay 20 21
Diameter From To Gauge Steel Plastic Welded Threaded	Blue Vokanic Cinder Cord 27 41
Casing: $12 + 1 \cdot 29 \cdot 250 \times \square$	Broken Basalt 41 68
	Brown Pimice Clay 68 74 Plus brown (Index Cong 74 75
	Que blank (Inder long 74 1/3 120
Liner: NONE	Hu Vokanic Cinter Cong 120 123
	1505alt 123 185
Drive Shoe used \square Inside \square Outside \square None Final location of shoe(s) \square NONE	Broken Basalt 185 214 41
(7) PERFORATIONS/SCREENS:	
Perforations Method	
☐ Screens Type Material	
Slot Tele/pipe	RECEIVED
From To size Number Diameter size Casing Liner	JUL 1 2 2001 JAN 08 114
	AZANTAN TARA
NONE	WATER RESOURCES DEPT
	SALEM, OREGON
(8) WELL TESTS: Minimum testing time is 1 hour	Date started 6-25-61 Completed 7-03-01
Flowing	(unbonded) Water Well Constructor Certification:
□ Pump □ Bailer ☑ Air □ Artesian	I certify that the work I performed on the construction, alteration, or abandon-
Yield gal/min Drawdown Drill stem at Time	ment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to the best of my
3500gpm 300' 1 hr.	knowledge and belief.
	Signed $\frac{1379}{\text{Signed}}$ Date $\frac{7-01-01}{1-01}$
1.00	
Temperature of water Depth Artesian Flow Found	(bonded) Water Well Constructor Certification: Laccept responsibility for the construction, alteration, or abandonment work
Was a water analysis done?	performed on this well during the construction dates reported above. All work
□ Salty □ Muddy □ Odor □ Colored ☑ Other different Static	performed during this time is in compliance with Oregon water supply well construction standards. This reposits true to the best of my knowledge and belief.
Depth of strata: 14-43 12'5tat 10	WWC Number 5/4
comented of 20gpm	Signed Date 1-04-01