NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

State Well No. 65/1E -1869

w.

(Please type or print)

ATER RESOURCES D. SALEM, OREGON within 30 days from of well complet	the date of	El	V	E	D	S Do
or well complet	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	~~	407	20	`	

not write above this line)
Application, No-G-6

State	Permit	No.	<u>G-</u>	6	3	9	<u> </u>

(1) OWNER: WATER RESOURCES DEPT.	(10) LOCATION OF WELL:					
D. I. WAILK RESOURCE	County Marion Driller's well number	r				
Name Dickman Farmsalem. OREGON Address 15829 Mt.Angel-Scotts Mills Hwy NE	7.0	LE w.m.				
Silverton, Oregon 97381	Bearing and distance from section or subdivision co	orner				
(2) TYPE OF WORK (check):						
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐						
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.					
(3) TYPE OF WELL: (4) PROPOSED USE (check):	070					
Determ W Driven D	777	- 1/25/79				
Cable	50000 10101	- 1				
Bored Irrigation X Test Well Other ORIGINAL	Artesian pressure lbs. per square inc	ch. Date				
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below	casing 8"				
" Diam, from ft. to ft. Gage	Depth drilled 463 ft. Depth of completed	well 463 ft.				
" Diam, from ft. to ft. Gage	Formation: Describe color, texture, grain size and s					
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in					
(6) PERFORATIONS: Perforated? Yes M No.	position of Static Water Level and indicate principal					
Type of perforator used	MATERIAL Fr	om To SWL				
Size of perforations in. by in.	Basalt Medium Grey 22	24 260				
perforations fromft. toft.		50 272				
perforations fromft. toft.	Basalt Hard Grev 2	72 311				
perforations fromft. toft.	Basalt Seamy Brown 3	11 340 WB				
		+0 373				
(7) SCREENS: Well screen installed? Yes X No		73 397				
Manufacturer's Name		97 410 WB				
Type Model No		10 430 WB 30 463				
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	Basalt Hard Grey 4	30 403				
Diani, Slot size						
(8) WELL TESTS: Drawdown is amount water level is lowered below static level						
Was a pump test made? ☐ Yes K No If yes, by whom?						
id: gal./min. with ft. drawdown after hrs.						
" " "	-					
" " " "						
ATR BEIEr-tesapp. 700 gal./min. with 110 ft. drawdown after 1 hrs.						
tesian flow g.p.m. comperature of water Depth artesian flow encountered	Work started 1/23/ 1979 Completed	1/25/ 1979				
	Date well drilling machine moved off of well	1/25/ 1979				
(9) CONSTRUCTION: ORIGINAL SEAL		1/2//				
Well seal—Material used	Drilling Machine Operator's Certification: This well was constructed under my din	rect supervision				
Well sealed from land surface to ft.	Materials used and information reported about	ove are true to my				
Diameter of well bore to bottom of seal in.	best knowledge and belief.	1/26 70				
Diameter of well bore below seal in.	[Signed] Date (Drilling Machine Operator)	e 1/26 , 19 79				
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No	720				
How was cement grout placed?						
	Water Well Contractor's Certification:					
	This well was drilled under my jurisdiction true to the best of my knowledge and belief.	on and this report is				
Was a drive shoe used? ☐ Yes 🏖 No Plugs Size: location ft.	Wort Const Drilling Co	. Inc.				
Did any strata contain unusable water? ☐ Yes X No	(Person, firm or corporation)	(Type or print)				
Type of water? depth of strata	Address 220 Academy St., Mt	Angel, OR 973				
Method of sealing strata off	I had be so the	Noli				
	[Signed] (Water Well Contractor	r)				
Was well gravel packed? ☐ Yes 🛮 No Size of gravel:	Contractor's License No. 519 Date 1/	26 19.79				