CCT 11 1961 AUG 25 1961 MARI. 5.67

File Original and First Copy with the STATE ENGINEWATER WELL REPORT SALEM, OREGON STATE OF OREGON

4/W-17

SALEM, OREGON			State Permit No	•••••		
(1) OWNER:			(11) WELL TESTS: Drawdown is amount lowered below static le	water love	l is	
Name Delbert Haener			Was a pump test made? Yes No If yes, by who		iller	
Address Rte 1 Box 36			Yield: 200 gal./min. with 6 ft. drawdow		hrs.	
Aurora, Oregon			" " "	711 42001	***	
(A) I OCIATIONI OTI TITTI			25 25 25		"	
(2) LOCATION OF WELL:			Bailer test gal./min. with ft. drawdow	m ofter	hrs.	
	ımber, if any—		Artesian flow g.p.m. Date	II arter		
34 34 Section 17 T	4S R. 1	W.M.	Temperature of water 52 Was a chemical analysis m	odes C V	es 🏗 No	
Bearing and distance from section or subdivis	ion corner		The a chemical analysis in	acc. OI	es . <u></u>	
			(12) WELL LOG: Diameter of well	10	inches.	
			Depth drilled 140 ft. Depth of completed w	vell 1	40 ft.	
	· · · · · · · · · · · · · · · · · · ·		Formation: Describe by color, character, size of materishow thickness of aquifers and the kind and nature of	al and stru	cture, and	
			show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each c	the materi change of	ial in each formation.	
			MATERIAL	FROM	то	
(3) TYPE OF WORK (check):			Surface	0	3	
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐ If abandonment, describe material and procedure in Item 11.			Sandy brown clay	3	32	
			Sandy blue clay	32.	62	
			Black clay	62	70	
PROPOSED USE (check):	(5) TYPE OF WE	LL:	Broken sand and blue clay	70	76	
Domestic ☐ Industrial ☐ Municipal ☐	Rotary 🗍 Driver	n 🗆	Brown sandy clay	76	81	
Irrigation 🖾 Test Weil 🔲 Other	Cable ☑ Jetted Dug ☐ Bored		Broken sand and gravel	81	91	
	Dug L Doreu		Gravel	91	92	
(6) CASING INSTALLED: Threaded □ Welded ⊠			Blue clay	92	100	
10 "Diam. from0 ft. to140			Blue sandy clay	100	121	
ft. Gage ft. to			Black sand	121	124	
ft. Gage ft. to ft. Gage				124	140	
			Gravel	124	140	
	erforated? 🏋 Yes 🗌 1	νo			<u> </u>	
Type of perforator used Millknife		·		 		
SIZE of perforations 3/8 in. by	2 in.					
72 perforations from1				-	 	
perforations from	ft. to	ft.		 		
perforations from	ft. to	ft.				
perforations from						
perforations from	ft. to	ft.		 		
(8) SCREENS: Well screen:	installed ☐ Yes 図 1	NTO.		1		
Manufacturer's Name	Les M			1		
wantiacturer's Name	Model No	·		-	 	
Slot size Set from						
Slot size Set from			Wash started Taylor OF 10 67 Completed To	77	10 67	
Diot Size ,			Work started July 25 19 61 Completed J	uly ol		
(9) CONSTRUCTION:	•		(13) PUMP:			
Was well gravel packed? ☐ Yes ₺ No Size of gravel:			Manufacturer's Name			
Gravel placed from ft. to ft.			Type: H.P.			
Was a surface seal provided? Yes No To what depth? ft.						
Material used in seal—			Well Driller's Statement:			
Did any strata contain unusable water? 🔲 Y	es 🛛 No		This well was drilled under my jurisdiction	and this	report is	
Type of water? Depth of	f strata	.	true to the best of my knowledge and belief.			
Method of sealing strata off			NAME John Truman Miller			
(10) WATER TEVELS.			(Person, firm, or corporation) (Type or print)			
(10) WATER LEVELS: Static level 38'6" ft. below land surface Date 7/31/61			Address P O Box 42 Hubbard, Oregon			
				•		
Artesian pressure lbs. per squ	are inch Date		Driller's well number	1 1 4		
Log Accepted by; /	1		[simed] John Averman MI	110		
1 1000 to Hoovels	/ Arrans 1: "	/ -	[Signed] (Well Dyller)	A. A. T.		
[Signed] Date	August 5, ,	1961.	License No. 277 Date Augu	st. 5	. 19 67	
· - · · · · · · · · · · ·			· =	و نر		