NOTICE TO WATER WELL CONTRACTOR The original and first cop

STATE ENGINEER, SALEM 10 OREG within 30 days from the date;

of this report are to be if

VATER WELL REPORT

STATE OF OREGON FER (Please type or print)

State	Well	No.	

				J/W-I		_
	State	Well	No.	1 * *		

,,

hrs.

FROM

0

ΙŔ

29

34

60

80

106

108

129

29

34

60

80

106

108

129

148

19

₁₉ 62

of well completion. State Permit No. .. G 2447 Drawdown is amount water level is lowered below static level (1) OWNER: (11) WELL TESTS: Name Carl Oslund. □ No If yes, by whom? J. T. Miller Was a pump test made? Tyes Address 7307 S.W.Capitol Hi-Way 350 gal./min. with ft. drawdown after Portland 19.0re. (2) LOCATION OF WELL: Bailer test gal./min. with ft. drawdown after County Marion Artesian flow W 1/4 Section T. 52 Was a chemical analysis made? 🗆 Yes 📋 No Temperature of water Bearing and distance from section or subdivision corner west 3168 ft. and south660 ft. (12) WELL LOG: Diameter of well below casing . the n.e. corner of sec. 17-T 4s-rlw Depth drilled ft. Depth of completed well Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation. MATERIAL surface soil (3) TYPE OF WORK (check): Well Reconditioning Deepening | Abandon [7] clay , yellow Sandonment, describe material and procedure in Item 12. sandy'clay yellow clay,blue (5) TYPE OF WELL: (4) PROPOSED USE (check): clay , gray Driven Rotary Domestic | Industrial | Municipal | sand, water, red Cable X Jetted Irrigation [X Test Well [Other Dug Bored $\overline{\Box}$ clay, blue sand, water, black Threaded Welded X 20 cemented (6) CASING INSTALLED: clay, blue 6 " Diam, from ft. to ... olack samd, clay breaks, gray ft. to 148 ft. Gage " Diam. from _____ft. to _____ft. Gage ____ (7) PERFORATIONS: mill knife Type of perforator used Size of perforations 19 perforations from 78 50 130 perforations from perforations from perforations from perforations from ft. to (8) SCREENS: Well screen installed lanufacturer's Name Set from Completed Diam. Slot size Set from Date well drilling machine moved off of well (9) CONSTRUCTION: (13) PUMP: Well seal—Material used in seal 12 sackcement Manufacturer's Name 20 ft, Was a packer used? Diameter of well bore to bottom of sealin. Water Well Contractor's Certification: Were any loose strata cemented off? Tyes No Depth This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was a drive shoe used? ☐ Yes ☐ No Was well gravel packed? 🖾 Yes 🗌 No Size of gravel: <u>Pe a</u> Gravel placed from top ft. to bottom J.T.Miller corporation) (Person, firm or corporation)
x 175, Aurora, Ure. Did any strata contain unusable water?

Yes

No Type of water? Depth of strata Method of sealing strata off Drilling Machine Operator's License No. (10) WATER LEVELS: [Signed] Static level ft. below land surface Date Artesian pressure lbs. per square inch Date