

The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED WATER WELL REPORT STATE OF OREGON

AUG 15 1979 (Please type or print)

MARKS 773

State Well No. 6S/1E-26 bd

State Permit No.

(1) OWNER:

Name Joseph Bielenberg Address 6592 Peaks View Rd. N.E. Scotts Mills, Oregon 97375

(2) TYPE OF WORK (check):

New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven [ ] Cable [ ] Jetted [ ] Dug [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [ ] Irrigation [X] Test Well [ ] Other [ ]

(5) CASING INSTALLED:

8" Diam. from +1 ft. to 244 ft. Gage 250 Threaded [ ] Welded [X]

(6) PERFORATIONS:

Perforated? [ ] Yes [X] No. Type of perforator used Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [ ] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [ ] Yes [X] No If yes, by whom? Field: gal./min. with ft. drawdown after hrs. Air test 450 gal./min. with 412 ft. drawdown after 1 hrs. Artesian flow g.p.m. Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement Well sealed from land surface to 20' ft. Diameter of well bore to bottom of seal 12" in. Diameter of well bore below seal 12" to 244" in. 8" to 567" in. Number of sacks of cement used in well seal 14 sacks How was cement grout placed? Grout Placed: Pressure Was a drive shoe used? [ ] Yes [X] No Plugs Size: location ft. Did any strata contain unusable water? [ ] Yes [ ] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [X] Yes [ ] No Size of gravel: 3/4 minus crushed Gravel placed from 20 ft. to 244 ft.

(10) LOCATION OF WELL:

County Marion Driller's well number SE 1/4 NW 1/4 Section 26 T. 6S R. 1E W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 335 ft. Static level 155 ft. below land surface. Date 7-23-79 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Table with columns: MATERIAL, From, To, SWL. Rows include Top soil, Clay Yellow, Clay Grey, Sandstone Grey, Clay Brown Sandy, Grey Sandstone Brown, Streaks Medium, Sandstone Grey Hard, Sandstone & Claystone, Grey Medium, Claystone Grey Hard, Claystone Grey & Green, Crevasy, Claystone Grey Hard, Sandstone Grey Hard, Claystone Grey Hard, Sandstone Grey Hard, Claystone Grey Hard.

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Steve N. Stadel Date July 26, 1979 (Drilling Machine Operator) Drilling Machine Operator's License No. 860

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name WEST COAST DRILLING CO., INC. (Person, firm or corporation) (Type or print) Address 220 Academy St. Mt. Angel 97362 [Signed] Charles E. Stadel (Water Well Contractor) Contractor's License No. 519 Date July 26, 1979