## RECEIVED

WATER SUPPLY WELL REPORT OCT 0 7 2005
(as required by ORS 537.765)
Instructions Instructions for completing this report awanter Rat Sources, DEPT

WELL I.D. # L 75904 START CARD # 163487

(1) OWNED.		- ONEGON	(9) LOCATION OF	WELL by legal descr	iption:		
(1) OWNER: Well Number		(9) LOCATION OF WELL by legal description:  County Marion Latitude Longitude					
Name Tom DeArmond			Township 4S N or S Range 1W E or W. WM.				. WM.
Address 11463 Broadacres Rd. NE  City Hubbard State OR Zip 97032				NW1/4			
(2) TYPE OF WORK			Tax Lot 201 I	ot Block	Sub	division	
New Well Deepening Alteration		ll (or nearest address)					
(3) DRILL METHOD:	(теринутесоналион	7					
	hle Auger		(10) STATIC WATE	R LEVEL:		·	
□ Rotary Air    □ Rotary Mud    □ Cable    □ Auger     □ Other    □				ow land surface.	Da	<sub>ite</sub> 9/8/	05
(4) PROPOSED USE:			Artesian pressure lb. per square inch. Date				
Domestic Community Industrial Irrigation			(11) WATER BEAR		****		
Thermal Injection Livestock Other			` '				
(5) BORE HOLE CONSTRUCTION	Depth at which water was first found						
Special Construction approval Yes X		leted Well 2∩3 ' & '	•				
Explosives used Yes No Type Amount			From	То	Estimated :	Flow Rate	SWL
HOLE SEAL			110	138	600	) apm	35
Diameter From To Material		Sacks or pounds	149	200	1200	) gipm	37
1 1	1 1 1	72 sacks					
5%bent	tonite	z backb					
20" 0 80 cements 5%bent 16" 80 203 4"							
			(12) WELL LOG:				
How was seal placed: Method	Ground Elevation						
Other			<u></u>				<del></del>
Backfill placed from ft. to	ft. Material		Mater		From	To	SWL
Gravel placed from ft. to	_ ft. Size of g	gravel	Clay hard b		0	1	
(6) CASING/LINER:			Clay brown	silty	_ 1	30	
Diameter From To Gau	ge Steel Plastic	Welded Threaded	Clay tan, s		30	36	
Casing: 16" +1'7"146 8"	.37 <u>5</u> × □			rown & clay	36	61	
			Clay blue c Sand & Clay	ray soft	81	84 92	
					92	97	
			Clay gray 8		97	103	
Liner:			Clay brown				
			Sand & clay		103	110	35
Final location of shoe(s) 146:8"			Sand black coarse		110	127	35
(7) PERFORATIONS/SCREENS:			Sand(80%)&		127	138	35
Perforations Method			Clay green		138	148	
Screens Type	Mate	rial stainles:	Clay gray,		148	149	
Site From To size Number I	i ere/pip: Diameter . size	Casing Liner	Sand coarse		149	181	37
+3: 148:6" 1	2"	_ 🛛 🗎	Sand (50%), 8	_	181	183	37
148:6"196:6" -075	12" p.s.	_ 0 0	Sand & gray	zel	183	200	37
1.70 0 400 1 - 1	2"	_ 😡 🗆	Clay		200	203'4	<del>  </del>
20 <u>3:4" Lift bail &amp; bot</u> t	om plate	_ 🗆 🗆				<del> </del>	
		_ 🗆 🗆					
		<del></del>				J	
(8) WELL TESTS: Minimum test	Date started 7/20/05 Completed 9/12/05 (unbonded) Water Well Constructor Certification:						
Flowing							
<b>⅓</b> Pump ☐ Bailer	☐ Air	Artesian	of this well is in compl	rk I performed on the con iance with Oregon water	sunnly well co	nstruction st	tandards.
Yield gal/min Drawdown	Drill stem at	Time	Materials used and info	rmation reported above	are true to the b	est of my k	nowledge
1150 44'4"		1 hr.	and belief.	, /	WANG No.	h 170	. 4
1150 52:3"		4hrs	WWC Number 1704				
			Signed Date 105/05				
Temperature of water 53 Depth Artesian Flow Found (bonded) Water Well Constructor Certification:							
Was a water analysis done? Yes By whom I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. All work							work
Did any strata contain water not suitable	nerformed during this	time is in compliance wi	th Oregon wate	r supply we	Ш		
Salty Muddy Odor Co	. This report is true to th	e best of my kn	iowieage an	ia bellel.			
Depth of strata:	1 /)	91	WWC Nu	mber			
Signed Wan / rosan Date 10/3/05							<u>/3/05</u>