NOTICE TO WATER WELL CONTRACTOR I E The original and first conv of this report and to be filed with the AUG 16 1968

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date ENGINEER of well comparing the date. 1988 Mino. 7/16 - 2 #J WATER WELL REPORT () STATE OF OREGINA A FE State Heriot No. .. Drawdown is amount water level is lowered below static level (11) WELL TESTS: (1) OWNER: Was a pump test made? ☐ Yes [X No If yes, by whom? M.L. Krack Klaxton S. Water, Silverton, Oregon gal./min. with ft. drawdown after •• ,, (2) LOCATION OF WELL: 7 gal./min. with 185 ft. drawdown after Beizer test hrX County Marion Driller's well number Artesian flow g.p.m. Date 1/4 Section W.M. Temperature of water XX Was a chemical analysis made? Tyes IXI No Bearing and distance from section or subdivision corner (12) WELL LOG: Diameter of well below casing .. 1375 ft.N.& 5 ft.W.of S.E.corner of ft. Depth of completed well 20215 ft. T.7 S. R.1 W. Formation: Describe by color, character, size of material and structure, and show thickness of aquifiers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation. MATERIAL FROM (3) TYPE OF WORK (check): 0 Top soil-red 10 Abandon 🗌 7. Deepening [Reconditioning [Clay & boulders-brown 80 10 <u> Claystone-grey-hard</u> indonment, describe material and procedure in Item 12. 5 gpm. water at 80 ft. (5) TYPE OF WELL: (4) PROPOSED USE (check): 80 Sandstone-hd., light grey Rotary X Domestic X Industrial | Municipal | 145 Claystone-grey-hd. Cable Jetted Irrigation

Test Well

Other Total of 7 gpm.at 200 ft. Dug Bored | (6) CASING INSTALLED: Threaded | Welded 7 0 ft, to 19 ft. Gage . 250 " Diam. from (7) PERFORATIONS: Perforated? ☐ Yes X No Type of perforator used in. by Size of perforations perforations from ft. to perforations from ft. to perforations from ft. to ft. perforations from ft. to ft. (8) SCREENS: Well screen installed? | Yes X No Manufacturer's Name Set from ft. to Work started 6/20/68 19 . Completed Diam. Slot size Set from ft, to Date well drilling machine moved off of well 6/20/68 (9) CONSTRUCTION: (13) PUMP: Well seal—Material used in seal Bentonite unknown Manufacturer's Name Depth of seal 19 ft. Was a packer used? no Diameter of well bore to bottom of seal 12-t to 18 & 2-5/8 to 19' Water Well Contractor's Certification: Were any loose strata cemented off? Tyes No Depth This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was a drive shoe used? [] Yes [X]No Size of gravel: Was well gravel packed? ☐ Yes 🗓 No Gravel placed from _____ft. to _____ft. NAME K. Stadeli & Sons
(Person, firm or corporation) Did any strata contain unusuable water? 🗌 Yes 🕱 No Address Rte. 3 Box 169 Silverton, Uregon depth of strata Type of water? Method of sealing strata off Drilling Mackine Operator's License No. (10) WATER LEVELS:

Contractor's License No. 296 Date 8/12/08 19

ft. below land surface Date 6/20/68

lbs. per square inch Date

Static level

Artesian pressure