MARI 60019

STATE	OF	OREGON	ł

Name	ND OW	'NER	F KER	TER	Well Nu	mber	e
Address			CHEM		RD		
City 🖌	KEIZI	ZR		State	ÓR	Zip 🕻	7730
• •	PE OF ' Well 🗌			ration (repa	ir/recondit	ion) 🗌 Aba	ndonm
			D: y Mud 🏹	Cable 🗆 A	Auger		
Dome Dome	nal 🗌	Comm Injectio	unity 🕱 In on 🗌 Li	vestock		n	
			DNSTRUC		pth of Co	mpleted We	ell
Explosiv		🗆 Yes	🗌 No Тур		Aı	mount	
Diemata	HOLE	To	M	SEAL	T-	Socks	unde
Diameter		То	Materia	l From	То	Sacks or po	ounds
	SE	E 7	AGE 1	/			
			_	_			
			Maik - J				[
How wa	s seal pla	ced:	Method]B []	C D	🗆 E
		om	ft. to	ft.	Materi	al	
	-		ft. to			gravel	
(6) CA	SING/L	INER	:				
	Diameter	r Fror	n ToG	auge Steel	Plastic	_	Threade
Casing: _	SEE	PAL	EI	L			
-							
_							
Liner: _			_				
			le 🗌 Outsi	de ∐Non	e		
Final loc			S/SCREE	NS:			
Final loc (7) PEI	кнока						
(7) PE	RFORA erforatior		Method				
(7) PEI		ns	Method	WIRE		terial 57	INZA
(7) PEI □ P ≰S	erforatior creens	ns Slot	Method Type		Tele/pij	pe	
(7) PEI P S S From	erforatior	ns	Method Type	WIRE Diameter	Tele/pij	pe Casing	<u>4/////</u> Lin
(7) PEI □ P ≰S	erforatior creens To	ns Slot	Method Type	Diameter	Tele/pij size	pe Casing	
(7) PE P S S From 265	erforation creens To 280	ns Slot	Method Type Number	Diameter	Tele/pij size	Casing	
(7) PE P S S From 265	erforation creens To 280	ns Slot	Method Type Number	Diameter	Tele/pij size	Casing	
(7) PEI	rforatior creens To 280 290	Slot size	Method Type Number	Diameter / 2 /0"	Tele/pij size TEL	pe Casing ∠ _ □ ▲ □ □	
(7) PEI P P S From 265 250 (8) WE	rforation creens 280 290 LL TES	Slot size	Method Type Number	Diameter / 2 /0'' testing tin	Tele/pij size TEL	casing	
(7) PE P P S S From 265 250 (8) WE Pu	rforation creens 280 290 LLL TES mp	Slot size 324 324 STS: N	Method	Diameter / 2 /0" testing tim □ Air	Tele/pig size TEL	pe Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing	Lin
(7) PE P P S S From 265 250 (8) WE Pu	rforation creens 280 290 LL TES	Slot size 324 324 STS: N	Method Type Number	Diameter / 2 /0'' testing tin	Tele/pig size TEL	pe Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing	
(7) PE P P S S From 265 250 (8) WE Pu	rforation creens 280 290 LLL TES mp	Slot size 324 324 STS: N	Method	Diameter / 2 /0" testing tim □ Air	Tele/pig size TEL	pe Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing	Lin ving sian `ime
(7) PE P P S S From 265 250 (8) WE Pu	rforation creens 280 290 LLL TES mp	Slot size 324 324 STS: N	Method	Diameter / 2 /0" testing tim □ Air	Tele/pig size TEL	pe Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing	Lin ving sian `ime
(7) PE P P (S From 265 250 (8) WE (8) WE Pu Yield	rforation creens To 280 290 LL TES mp gal/min	Slot size 324 344 STS: N B Dr	Method	Diameter / 2 /0" testing tin □ Air Drill st	Tele/piŋ size <i>TEL</i> ne is 1 h	pe Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing Casing	Lin ving sian hr.

PAGE	20+2
WELL I.D. # L_	L82935
STADT CADD #	· · -

START	CARD	#	_W	1	66	l	<u>2</u>	

County IN AND	F WELL by legal A Latitude	ե	ongitude	
Township	N o Rang	je <u>3</u>	E or 🐼 '	WM.
Section	Νω 1/4.	Νω1	/4	
Tax Lot	_LotBlo	ckS1	ubdivision _	
Tax Lot Street Address of Rd NE + R 10	Well (or nearest addres	s) <u>SW Corne</u> NE	r of C	remai
(10) STATIC WAT	ER LEVEL: below land surface.		Date	
	lb. per	square inch		
(11) WATER BEA		square men		
Depth at which water				
From	То	Estimated F	low Rate	SWL
-				
SER	AAGER 1			
(12) WELL LOG:				
	ound Elevation			
Mate	erial	From	То	SWI
SILTY COBBLE	ES /GRAVEL	238	246	
SILT BOUND G	RAVELS	246	250	
SUTV ALDI				
JILIT CODE	3LES	250	259	
GREY SAND :	SILT	259	259 269	
GREY SAND : GREY SILTY SAL	SILT UD/BRAVEL	259 269	257 269 277	
GREY SAND : GREY SILTY SAN BLUE CLAY L	SILT UD/GRAVEL J/GRAVEL	259 269 277	259 269 277 281	
GREY SAND : GREY SILTY SAN BLUE CLAY L FINE TO ME	SILT WD/GRAVEL W/GRAVEL ED SAND	259 269 277 281	259 269 277 281 285	
GREY SAND : GREY SILTY SAN BLUE CLAY L	SILT WD/GRAVEL W/GRAVEL ED SAND	259 269 277	259 269 277 281	
GREY SAND : GREY SILTY SAN BLUE CLAY L FINE TO ME	SILT WD/GRAVEL W/GRAVEL ED SAND	259 269 277 281	259 269 277 281 285	
GREY SAND : GREY SILTY SAN BLUE CLAY L FINE TO ME	SILT WD/GRAVEL W/GRAVEL ED SAND	259 269 277 281 285	259 269 277 281 285 290	
GREY SAND : GREY SILTY SAN BLUE CLAY L FINE TO ME	SILT WD/GRAVEL W/GRAVEL ED SAND	259 269 277 281 285	259 269 277 281 285	D
GREY SAND : GREY SILTY SAN BLUE CLAY L FINE TO ME	SILT WD/GRAVEL W/GRAVEL ED SAND	259 269 277 28/ 285	259 269 277 281 285 290	
GREY SAND : GREY SILTY SAN BLUE CLAY L FINE TO ME	SILT WD/GRAVEL W/GRAVEL ED SAND	259 269 277 28/ 285 RE	269 269 277 281 285 290 CEIVE	06
GREY SAND : GREY SILTY SAN BLUE CLAY L FINE TO ME	SILT WD/GRAVEL W/GRAVEL ED SAND	259 269 277 28/ 285 RE OCT	269 269 277 281 285 290 CEIVE	06 S Def
GREY SAND : GREY SILTY SA BWE CLAY U FINE TO ME	SILT WD/GRAVEL W/GRAVEL ED SAND	259 269 277 28/ 285 RE OCT	259 269 277 28/ 285 290 CEIVE 26 20 SOURCE	06 S Def
GREY SAND : GREY SILTY SA BWE CLAY U FINE TO ME	SILT WD/GRAVEL W/GRAVEL ED SAND	259 269 277 28/ 285 RE OCT	259 269 277 28/ 285 290 CEIVE 26 20 SOURCE	06 S Def
GREY SAND : GREY SILTY SAN BLUE CLAY L FINE TO ME	SILT WD/GRAVEL W/GRAVEL ED SAND	259 269 277 28/ 285 RE OCT	259 269 277 28/ 285 290 CEIVE 26 20 SOURCE	06 S Def

I certify that the work I performed on the construction, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to the best of my knowledge and belief.

Signed Tran R Nul Date 7-6-04	and F. DALL	WWC Number 1829
	Signed Time R Nul	Date 7-604

(bonded) Water Well Constructor Certification:

l accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well construction standards, this report is true to the best of my knowledge and helief WWC Number

. Date 🟒

Signed 1

MARI 60019

STAT	TE OF	OREGON					PAGE	1 OF	2	
		PLY WELL RE	PORT				WELL I.D. #	L 82	935	
-		ORS 537.765)					START CARL)# <u>W16</u>	6123	
-					page of this form.					
(1) LA! Name		NER TY OF KE	2/250	Well Nu	mber	(9) LOCATION Q			ongitude	
Address				HEM	awa RD	Township 7	Latitude N or SRang	. 3		WM
City /				OR	Zip 97307	Section2	NOLSKAII	NW		** *!.
(2) TYP	PE OF	WORK					Lot Blo			
New V	Well 🖸	Deepening Alt	teration (repair	/recondit	ion) Abandonment		Well (or nearest addres			
(3) DRI	ILL MI	ETHOD:				Pd HE + Rid	mond Rd N	ć		
		🛾 Rotary Mud 🛛 🗮	Cable 🗆 A	uger		(10) STATIC WAT				
Other.				-			elow land surface.		Date 6	
		D USE: Community 🗆 In	ductrial 🗖	Inicatio	-		lb. per	square inch	Date	
		-	ivestock	-		(11) WATER BEAI	RING ZONES:	- 1		
	_	LE CONSTRU				Depth at which water	was first found	34'		
Special C	Construc	tion approval	es 🗖 No Dep	oth of Co	ompleted Well 270 ft.	From	То	Estimated	Flow Rate	SWL
Explosive		🗆 Yes 🛣 No Typ		A1	nount	34	71_	15	0	29
Diamatan	HOLE	T- Matari	SEAL	m -	Casha	170	240	500	>	29
Diameter	D	To Materi 90 CEME		70	Sacks or pounds	265	280	30	0	29
12	90	290								
										·
	<u> </u>					(12) WELL LOG:				
How was	seal pla	ced: Method MBRCM	GO'TA	B []	C ⊡D ⊡E F4 <f< td=""><td>Grou</td><td>und Elevation</td><td></td><td></td><td></td></f<>	Grou	und Elevation			
		omft. to			al	Mate	rial	From	To	SWL
		mft_te_			gravel	BIRDWA SANDY S	ILT	6	7	
(6) CAS					<u>e</u>	BREWN SANDY S		9	18	f
. 1	Diameter	From To G	auge Steel	Plastic	Welded Threaded	SILTYSAND W/		18	51	I
Casing:	12	+2 170 .	375 🗵			COURSE SAND / C		51	62	
_						SILTY SAND / SM		67	7/	t
_			Ċ) ·			GREY CLAY W/W		71	73	
						SILTY GREY SAND		73	78	
Liner:						GREY CLAY	CATVES	78	98	
						GREYSILT / LR	1 1. PAUZIS	98	125	┥──┤
Drive Sho	e used	Inside Outsi	de 🗌 None	2		CLEAN SAND /		176	131	
				801		SILTY GRAVEL		131	146	
		FIONS/SCREE	NS:			CLEAN SAND!		146	152	
	foration		-WIRE		erial STAINLESS	SILTY COBBLE		152	141	
Scr Scr	eens	Slot		Tele/pir		CLEAN GRAVE		191	210	
From	To		Diameter	size	Casing Liner	STILTY COBBLE:	5 16PAVEL	210	214	
170	175	JESO 💈	12" TELE			CLEAN SAND / C		214	219	
175	200	.ico	12	TEL	<u>e</u> o o	LARGE COBBLE	S/GRAVEL	219	227	
	240	er35	12	TEL		SILTY GRAVE		227	232	
240	265	BLANK	10"		_ • 🖄 🗆	CLEAN SAND		232	238	
(8) WE1	1 755	TS: Minimum	tecting time	ie 1 b		Date started 3-15			-23-06	, ·
		15: Millinulli	testing time	. 15 1 11	Flowing	(unbonded) Water Weil				
X Pum		🗆 Bailer	🗋 Air		Artesian		k performed on the c		ration or aba	ndon-
Yield ga	al/min	Drawdown	Drill ster	mat	Time	ment of this well is in con	mpliance with Oregor	water supply w	ell construction	on .
- 50					i hr.	standards. Materials used knowledge and belief.	l and information repo	orted above are to	ue to the best	of my
820)	120			24	-	11/	WWC Nur	nber / 8 :	29
						Signed Tar R	Viel	I	Date	6-05
Temperatu	ure of wa	ater <u>53°</u>	Depth Artesia	n Flow i	Found	(bonded) Water Well Co	onstructor Certificat	ion:		
Was a wat			es By whom				y for the construction			
		tain water not suita	•			performed on this well du				k
•		ddy 🗌 Odor 🗌		Other		performed during this tim construction standards.				elief.
Depth of s				JAN	2 2 2008	il/./.	Un.n.		nber	5
		· · ·				Signed March	L'and		Date	<u>Z~@</u>
		AL WATER P	WA	IEHH	ESOURCES DEPT	CORV CONSTRUCT			ISTOLED	
C	NION	AL - WAIEK R	ESUUKCE	° SAĽ	EM, OREGON TRST	COPY - CONSTRUC	TOR SECON	D COPY – Cl	STOMER	

15-06

MARI	60019

Address MM P30 CHEMAWA RD City KE/ZER State OR Zip 973. City KE/ZER State OR Zip 973. 2) TYPE OF WORK New Well Deepening Alteration (repair/recondition) Abandonn 3) DRILL METHOD: Rotary Air Rotary Mud Cable Auger Other	Address MMA T30 CHEMAWA RD City KE/ZER State 0k Zip 773. City Caller Ok Zip 773. City Rotary Air Decepening Alteration (repair/recondition) Abandonn City Rotary Air Rotary Mud Cable Auger Other Other Other	Address HIA 730 CHEMA City KE/ZER State OR (2) TYPE OF WORK New Well Deepening Alteration (repair/recondition (3) DRILL METHOD: Alteration (repair/recondition Alteration (repair/recondition (3) DRILL METHOD: Cable Auger Other Other Other (4) PROPOSED USE: Domestic Community Industrial Irrigation Thermal Injection Livestock Other Other (5) BORE HOLE CONSTRUCTION: Special Construction approval Yes No No Depth of Con Explosives used Yes No No Type Am	Zip 973 (
ity KE/ZER State Q Zip 9734 2) TYPE OF WORK Answe Well Deepening Alteration (repair/recondition) Abandonn 3) DRILL METHOD: Rotary Air Rotary Mud Cable Auger 3) DRILL METHOD: Rotary Air Rotary Mud Cable Auger 0 Other	City Kerzek State Qk Zip 9734 (2) TYPE OF WORK New Well Deepening Alteration (repair/recondition) Abandonn (3) DRILL METHOD: Rotary Air Rotary Mud Cable Auger $ $ Other Other	City KE/ZER State (2) TYPE OF WORK (3) Depening Alteration (repair/recondition) (3) DRILL METHOD:	Zip 973 (
2) TYPE OF WORK New Well Deepening Alteration (repair/recondition) Abandonn 3) DRILL METHOD: Rotary Air Rotary Mud Cable Auger Other	(2) TYPE OF WORK New Well Deepening Alteration (repair/recondition) Abandonn (3) DRILL METHOD: Rotary Mud Cable Auger Other	 (2) TYPE OF WORK New Well Deepening Alteration (repair/recondition) (3) DRILL METHOD: Rotary Air Rotary Mud Cable Auger Other	n) 🗌 Abandonm
New Well Deepening Alteration (repair/recondition) Abandonn 3) DRILL METHOD: Rotary Mud Cable Auger Rotary Air Rotary Mud Cable Auger Other	New Well Deepening Alteration (repair/recondition) Abandonn (3) DRILL METHOD: Rotary Air Rotary Mud Cable Auger Other	X New Well Deepening Alteration (repair/recondition) (3) DRILL METHOD:	
3) DRILL METHOD: Rotary Air Rotary Mud Cable Auger Other	(3) DRILL METHOD: □ Rotary Air □ Rotary Mud Cable □ Auger □ Other	(3) DRILL METHOD: Rotary Air Rotary Mud Cable Auger Other	
Rotary Air Rotary Mud Cable Auger Other	□ Rotary Air □ Rotary Mud □ Cable □ Auger □ Other	□ Rotary Air □ Rotary Mud ▲ Cable □ Auger □ Other	
Other 4) PROPOSED USE: Domestic Community Injection Livestock Other 5) BORE HOLE CONSTRUCTION: Special Construction approval Yes No Depth of Completed Well Explosives used Yes No Type Amount HOLE SEAL Diameter From To Sacks or pounds 100 10 CEMENT 70 SS 12 70 290	□ Other	Other Other Other Domestic	
Domestic Community Industrial Irrigation Thermal Injection Livestock Other 5) BORE HOLE CONSTRUCTION: Sepecial Construction approval Yes No Depth of Completed Well Explosives used Yes HOLE SEAL To Material From To Sacks or pounds 16 0 70 12 70 290 290 Amount 400 0 12 70 290 290 Amount 12 70 290 290 Backfill placed from ft. to ft.	□ Domestic X Community □ Industrial □ Irrigation □ Thermal □ Injection □ Livestock □ Other	Domestic Community Industrial Irrigation Thermal Injection Livestock Other (5) BORE HOLE CONSTRUCTION: Special Construction approval Yes No Depth of Con Explosives used Yes No TypeAm	
Thermal Injection Livestock Other 5) BORE HOLE CONSTRUCTION: special Construction approval Yes No Depth of Completed Well Explosives used Yes No Type Amount HOLE SEAL Diameter From To Sacks or pounds /2 70 270 270 How was seal placed: Method A B C D I C Other TREMIE Render Render From To Gauge Steel Plastic Welded Thread I and the steel Interval I and the steel I and th	□ Thermal □ Injection □ Livestock □ Other	□ Thermal □ Injection □ Livestock □ Other (5) BORE HOLE CONSTRUCTION: Special Construction approval □ Yes No Depth of Con Explosives used □ Yes No Type Am	
5) BORE HOLE CONSTRUCTION: special Construction approval Yes No Depth of Completed Well 27 Explosives used Yes No Type Amount	(5) BORE HOLE CONSTRUCTION: Special Construction approval □ Yes No Depth of Completed Well Zi Explosives used □ Yes No Type Amount	(5) BORE HOLE CONSTRUCTION: Special Construction approval Explosives used Yes No Type Am	~~~~
Special Construction approval Yes No Depth of Completed Well Explosives used Yes No Type Amount HOLE SEAL Diameter From To Sacks or pounds 10 10 10 10 10 12 10 290 10 10 10 10 10 10 10 12 10 290 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10	Special Construction approval Yes No Depth of Completed Well Explosives used Yes No Type HOLE SEAL Diameter From To Material From To Material From To Sacks or pounds 12 90 290 290 How was scal placed: Method How was scal placed: Method A B C D How was scal placed: Method A B C D I Other TREMIS RROM 90' TO Size of gravel How was scal placed fromft. toft. MaterialGravel placed fromft. toft. Size of gravel	Special Construction approval Yes No Depth of Con Explosives used Yes No Type Am	
Amount	Explosives used Yes No Type Amount HOLE SEAL Diameter From To Sacks or pounds 12 90 290 90 35 12 90 290 90 35 12 90 290 90 35 12 90 290 90 55 How was scal placed: Method A B C D How was scal placed: Method A B C D I How was scal placed: Method A B C D I How was scal placed from ft. to ft. Material	Explosives used 🗆 Yes 🗶 No Type Am	npleted Well
Diameter From To Sacks or pounds 16 0 70 $CEMENT$ 0 70 $8cks$ or pounds 12 70 270 0 70 $8cks$ or pounds 12 70 270 0 70 $8cks$ or pounds 12 70 270 0 10 10 100 was seal placed: Method A B C D 100 other $TREMIS$ $RRom 90' To SAEFACE Backfill placed from ft. to ft. Material acksing ackfill placed from ft. to ft. Sacks of gravel acksing ackfill placed from ft. ft. Size of gravel acksing $	Diameter From To Material From To Sacks or pounds $\begin{array}{ c c c c c c c c c c c c c c c c c c c$	HOLE SEAL	ount
16 0 90 $CEMBUT$ 0 90 \overline{SS} 12 90 290	16 0 90 \overline{SS} 12 90 290 \overline{SS} 12 90 290 \overline{SS} How was seal placed: Method A B C D B How was seal placed: Method A B C D D How was seal placed: Method A B C D D Backfill placed from ft. to ft. Material	Diameter From To Material From To	Sacks or nounds
How was seal placed: Method A B C D B Other $TREMIS$ $RRom$ $90'$ TO $SVEFACE$ Backfill placed from ft. toft. Material	How was seal placed: Method A B C D B How was seal placed: Method A B C D D Material TO $SVRFACE$ $Backfill placed fromft. D_{aterial} D_{aterial} D_{aterial} Gravel placed fromft. toft. D_{aterial} D_{aterial} D_{aterial} D_{aterial} (6) CASING/LINER: Diameter From TO Gauge Plastic Welded Thread (6) CASING/LINER: Diameter From TO Gauge Plastic Welded Thread (6) CASING/LINER: Diameter From TO Gauge Plastic Welded Thread (6) CASING/LINER: Diameter From D_{aterial} $	16 0 90 CREMBAUT 0 90	Sacks of publics
Other TREMIE Rom 90' To SURFACE Backfill placed from ft. to ft. Material Gravel placed from ft. to ft. Size of gravel Gother ft. to ft. Size of gravel Gravel placed from ft. to ft. Size of gravel Gother From ft. Gauge Steel Plastic Welded Thread Gother 122 120 375 120 Gauge 122 120 375 120 Gauge 120 120 120 120	Product TREMIS Rom 90' TO SURFACE Backfill placed fromft. toft. Material Gravel placed fromft. toft. Size of gravel (6) CASING/LINER: Diameter From To Gauge Steel Plastic Welded Thread (6) CASING/LINER: Diameter From To Gauge Steel Plastic Welded Thread Casing: 12 12 12 .375 Image: Im	12 90 290	
Other TREMIE Rom 90' To SURFACE Backfill placed from ft. to ft. Material Gravel placed from ft. to ft. Size of gravel Gother ft. to ft. Size of gravel Gravel placed from ft. to ft. Size of gravel Gother From ft. Gauge Steel Plastic Welded Thread Gother 122 120 375 120 Gauge 122 120 375 120 Gauge 120 120 120 120	Product TREMIS Rom 90' TO SURFACE Backfill placed fromft. toft. Material Gravel placed fromft. toft. Size of gravel (6) CASING/LINER: Diameter From To Gauge Steel Plastic Welded Thread (6) CASING/LINER: Diameter From To Gauge Steel Plastic Welded Thread Casing: 12 12 12 .375 Image: Im		
Other TREMIE Rom 90' To SURFACE Backfill placed from ft. to ft. Material Gravel placed from ft. to ft. Size of gravel Gother ft. to ft. Size of gravel Gravel placed from ft. to ft. Size of gravel Gother From ft. Gauge Steel Plastic Welded Thread Gother 122 120 375 120 Gauge 122 120 375 120 Gauge 120 120 120 120	Product TREMIS Rom 90' TO SURFACE Backfill placed fromft. toft. Material Gravel placed fromft. toft. Size of gravel (6) CASING/LINER: Diameter From To Gauge Steel Plastic Welded Thread (6) CASING/LINER: Diameter From To Gauge Steel Plastic Welded Thread Casing: 12 12 12 .375 Image: Im	How was seal placed: Method $\Box A \Box B \Box C$	
Backfill placed fromft. toft. Material Gravel placed fromft. toft. Size of gravel 6) CASING/LINER: Diameter From To Gauge Steel Plastic Welded Thread Casing: 12 + 2 /70 : 375 \square Liner: \square \square \square Liner: \square \square \square \square Drive Shoe used \square Inside \blacksquare Outside \square None Final location of shoe(s) <u>CuT / LEFT ON BOTTEM</u> TOPERFORATIONS/SCREENS: \square Perforations Method Screens Type <u>V -w/RE</u> Material <u>STAINLE</u> From To size Number Diameter size Casing Li (70 / 75 = 0.050	Backfill placed fromft. toft. Material Gravel placed fromft. toft. Size of gravel (6) CASING/LINER: Diameter From To Gauge Steel Plastic Welded Thread Casing: 12 12 12 375 \square \square Liner:	Other TREMIE FROM 90' TO SURF	ACE
6) CASING/LINER: Diameter From To Gauge Steel Plastic Welded Thread Casing: 12 + 2 /70 : 375 [X]	(6) CASING/LINER: Diameter From To Gauge Steel Plastic Welded Thread Casing: 12 + 2 /70 .375 \square \square \square Casing: 12 + 2 /70 .375 \square \square Casing: 12 + 2 /70 .375 \square \square Casing: 12 + 2 /70 .375 \square Casing: 12 + 2 /20 .375 \square Casing: 12	/	
Diameter From To Gauge Stell Plastic Welded Thread Casing: 12 12 170 375 2 $1100000000000000000000000000000000000$	Diameter From To Gauge Stel Plastic Welded Thread Casing: 12 12 12 1375 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12 12		gravel
Casing: 12 12 170 375 \square \square Casing: 12 12 170 375 \square \square \square Casing: 12 120 375 \square	Casing: 12 $+2$ 170 375 10 0 0 12 170 375 10 0 0 0 0 0 0 0 0 0		11/-13 - 3 /09
iner:	Liner: \square	19 120 12°K H	
Drive Shoe used Inside Outside None Final location of shoe(s) <u>OUT / LEFT ON BOTTEM</u> 7) PERFORATIONS/SCREENS: Perforations Method Screens Type <u>V-wIRE</u> Material <u>STAINLE</u> Slot Tele/pipe From To size Number Diameter size Casing Li 176 175 <u>SCREENS</u>	Drive Shoe used Inside Outside None Final location of shoe(s) Out Image: Control of the shoe		
Drive Shoe used Inside Outside None Final location of shoe(s) <u>OUT / LEFT ON BOTTEM</u> 7) PERFORATIONS/SCREENS: Perforations Method Screens Type <u>V-wIRE</u> Material <u>STAINLE</u> Slot Tele/pipe From To size Number Diameter size Casing Li 176 175 <u>SCREENS</u>	Drive Shoe used Inside Outside None Final location of shoe(s) Out Image: Control of the shoe		
Drive Shoe used Inside Outside None Final location of shoe(s) <u>OUT / LEFT ON BOTTEM</u> 7) PERFORATIONS/SCREENS: Perforations Method Screens Type <u>V-wIRE</u> Material <u>STAINLE</u> Slot Tele/pipe From To size Number Diameter size Casing Li 176 175 <u>SCREENS</u>	Drive Shoe used Inside Outside None Final location of shoe(s) Out Image: Control of the shoe		
Drive Shoe used Inside Outside None Final location of shoe(s) Out Image: Content of the state of th	Drive Shoe used ☐ Inside ☑ Outside ☐ None Final location of shoe(s) <u>CUT / LEFT ON BOTTEM</u> (7) PERFORATIONS/SCREENS: ☐ Perforations Method ☑ Screens Type <u>V - WIRE</u> Material <u>STAINLE</u> Slot Tele/pipe From To size Number Diameter size Casing Li 176 175 200 100 12 TELE []		
Sinal location of shoe(s) CUT LEFT ON BOTTEM 7) PERFORATIONS/SCREENS: □ Perforations Method Image: Solid structure Stot Tele/pipe Slot Tele/pipe From To size Number Diameter size 175 200 100 12 12 TELE Image: Slot Image: Slot	Final location of shoe(s) \mathcal{OUT} / LEFT ON BOTTEM (7) PERFORATIONS/SCREENS: \square Perforations Method \square Screens Type \mathcal{V} - \mathcal{W} / \mathcal{RE} Material STAINLE Slot Tele/pipe From To size Number Diameter size Casing 176 175 \mathcal{OSO} 12 TELE 175 2.00 12 TELE []		
□ Perforations Method ☑ Screens Type V - WIRE Material STAINLE Slot Tele/pipe From To size Number Diameter size Casing Li 70 175	□ Perforations Method Screens Type <u>V</u> -wiRE Material STAINLE Slot Tele/pipe From To size Number Diameter size Casing Li 176 175 ∞00 <u>12</u> TELE □ 175 200 .100 <u>12</u> TELE	Final location of shoe(s) CUT / LEFT ON BOTT	<u>em</u>
Screens Type V-w/RE Material STAINLE Slot Tele/pipe From To size Number Diameter size Casing Li 76 175 So 12"TELE Image: Casing Li 75 200 100 12 TELE Image: Casing Li	ScreensType $V - WIRE$ MaterialSTAINLESlotTele/pipeFromTosizeNumberDiametersizeCasingLi176175 ~ 050 \$ $12^{\prime\prime}$ TELE \Box \Box 175200 $\cdot 100$ 12 TELE \Box		
Slot Tele/pipe From To size Number Diameter size Casing Li 176 175 200 \$ 12" TELE I I 175 200 .100 12 TELE I	SlotTele/pipeFromTosizeNumberDiametersizeCasingLi 170 175 050 $12^{\prime\prime}$ $7ELE$ \Box 175 200 100 12 $7ELE$ \Box		TAILIT
FromTosizeNumberDiametersizeCasingLi 170 175 200 8 $12^{\prime\prime}$ TELE \Box \Box 175 200 100 12 TELE \Box	From To size Number Diameter size Casing Li 170 175 000 $12''TELE$ $17''TELE$ $17'' TELE$ $17'$	X	
75 200 .100 12 TELE	175 200 .100 12 TELE [From To size Number Diameter size	
200 240 035 1 / 2 15/F 🗖 👘			
	24/ 0/6 /2: 44/1/		
		Drive Shoe usedInsideOutsideNoneFinal location of shoe(s) \mathcal{OUT} \mathcal{L} \mathcal{FT} \mathcal{OH} (7) PERFORATIONS/SCREENS: \square PerforationsMethod \square ScreensType \mathcal{V} \mathcal{W} FromTosizeNumberDiameter170175 \mathcal{OOO} \mathcal{I} \mathcal{TELE} \mathcal{I} 200 \mathcal{I} \mathcal{OO} \mathcal{I} 200240 \mathcal{OOS} \mathcal{I} \mathcal{TELE}	Casing

	DALE	IDE	1	
	<u> </u>	182	935	
	START CARD	# W 160	6123	
	START CARD	#		-, ·
LOCATION OF	WELL by legal	description:		·
County MAYION	Latitude	l	.ongitude	
Township 7	N or SRange	3	E or W	WM.
County <u>Marion</u> Township 7 Section 2	NW 1/4	NW	1/4	
Tax Lot Lo				
Street Address of We	ell (or nearest address	SW Corne		
INE + Richn	nand Rd NE			<u> </u>
) STATIC WATE	R LEVEL:			10.01
29 ft. bel			Date <u>6</u>	
Artesian pressure		square inch	Date	
WATER BEARI		,		
th at which water wa	s first found	34'		
		Estimated		SWL
From 34	<u>To</u>	Estimated /5		3WL 29
		500		<u> </u>
170	240			29
265	280	20	<u> </u>	29
				╀───┥
		L		
WELL LOG:				
	d Elevation			
		From	То	SWL
Groun Materi Zown Sandy Sid	al	From	2	SWL
Groun Materi 20WN SANDY SIL	al		·	SWL
Groun	al LT T / LRAVELS	6	2	SWL
Groun Materia DOWN SANDY SIL DOWN SANDY SIL DIVSANO W/GU IRSE SAND / GR	ai LT LT / LRAVCUS RAVELS DAVELS	6 9 18 51	9 18	SWL
Groun Materia DOWN SANDY SIL DOWN SANDY SIL DIVSANO W/GU IRSE SAND / GR	ai LT LT / LRAVCUS RAVELS DAVELS	0 9 18	9 18 51	SWL
Groun Materia DWA SANDY SIL DWA SANDY SIL DYSAND W/G IRSE SAND / GL TY SAND / SMA EY CLAY W/LA	al LT T / LRAVOUS RAVELS 2A VELS LL LRAVEL ZG GRAVELS	6 9 18 51	9 18 51 62	SWL
Groun Materia BOWN SANDY SIL DWN SANDY SIL LTYSAND W/GU LTYSAND / GU LTY SAND / SMA LTY GREY SAND	al LT T / LRAVELS RAVELS AVELS AVELS TL GRAVELS S GRAVELS	6 9 18 51 67 71 73	9 18 51 62 71 73 78	SWL
Groun Materia DWN SANDY SIL DWN SANDY SIL DWN SAND SIL DYSAND W/G DYSAND / SMA DY SAND / SMA DY CLAY W/LA TY GREY SAND C REY CLAY	al LT T / LIRAVOIS RAVELS 24 VELS 24 LE LIRAVEL 26 GRAVELS 5 GRAVELS	6 9 18 51 67 71 73 78	9 18 51 62 71 73 78 98	SWL
Groun Materia DWN SANDY SIL DWN SANDY SIL DWN SAND W/GU DYSAND W/GU TY SAND / SMA EY CLAY W/LA TY GREY SAND C REY CLAY	al LT T / LIRAVOIS RAVELS 24 VELS 24 LE LIRAVEL 26 GRAVELS 5 GRAVELS	6 9 18 51 67 71 73	9 18 51 62 71 73 78	SWL
Groun Materia ROWA SANDY SIL DWA SANDY SIL DYSAND W/G DRSE SAND / G TY SAND / SMA EY CLAY W/LA EY CLAY W/LA EY CLAY EY CLAY EY SILT / LRG EAN SAND / G	ai LT LT LAVELS RAVELS AVELS AVELS CRAVELS CRAVELS CRAVELS RAVEL	6 9 18 51 67 71 73 78	9 18 51 62 71 73 78 98	SWL
Groun Materia DWA SANDY SIL DWA SANDY SIL DYSAND W/G DRSE SAND / G DYSAND / SMA EY CLAY W/LA EY CLAY W/LA EY CLAY EY SILT / LRG EAN SAND / GU LTY GRAVEL	al LT T/LRAVELS RAVELS 2AVELS HL LRAVEL ZG GRAVELS GRAVELS GRAVELS 2AVEL / SANG	6 9 18 51 62 71 73 78 98	9 18 51 62 71 73 78 98 125	SWL
Groun Materia DWN SANDY SIL DWN SANDY SIL DWN SANDY SIL DYSAND W/GU DRSE SAND / GU TY SAND / SMA REY CLAY W/LA DEY SILT / LRG RAN SAND / GU EAN SAND / GU	al LT T / LRAVELS RAVELS AVELS LL GRAVELS C GRAVELS C GRAVELS C GRAVEL AVEL / SANLS GRAVEL	6 9 18 51 67 71 73 78 98 98 126	9 18 51 62 71 73 78 98 125 131 146 152	SWL
Groun Materia DOWN SANDY SIL DOWN SANDY SIL DIYSAND W/G IRSE SAND / G IRSE SAND / G IY SAND / SMA EY CLAY W/LA EY CLAY W/LA EY CLAY W/LA EY CLAY EAN SAND / G EAN SAND / G	al LT T / LIRAVOUS RAVELS AVELS AVELS CEAVELS CEAVELS CEAVELS AVEL / SANS GRAVELS / LIRAVELS	6 9 18 51 67 71 73 78 98 126 131	9 18 51 62 71 73 78 98 125 131 146	
Groun Materia BOWN SANDY SIL DWN SANDY SIL DWN SANDY SIL DWN SANDY SIL DWN SANDY SIL DWN SANDY SIL DY SAND / G REY CLAY DEY SILT / LRO REY CLAY DEY SILT / LRO REY CLAY DEY SILT / LRO RAN SAND / G EAN SAND / G LTY COBBLES BAN GRAVEL	al LT LT LT LAVELS RAVELS AVELS LL GRAVELS S GRAVELS GRAVELS GRAVEL SANG GRAVEL JGRAVELS JGRAVELS JGRAVELS	6 9 18 51 62 71 73 78 98 126 131 146 152 (9)	9 18 51 62 71 73 78 98 125 131 146 152 141 210	
Groun Materia COWN SANDY SIL DWN SANDY SIL DWN SANDY SIL DWN SANDY SIL DWN SANDY SIL DY SAND / GU TY SAND / GU EY CLAY W/ LA EY CLAY W/ LA EY CLAY EY CLAY EY CLAY EY CLAY EY CLAY EY CLAY EY CLAY EY CLAY EY CLAY EY CLAY EX SAND / G EAN SAND / G LTY COBBLES	al LT LT LT LAVELS RAVELS AVELS LL GRAVELS S GRAVELS CEAVELS CEAVELS CEAVELS CAVEL / SANS / GRAVEL / SANS / GRAVEL	6 9 18 51 67 71 73 78 98 78 98 126 131 146 152	9 18 51 62 71 73 78 98 125 131 146 152 141	
Groun Materia DOWN SANDY SIL DOWN SANDY SIL DOWN SANDY SIL DIYSAND W/G. TYSAND /G. TYSAND /G. TY GREY SAND G EY CLAY DEY COBBLES DEAN SAND /G DESS DEAN SAND /G	al LT T / LRAVELS RAVELS RAVELS AVELS AVELS CEAVELS CEAVELS CEAVELS AVEL / SANS / LRAVEL / SANS / LRAVEL RAVEL RAVEL	6 9 18 51 67 71 73 78 98 126 131 146 131 146 152 191 210 214	9 18 51 62 71 73 78 98 125 131 146 152 141 210	
Groun Materia 2000 A SANDY SIL 2000 A SANDY S	al LT T / LRAVELS RAVELS RAVELS AVELS AVELS CEAVELS CEAVELS CEAVELS AVEL / SANS / SANS	6 9 18 51 67 71 73 78 98 126 131 146 131 146 152 191 210 214 219	9 18 51 62 71 73 78 98 125 131 146 152 141 210 214 219 227	
Groun Materia 2000 A SANDY SIL 2000 A SAND / GANGL 2000 A SAND / GANGL	al LT T / LRAVELS RAVELS RAVELS AVELS AVELS CEAVELS CEAVELS CEAVELS CEAVELS CAVEL / SANS / LARAVEL / SANS / LARAVEL S / CEAVEL S / COBOLES	6 9 18 51 67 71 73 78 98 126 131 146 132 191 210 214 219 217	9 18 51 62 71 73 78 98 125 131 146 152 141 210 214 219	
Groun Materia DOWN SANDY SIL DOWN SANDY SIL DIYSAND W/G DISE SAND / G DISE SAND / G TY GREY SAND EY CLAY EY CLAY CLAY COBBLES EAN SAND / G EAN SAND / G	al LT T / LRAVELS RAVELS RAVELS AVELS AVELS CEAVELS CEAVELS CEAVELS CEAVELS CAVEL / SANS / LARAVEL / SANS / LARAVEL S / CEAVEL S / COBOLES	6 9 18 51 67 71 73 78 98 78 98 78 98 78 78 78 78 78 78 78 78 78 78 78 78 78	9 18 51 62 71 73 78 98 125 131 146 152 141 210 214 219 227	

(unbonded) Water Well Constructor Certification:

I certify that the work I performed on the construction, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to the best of my knowledge and belief.

1829 WWC Number Date ned .

(bonded) Water Well Constructor Certification:

I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief. WWC Number

06

Date _

ORIGINAL - WATER RESOURCES DEPARTMENT

Depth of strata:

ALEN ODECON

ARTMENT FIRST COPY - CONSTRUCTOR SECOND COPY - CUSTOMER

Signed

MARI 60019

ST	ATE OF	OREG	ON						PAGE	E 2 OF	- 2 _	
			ELL RE	PORT					WELL I.D. #	L	935	
	equired by								START CAR) # <u>w 166</u>	123	
Instru	ctions for	comple	ting this r	eport are on	the last	page of th	is form.					
(1) L	AND OW	VNER	= <u> KE</u>	760	Well Nu	mber	6	(9) LOCATION O				
Addre	. 6	730	CHEM	AWA	RD				N Latitude			
	KEIZI		<u>C 11-717</u>	State	OR	Zin	97307		N ogRang			WM.
	PE OF		7		0~	2.0	11201		LotBlo			
• •	_		_	eration (repair	/recondi	tion) 🗆 At	andonment		Lot Blo Well (or nearest addres			
<u> </u>	RILL MI	<u>.</u>	-					Red NE + Ric	hell (or nearest addres	NE COM		MET MAN
				Cable 🛛 A	uger			(10) STATIC WAT				
Oth			^						elow land surface.		Date	
(4) PI	ROPOSE	D USE	:					Artesian pressure _	lb. per	square inch	Date	
				dustrial 🗌	_			(11) WATER BEA	RING ZONES:			<u>`</u>
_				ivestock	Other_			Depth at which water	une front found			
							(-)] F a					
				e No Dep				From	To	Estimated	Flow Rate	SWL
2.10.0	HOLE	<u> </u>		SEAL					MICI			\vdash
Diamet	er From	To	Materi	al From	То	Sacks or p	ounds		PAGE 1			
	SE	F 2	ALE ,	_								
			100-1	,								
	-							(12) WELL LOG:				
How w	as seal pla	ced:	Method		BC		Ē		and Elevation			
🗌 Oth	er											
	•		ft. to			al		Mate		From	То	SWL
				ft.	Size of	gravel		SILTY COBBLE		238	246	
(6) CA	SING/L							SILTBOUND GI		246	250	
		r From	n To G	auge Steel	_	Welded		SILTY COB		250	259	
Casing:	SEE	246	E /					GREY SAND S		259	269	├ ──┤
								GREY SILTY SAN BLUE CLAY W		269	277 281	
								FINE TO ME		281	285	
Liner:								GREY STIPF		285	290	
								Cherry Cr.		0.00		<u> </u>
				de 🗌 None						<u> </u>		
			CONT	and the second						,		
	RFORA Perforation		SCREE	NS:				DEA	CIMPA			
	creens	3		WIRE	Ma	terial 57	AINLESS	TEU				
		Slot	-) po _ u		Tele/pi				0.000			
From	To			Diameter	size	Casing	Liner	JAN 2	2 2 2008			
265	280	.125		12	TEL							
280	290	BLA	<u> </u>	10"		<u> </u>			OURCES DEPT			
								SALEM	OREGON			
		_	<u></u>								1	
(8) WI	ELL TES	STS: M	linimum	testing time	e is 1 h			Date started		npleted		_
⊡ռ	mp	🗆 Ba	iler	🗆 Air			wing sian	(unbonded) Water Well				
	gal/min		wdown	Drill ste	m at		Time	l certify that the wor ment of this well is in co	k I performed on the multiance with Orego			
			•				l hr.	standards. Materials used				
			_					knowledge and belief.	1.1	WWC Nu	mber 18.	29
								Signed Tree R	Nul		Date	···de
Temper	ture of	aler		Depth Artesia	n Flow	Found		(bonded) Water Well C				
•	ater analy			s By whon					y for the construction		bandonment v	vork
	•			ble for intend			oo little	performed on this well d	uring the construction	dates reported a	bove. All wor	
-				Colored		_		performed during this tin construction spundards		e best of my kno	owledge-and b	1.3
		•						1 1 Kela	lan	WWC Nut	mber 🥢	2-12
								Signed Mary	you -	<u> </u>	Date 7-	

ORIGINAL – WATER RESOURCES DEPARTMENT FIRST COPY – CONSTRUCTOR SECOND COPY – CUSTOMER