The original and first cor of this report are to b filed with the STATE ENGINEER, SALEM, ORECON

Gravel placed from

Size of gravel:

Was well gravel packed?
Yes I No

STATE OF OREGONMAY 1 9 1975 (Please t

State Well No. 25- /w-5

STATE ENGINEER, SALEM, ORECON More (Please type within 30 days from the date of well completion. (Do not write ab	or print) STATE ENGINEER State Permit N	o
	STATE ENGINEER State Permit N SALEM, OREGON	
(1) OWNER:	(10) LOCATION OF WELL:	
Name Great Gary Bean	County Marion Driller's well no	ımber '4
Address 1908 Weis Net	14 14 Section T. 23	R. / (4) W.M.
SAlem Oregon	Bearing and distance from section or subdivisi	on corner
(2) TYPE OF WORK (check):		
New Well ☐ Deepening Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	vell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.	
Rotary Driven Domestic Industrial Municipal	Static level 20 ft. below land surface. Date 4-30-25	
Cable	Artesian pressure lbs. per squar	
CASING INSTALLED: Threaded	(12) WELL LOG: Diameter of well below casing ft. Depth drilled 200 ft. Formation: Describe color, texture, grain size and structure of materials;	
PERFORATIONS: Perforated? Yes No.	and show thickness and nature of each stratu with at least one entry for each change of forma position of Static Water Level and indicate prin	m and aquifer penetrated, tion. Report each change in
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	BASA (+	155 159
perforations fromft. toft.	wentherd out Rock	159 162
perforations from ft. to ft.	Tuffstone	162 166
perforations fromft. toft.	Gravel	66 67
· · · · · · · · · · · · · · · · · · ·	CLAY Brown	162 175
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Talfstone	125 194
Manufacturer's Name	BASAIT Broken	194 200
Type Model No		
Diam Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.	F- 074447A	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? Yes No If yes, by whom?	,	
Yield: gal./min. with ft. drawdown after hrs.		
<i>"</i> " " " " " " " " " " " " " " " " " "		
" " " "		
Har test 1/1) gal./min. with 50 ft. drawdown after / hrs.		
perature of water Depth artesian flow encountered ft.	Work started 4-23 1925 Complete	$\frac{19}{25}$
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4-30 1975
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface to ft.	This well was constructed under my Materials used and information reported	
Diameter of well bore to bottom of seal in.	best knowledge and belief.	
Diameter of well bore below seal in.	[Signed] (Drilling Machine Operator)	Date 5-12, 1925
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	
Number of sacks of bentonite used in well seal sacks	Diamig Machine Operator's License No.	······································
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is	
of water lbs./100 gals.	true to the best of my knowledge and belief.	
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Dobingon Eola	Drilling
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address 45/6 DAMAS 4	wy SAlomore
Method of sealing strata off	[Signed] Story H. Molindon	
Was well gravel packed? [] Yes [] No. Size of gravel.	(Water Well Contr	actor)