NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

6180 MARI.....

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED
OCT 22 1976
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 7s/1w-9aa
Permit No.

(1) OWNER:
Name Otto Stadeli
Address 3918 Cascade Highway N.E.
Silverton, OR 97381

(2) TYPE OF WORK (check):
New Well ☐ Deepening ☒ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

CASING INSTALLED:
Threaded ☐ Welded ☐
" Diam. from Orig. ft. to ft. Gage
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " "
" " "
Air test 200 gal./min. with ft. drawdown after 2 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Original
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Marion Driller's well number
N.E. ¼ N.E. ¼ Section 9 T. 7 S. R. 1 W. W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found ft.
Static level 30 ft. below land surface. Date 9/16/76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 10"
Depth drilled 165 ft. Depth of completed well 246 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Basalt grey hard	81	117	
Basalt grey porous	117	121	
Basalt weathered brown	121	139	
Basalt grey seamy	139	246	W.B.

Work started 8/30/76 19 Completed 9/16/76 19
Date well drilling machine moved off of well 9/16/76 19

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Robert Boydston Date 10-1, 1976
(Drilling Machine Operator)
Drilling Machine Operator's License No. 646

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name R. Stadeli & Sons, Inc.
(Person, firm or corporation) (Type or print)
Address 11364 Evgrn. Rd. NE Silverton, OR 97381
[Signed] Paul R. Stadeli
(Water Well Contractor)
Contractor's License No. 296 Date 9-30, 1976

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119