NOTICE TO WATER WELL CONTRACTOR The original and first copy			
of this report are to be filed with the	OREGON CELVE STATE WELL NO.	75 /IW.	The
STATE ENGINEER, SALEM, OREGON 97310 (Please type		,	
within 30 days from the date of well completion. (Do not write ab	ove this line) OVER RESOURCES DEDT)	
(1) OWNER:	(10) LOCATION OF WELL:		-
Name Wayne Zurbrugg	County Marion Driller's well number		
Address 11834 Evergreen Rd. NE	S.E. 4N.W. 4 Section 9 T. 7 S R. 1 W W.M.		
Silverton OR 97381			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner 1500' S. & 1500' E. of N.W. corner of Section		
New Well ☐ Deepening ♣ Reconditioning ☐ Abandon ☐	9. T 7S R IW		
If abandonment, describe material and procedure in Item 12.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.		
	Depth at which water was first found 207 ft.		
Cable	Static level 81 ft. below land surface. Date 10/15/76		
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per squar	e inch. Date	,
CASING INSTALLED: Threaded Welded	(19) WEIT LOC.		6"
" Diam. from ORIGINAL to ft. Gage 250			
ft. Gage	Depth drilled 1.69 ft. Depth of completed well 290 ft.		
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each strature.		
	with at least one entry for each change of format	tion. Report each	change in
PERFORATIONS: Perforated? Yes X No.	position of Static Water Level and indicate prin	cipal water-bear	ing strata.
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Basalt grey hard	121 182	
perforations from ft. to ft.	Basalt weathered	182 191	7
perforations from ft. to ft.	Basalt grey seamy	191 211	
perforations from ft. to ft.	Basalt grey crevacy	211 290	W.B.
(7) SCREENS: Well screen installed? Yes X No			
Manufacturer's Name			-
Type Model No.	Francisco Philade - Table to		
Diam Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is			
lowered below static level	The state of the s		
Was a pump test made? Yes No If yes, by whom? What: \$2.5 gal./min. with /27 ft. drawdown after 2 hrs.		<u> </u>	
	<u></u>		
7 54 " 152 " s "			
Aim 6/ " 177 " " "			
partir test 62 gal./min. with 201 ft. drawdown after 2 hrs.	-		
esian flow g.p.m.			
mperature of water Depth artesian flow encountered ft.	Work started 10/12/76 19 Complete	ed 10/15/76	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	10/15/76	19
• •	Drilling Machine Operator's Certification:		
Well seal-Material used ORIGINAL	This well was constructed under my	direct supe	rvision.
I sealed from land surface toft.	Materials used and information reported	above are tru	e to my
Diameter of well bore to bottom of sealin.	best knowledge and belief. [Signed] Redert Baydston	11-18	76
Diameter of well bore below sealin.	(Drilling Machine Öperator)		
Number of sacks of cement used in well sealsacks Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	by y	
Brand name of bentonite			
Number of pounds of bentonite per 100 gailons	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Yes No Plugs Size: location ft.	·		
Did any strata contain unusable water? Yes X No	Name R. Stadeli & Sons. Inc. (Person, firm or corporation)	(Type or p	rint)
Type of water? depth of strata	Address 1364 Evgrn Rd NE Silverton, OR 97381		
Method of sealing strata off	[Signed] Gaul W. Stad	eli	
Was well gravel packed? Yes X No Size of gravel:	(Water Well Contr	•	ر سے
Gravel placed from ft. to ft.	Contractor's License No. 296 Date	1-18	, 19 Z