## **MARI 62801**

## STATE OF OREGON WATER SUPPLY WELL REPORT

Westerberg Drilling, Inc. 36728 S. Kropf Rd. Molalla, OR 97038

| WELL I.D. # L | 93417 |
|---------------|-------|
|               |       |

START CARD # 201556

(as required by ORS 537.765)

| Instructions for completing this report are on the last page of this form.   |   |  |
|--|---|--|
| (1) LAND OWNER Well Number   | (9) LOCATION OF WELL (legal description) County Marlon  |  |
| Address 16484 S. Abiqua Rd. NE   | Tax Lot Lot   |  |
| City Silverton State OR Zip 97381  | Township 6 S Range 2 W WM   |  |
| (2) TYPE OF WORK ☐ New Well ☐ Deepening ☑ Alteration (repair/recondition) ☐ Abandonment ☐ Conversion   | Section 25         NW         1/4 NE         1/4           Lat         o         '         " or         (degrees or decimal)           Long         o         '         " or         (degrees or decimal) |  |
| (3) DRILL METHOD  ☐ Rotary Air ☐ Rotary Mud ☑ Cable ☐ Auger ☐ Cable Mud ☐ Other  | Street Address of Well (or nearest address) No Address  Howell Praire Rd NE (E. Side)   |  |
| (4) PROPOSED USE  ☐ Domestic ☐ Community ☐ Industrial ☐ Irrigation ☐ Thermal ☐ Injection ☐ Livestock ☐ Other   | (10) STATIC WATER LEVEL         57.5       ft. below land surface.        ft. below land surface.       Date  |  |
| (5) BORE HOLE CONSTRUCTION Special Construction: Yes No Depth of Completed Well 215 ft.  | Artesian pressure lb. per square inch Date  |  |
| Explosives used: Yes V No Type Amount  | (11) WATER BEARING ZONES Depth at which water was first found See MARI 62243  |  |
| BORE HOLE SEAL Diameter From To Material From To Sacks or Pounds   | From To Estimated Flow Rate SWL   |  |
| See Original Well Log MARI 52243   |   |  |
| How was seal placed: Method ABCDDE   |   |  |
| Other No Seal Change   | (12) WELL LOG Ground Elevation  |  |
| Backfill placed from 213 ft. to 215 ft. Material Cement Plug   | Material From To SWL  |  |
| Gravel placed from <u>0</u> ft. to <u>215</u> ft. Size of gravel <u>6/9 CSS</u>  | No Drilling Performed   |  |
| (6) CASING/LINER Diameter From To Gauge Steel Plastic Welded Threaded  |   |  |
| Casing:  |   |  |
| Liner: 10" +2 146 .250   | RECEIVED  |  |
|  |   |  |
| Liner: 10" +2 146 .250   | DE († 2 4 2009  |  |
|  |   |  |
| Drive Shoe used Inside Outside None  Final location of shoe(s) None on 10"   | WATER RESOURCES DEPT  |  |
| That recation of shee(s) 140He on 10   | SALEM, OREGON   |  |
| (7) PERFORATIONS/SCREENS  [X Perforations Method Mills Knife  [The Company of the |   |  |
| ✓ Screens Type V-Wire Material Stainless   | Date Started 11/05/09 Completed 12/16/09  |  |
| From To Slot Number Diameter Tele/pipe Casing Liner Size size  | (unbonded) Water Well Constructor Certification   |  |
| I certify that the work I performed on the construction, deepening, altera abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are to the best of my knowledge and belief.   |   |  |
| 153' 213' 3/8 x 3 1170 12"   | the best of my knowledge and belief.  |  |
|  | WWC Number Date   |  |
| (8) WELL TESTS: Minimum testing time is 1 hour Pump Bailer Air Flowing Artesian Signed   |   |  |
| Yield gal/min Drawdown Drill stem at Time (bonded) Water Well Constructor Certification  |   |  |
| 450 84 5 hr. I accept responsibility for the construction, deepening, alteration   |   |  |
|  | abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water  |  |
| supply well construction standards. This report is true to the best of my knowledge.   |   |  |
| Was a water analysis done? Yes By whom and belief.   |   |  |
| Did any strata contain water not suitable for intended use?  | WWC Number 668 Pate 12/21/09  |  |
| Salty Muddy Odor Colored Other   | 14 11   |  |
| Depth of strata: Signed  |   |  |