
## WATER WELL REPORT STATE OF OREGON



State Well N

State Well No. 75/10-17dC

EALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name JAMES G. KUENZI	County Marion Driller's well number 2688
Address 2103 Hibbard Rd. N.E.	SW 4 SE 4 Section 17 T. 7S R. 1W W.M.
City Silverton, Oregon 97381 State	Tax Lot # Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: 2103 Hibbard Rd. N.E.
New Well □ Deepening 🕅 Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found existing ft.
Potentia N Potentia N Potentia N N Potentia N N Potentia N N Potentia N N N N N N N N N N N N N N N N N N N	Static level 204 ft. below land surface. Date 5/13/87
Rotary Mud  Dug  Irrigation  Test Well  Other	Artesian pressure lbs. per square inch. Date
☐ Bored ☐ Thermal: Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel K Plastic D Welded A	Depth drilled 282 ft. Depth of completed well 281 ft.
NO CASING INSTALLED	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry
Diam from ft. to ft. Gauge	for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
LINER INSTALLED:	
The state of the s	MATERIAL From To SWL
4"Diam. from	Hard Black Basalt 243 255
(6) PERFORATIONS: Perforated? X Yes □ No LINER ON	LyBlack Basalt with shale strips
Type of perforator used XX Skilsaw	and_two_cavitites_about
Size of perforations 1/8 in. by 8 in.	one foot thick. W.B. 255 276
	Sticky Blue Clay 276 282
perforations from	
perforations from ft. to ft.	XXX Air circulation was frequently
(7) SCREENS: Well screen installed? ☐ Yes 🗓 No	lost during drilling operation below
Manufacturer's Name	2 55 feet, A neoprene packer was
Type   Model No.     Diam.   Slot Size   Set from   ft. to   ft.	placed on liner to rest at 240 feet,
	however packer may have been destroyed
Diam. Slot Size Set from ft. Drawdown is amount water level is lowered	during installation.
8) WELL TESTS:  Drawdown is amount water level is lowered below static level	
pump test made?   Yes No If yes, by whom?	
a. gal./min. with ft. drawdown after hrs.	
" " " " "	
Air test 25+ gal/min. with drill stem at 255 ft. 1 hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
perature of water Depth artesian flow encountered ft.	
	Work started 5/12/87 19 Completed 5/13/87 19
9) CONSTRUCTION: Special standards: Yes \( \simega \) No \( \sqrt{N} \)	Date well drilling machine moved off of well $5/13/87$ 19
Vellseal—MaterialusedExistingsealno.tdisturbed	Drilling Machine Operator's Certification:
Vell sealed from land surface to	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of sealin.	and information reported above are true to my best knowledge and belief. [Signed] Date 5/13 19.87
Further of sacks of cement used in well seal sacks	(Drilling Machine Operator)
low was cement grout placed?	Drilling Machine Operator's License No811
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to
Vas pump installed? Type HP Depth ft.	
Vas a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	Name WILLAMETTE DRILLING CO.  (Person, firm or corporation)  (Type or print)
lid any strata contain unusable water? □ Yes □ No	Address (300. U.Neil Rd. N.E. Salem. Oregon 97303
ype of Water? depth of strata	[Signed] Mod D Juli (Water Well Contractor)
lethod of sealing strata off	(Water Well Contractor)
Was well gravel packed? ☐ Yes ☐ Yes ☐ Size of gravel:	Contractor's License No. 753Date
reaves placed 110iii	