STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210) SEP 2 4 2010

WATER RESOURCES DEPT SALEM, OREGON

WELL LABEL # L	102925	_	 7	
START CARD#	205285			

(1) LAND OWNER Owner Well I.D.	(A) LOCATION OF WEY Y (I I I I - I'-			
	(9) LOCATION OF WELL (legal description)			
First Name Last Name		E/W WM		
Company TA OPERATING LLC	Sec 9 1/4 of the 1/4 Tax			
Address 24601 CENTER RIDGE RD City WESTLAKE State OH Zip 97493	Tax Map Number Lot			
	Lat " or 45.23666667 DMS or DD			
(2) TYPE OF WORK X New Well Deepening Conversion	Long " or 122.80694444	DMS or DD		
Alteration (repair/recondition) Abandonment	Street address of well Nearest address			
(2) DDILL METHOD	21856 BENTS RD NE AURORA, OR			
(3) DRILL METHOD Rotary Air Rotary Mud Cable Auger Cable Mud	(10) STATIC WATER LEVEL Date SWL(psi) + SWL(ft)			
Reverse Rotary Other		osi) + SWL(ft)		
(4) PROPOSED USE Domestic Irrigation Community	Existing Well / Predeepening Completed Well 09-01-2010			
Industrial/ Commercial Livestock Dewatering	Completed Well 09-01-2010 Flowing Artesian? Dry Ho	88		
Thermal Injection Other				
(5) BORE HOLE CONSTRUCTION Special Standard Attach copy)	WATER BEARING ZONES Depth water was firs			
Depth of Completed Well 221 ft.	SWL Date From To Est Flow SW 08-18-2010 28 28 5	(L(psi) + SWL(ft)		
BORE HOLE SEAL sacks/	08-23-2010 72 150 30	70		
Dia From To Material From To Amt Ibs	09-01-2010 170 221 125	88		
14 0 20 Bentonite 0 5 6 S				
12 20 70 Cement 5 70 40 S				
10 70 170 Cement 70 170 28 S	(11) WELL LOG Ground Flourism			
	Glound Elevation			
How was seal placed: Method A B X C D E	Material Fi	rom To		
Other A. Mariel	Silty brown clay with trace of sand	1 28		
Backfill placed from ft. to ft. Material Filter pack from ft. to ft. Material Size	Firm gray-blue clay	28 36		
	Blue-gray sticky and gritty clay	36 54		
Explosives used: Yes Type Amount	Tan clay	54 56		
(6) CASING/LINER	Brown clay	56 72		
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	Brown sand with brown binder	72 85		
	Red very fine sand and gravel Brown very sandy soft clay w/fine sandy seams	85 96 96 126		
	Fine brown sand with some gravels	126 144		
	Broken basalt dark w/brown dark sandy gravel	144 150		
	Hard dark gray basalt	150 170		
	Semi-fractured gray basalt	170 176		
Shoe Inside Outside Other Location of shoe(s)	Porous semi-broken gray basalt	176 185		
Temp casing Yes Dia From To	Weathered brown basalt Semi-fractured gray basalt	185 188		
(7) PERFORATIONS/SCREENS	Hard dark gray basalt with some fractured seams	188 190 190 221		
Perforations Method	Trade dark gray outstate with some fractured seams	170 221		
Screens Type Material				
Perf/S Casing/ Screen Scrn/slot Slot # of Tele/ creen Liner Dia From To width length slots pipe size	Date Started 08-17-2010 Completed 09	9-02-2010		
	(unbonded) Water Well Constructor Certification			
	I certify that the work I performed on the construction			
	abandonment of this well is in compliance with O construction standards. Materials used and information			
	the best of my knowledge and belief.	reported above are true to		
(8) WELL TESTS: Minimum testing time is 1 hour	License Number 1629 Date 09-07-2010			
Pump Bailer • Air Flowing Artesian	Password : (if filing electronically) Signed			
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)				
125 220 3	(bonded) Water Well Constructor Certification			
	I accept responsibility for the construction, deepening, alteration, or abandonment			
Temperature 53 t/7 °F Lab analysis Yes By	work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well			
Water quality concerns? Yes (describe below)	construction standards. This report is true to the best of my knowledge and belief.			
From To Description Amount Units	License Number 1 1273 Date 09-07-2010			
	Password: (if thing electronically) ****			
	Signed The Signed			
	Contact Info (optional)			