NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Permit No.

of well completion.			
(1) OWNER:	(10) LOCATION OF WELL:		
Name Moste Caspenter	County Marion Driller's well nu	mber	
Address 910 Casscale Dy ne Sales	1 14 14 Section 34 T.	R.	W.M.
(9) MVDE OF WORK (sheets):	Bearing and distance from section or subdivision	n common	•
(2) TYPE OF WORK (check):	-		
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.		
F Driven Domestic Industrial Municipal Domestic	Static level FO ft. below land s	urface.Date 🖇	16/8
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square	e inch. Date	
(5) CASING INSTALLED: Threaded Welded 5250 "Diam. from ft. to 62 ft. Gage 250 "Diam. from ft. to ft. Gage	(12) WELL LOG: Diameter of well below casing below drilled 222 ft. Depth of completed well 222 ft. Formation: Describe color, texture, grain size and structure of materials;		
"Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
(6) PERFORATIONS: Perforated? ☐ Yes ☑ No.			
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Med Clay	0 15	
perforations from ft. to ft.	- lock	15 30 30 56	
perforations from ft. to ft.	Cayplane	30 56	
perforations from ft. to ft.	Slave The	85 89	
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	Balet	99 150	
Manufacturer's Name	Clareston a	150 165	
Type Model No.	Babalt.	165 189	
Diam Slot size Set from ft. to ft.	Grey Tuffstone	189 220	
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is			
lowered below static level	12 (7) 2 H A H E 2		
s a pump test made? Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.	AUG 191980		•
<u>" " " " " " " " " " " " " " " " " " " </u>			
" " " "	WATER RESOURCES DEPT		
test 23 gal./min. with 140 ft. drawdown after hrs.	SALEM, OREGON		
Artesian flow g.p.m.	6 / 60	6-1	
Temperature of water Depth artesian flow encountered ft.	Work started 3-4 19 80 Complete		19 0
(9) CONSTRUCTION:	Date well drilling machine moved off of well	8-6	198
Well seal—Material used Comunt	Drilling Machine Operator's Certification:		
Well sealed from land surface to ft.	This well was constructed under my Materials used and information reported	above are true	to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.	1	
Diameter of well bore below seal in.	[Signed] Atman Ulfury Mahine Operators Date 8 - 8, 19 80		
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 455		
How was cement grout placed?	Diffing Machine Operator & Dicease 140.		
Funfied.	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? ☐ Yes TNo Plugs Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water? Yes No	NameEOLA WELL DRILLING (Person, firm of corporation RD. N.W	(Type or pri	int)
Type of water? depth of strata	Address SALEM OR 97300	, 	
Method of sealing strata off	Tank It Al Bo	- 1	
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	[Signed] (Water Well Contr	ractor)	•••••
	Contractor's License No. 6. Date	3-8	, 19 <i>8</i> .0
Gravel placed from ft. to ft.	Communication a filentian 140.	F	, 1062.0