NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report

are to be filed with the

WATER

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date

JUL 2 2 1979 (Please type or print)

tate Well No. State Permit No.

of well completion. WATER RESOURCES INCHAING IN	ove ans inte		
(1) OWNER:	(10) LOCATION OF WELL:		
Name Santos Garcia	County Marion Driller's well number 2215		
Address 4861 Howell Prairie Rd. NE	14 34 Section 1 T. 7S	R. 2W	W.M.
Silverton, Oregon 97381	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	Bearing and distance from section of subdivisi	on corner	
New Well → Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	- all	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Double of which were the second of the secon		
Rotary M Driven Cl	Depth at which water was first found 59		/22/70
Cable		surface. Date 5	/ 23/ 19
	Artesian pressure lbs. per squar	e inch. Date	
CASING INSTALLED: Threaded Welded W	(12) WELL LOG: Diameter of well below casing		
8 " Diam. from top ft. to 160 ft. Gage .250	Depth drilled 160 ft. Depth of completed well 160 ft.		
	Formation: Describe color, texture, grain size and structure of materials;		
ft. toft. Gage	and show thickness and nature of each stratum and aguifer penetrated.		
PERFORATIONS: Perforated? Y Yes No.	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Report each cipal water-bear	change in
Type of perforator used Mills Knife	MATERIAL	From To	swL
Size of perforations 3/8 in. by $2\frac{1}{4}$ in.	Topsoil	0	2
664 perforations from 80 ft. to 155 ft.	Brown Clay	2 3	1
perforations from ft. to ft.	Gray Clay	31 5	
perforations from ft. to ft.	Black Sand	59 6	8
(7) CODENIC.	Brown Sand and Gravel	68 15	7
(7) SCREENS: Well screen installed? ☐ Yes ☒ No	Blue Clay	157 16	0
Manufacturer's Name Model No		ļ	
Diam. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			-
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? X Yes ☐ No If yes, by whom? driller			
Yield: 550 gal./min. with 41 ft. drawdown after 2 hrs.			
" " "			
" " " "			<u> </u>
Bailer test gal./min. with ft. drawdown after hrs.			 -
Artesian flow g.p.m.			
perature of water Depth artesian flow encounteredft.	Work started 5/22/79 19 Complete	ed 5/23/79	10
		$\frac{5}{5/23/79}$. 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3, 23, 7,	19
Well seal—Material used Portland Cement	Drilling Machine Operator's Certification:		
well sealed from land surface toft.	This well was constructed under my Materials used and information reported	above are tru	rvision. ie to my
Diameter of well bore to bottom of sear	best knowledge and belief.		
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date 5/23/7.	9., 19
Number of sacks of cement used in well sealsacks How was cement grout placed? poured thru tremy pipe	Drilling Machine Operator's License No.	752	-
was content grout placed;			
	Water Well Contractor's Certification:	· immercial to the Committee	
	This well was drilled under my jurisdi true to the best of my knowledge and bel	ction and this	report is
Was a drive shoe used? 🕱 Yes 🗌 No Plugs Size: location ft.	Name Willamette Drilling Co.	IC1.	
Did any strata contain unusable water? 🗌 Yes ឺ No	(Person, firm or corporation)	(Type or p	
Type of water? depth of strata	Address 7365 O'Neill Rd. NE Sale	em, Oregon	97303
Method of sealing strata off	and I Dis		
Was well gravel packed? [] Yes 🕅 No Size of gravel:	[Signed] # THIS (Water Well Contra	actor)	
Gravel placed fromft. toft	Contractor's License No 561 Date	5/23/79	10