

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97330
within 30 days from the date
of well completion.

RECEIVED

STATE OF OREGON
(Please type or print)

MAR 16 4 71

State Well No.

75/2w-120

State Permit No.

48608 A-9921

FEB 26 1979 (Do not write above this line)

(1) OWNER: WATER RESOURCES DEPT.
SALEM, OREGON

Name Raymond Werner
Address 4783 Shannon Rd.
Silverton, Oregon 97381

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
10" Diam. from top ft. to 281 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.
Type of perforator used Mills Knife
Size of perforations 3/8 in. by 2 1/2 in.
730 perforations from 90 ft. to 150 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? driller
Yield: 600 gal./min. with 8 ft. drawdown after 3 hrs.
" " " "
" " " "
Baller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Portland Cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 14 in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal 11 sacks
How was cement grout placed? poured in from the top

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number 2191
1/4 1/4 Section 1 T. 7S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 77 ft.
Static level 32 ft. below land surface. Date 1/3/79
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing
Depth drilled 281 ft. Depth of completed well 281 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Topsoil	0	1	
Yellow Clay	1	28	
Blue Clay	28	77	
Cemented Brown Sand and Gravel	77	150	
Blue Clay	150	174	
Black Sand	174	193	
Blue Clay	193	270	
Red Clay	270	281	
Basalt	281	???	

Work started 11/14/78 19 Completed 1/3/79 19 79
Date well drilling machine moved off of well 1/4/79 19 79

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Ronald W. Martin Date 1/4/79, 19
(Drilling Machine Operator)

Drilling Machine Operator's License No. 536

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Willamette Drilling Co.
(Person, firm or corporation) (Type or print)

Address 7365 O'Neil Rd. NE Salem, Oregon 97303

[Signed] Dale D. Bair
(Water Well Contractor)

Contractor's License No. 561 Date 1/4/79, 19