NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER RESOURCES, DEPARTMENT,

SALEM, OREGON 97310

A P 2 (1981) (Please type or print)

within 30 days from the date of well completion. WATER RESOURCES DEPT

APR 21980 (Please type or print)

State Well No.

State Permit No.

(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:
Name Grace Slover	County Marion Driller's well number
Address 3660 Vista Dr.	SW 14 NE 14 Section 2 T. 7S R. 2W W.M.
North Bend Or. 97459	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Desired that appeared to the property of the p
New Well 💆 Deepening 🗌 Reconditioning 🗍 Abandon 🗍	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	7116
Rotary Driven Domestic D Industrial D Municipal D	Static level 36 ft. below land surface. Date10/10/79
Cable	
F	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded 12 Threaded 197 ft. Gage .250	(12) WELL LOG: Diameter of well below casing
	Depth drilled 197 ft. Depth of completed well 197 ft.
" Diam. from	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
(6) PERFORATIONS: Perforated? \( \frac{1}{2} \) Yes \( \superset \) No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Mills Knife	MATERIAL From To SWL
Size of perforations 5/16 in. by 4 in.	Topsoil 0 1
800 perforations from 130 ft. to 180 ft.	Clay Brown 1 26
perforations from ft. to ft.	Clay Grey 26 34
perforations from ft. to ft.	Clay Grey Sticky 34 69
(7) SCREENS: Well screen installed?   Yes   Yes	Sand Brown Fine 69 72
	Conglomerate Brown Medium 72 77
Manufacturer's Name	Sand Brown Coarse & Some
Diam. Slot size Set from ft. to ft.	Gravel 77 112
Diam. Slot size Set from ft. to ft.	Conglomerate Brown W.B. 112 184 W.B.
	Clay Grey 184 187 Sand Grey Coarse 187 192 W.B.
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Clay Grey Sticky 192 197
Was a pump test made? 🗌 Yes 🙀 No If yes, by whom?	DEDERVER
d: gal./min. with ft. drawdown after hrs.	VEDELAE
<i>" " " "</i>	Perforated 130' - 180' A #625 1980
A'9 " " " "	<u> </u>
Pailer test 600 gal./min. with /0/ ft. drawdown after hrs.	6" FILLER PIPE WATER RESOURCES DE
sian flow g.p.m.	FROM +1' +0 126' SALEM. OFFGON
Temperature of water Depth artesian flow encountered	Work started 9-25 19 79 Completed 10-10 19 79
(9) CONSTRUCTION:	Date well drilling machine moved of rot well 10-10 19 79
Compant Consist	
Well seal—Material used Cellient Grout  Well sealed from land surface to 26 ft.	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my
Diameter of well bore below seal	[Signed] Dynam D. Statel Date 10-20, 1979.
Number of sacks of cement used in well seal	(Drilling Machine Operator)
Now was cement grout placed? PRESSURE	Drilling Machine Operator's License No
	Water Well Contractor's Certification:
The same of the sa	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ₹ Yes □ No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? $\square$ Yes $X$ No	Name WEST COAST DRILLING CO., INC.
Type of water? depth of strata	(Person, firm or corporation) (Type or print)  Address 220 Academy St. Mt. Angel, OR 97362
	A The second of
Method of sealing strata off	[Signed] (Marlos C. Trillli
Was well gravel packed? 🗍 Yes 🕌 No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 519 Date 10-20 1979