

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

RECEIVED
WATER WELL REPORT
DEC 9 1974
STATE OF OREGON

RECEIVED M.A. (650)
FEB 7 1974
State Well No. 15/2W-3da
State Permit No. 6-6523

STATE ENGINEER, SALEM, OREGON
within 30 days from the date
of well completion.

STATE ENGINEER (Please type or print)
SALEM, OREGON

STATE ENGINEER
SALEM, OREGON

(1) OWNER:

Name Leonard Roth
Address 7088 Indigo St. SE Salem Ore

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

10" Diam. from +1 ft. to 177 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.
Type of perforator used Miller
Size of perforations 3/8 in. by 2 in.
972 perforations from 119 ft. to 159 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: 1000 gal./min. with 80 ft. drawdown after 4 hrs.
No test at this time " " " "
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 14 in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 3 sacks
Brand name of bentonite National
Number of pounds of bentonite per 100 gallons
of water 30 lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Mexion Driller's well number
NE 1/4 SE 1/4 Section 3 T. 7S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 20 ft.
Static level 40 ft. below land surface. Date 1-9-74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 10
Depth drilled 177 ft. Depth of completed well 177 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Brown Clay	0	22	
Grey Clay	22	47	
Brown Clay	47	75	
Cemented Gravel	75	88	
Small to Large Gravel w/ Sand	88	97	
Cemented Gravel	97	115	
Small to Large Gravel w/ Sand	115	159	
Cemented Gravel	159	177	

Work started 12-4 1973 Completed 1-9- 1974
Date well drilling machine moved off of well 1-10- 1974

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Norman J. Turrell Date 2-2, 1974
(Drilling Machine Operator)
Drilling Machine Operator's License No. 455.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name ROBINSON'S FOLA WELL DRILLING (Type or print)
(Person, firm or corporation)
Address 4510 DALLAS RD., N.W.
SALEM, OREGON 97304
[Signed] George H. Robinson
(Water Well Contractor)
Contractor's License No. 13 Date, 19.....