STATE ENGINEE	MAKK	l Record	COUNTY	NO. 7/2W_4D ARION - NO. GR_2632
OWNER: Alvin Schwengel	6550	MAILING ADDRESS:	5715 Van Cleave	Road Pg lof 4
LOCATION OF WELL: Owner MW 1/4 NW 1/4 Sec. 4 T.	r's No	CITY AND STATE:	Salem, Oregon	
Bearing and distance from section corner 1031; E. and 390;	on or subdivision			
corner				
Altitude at well				
TYPE OF WELL: Drilled			Section	
CASING RECORD:				
FINISH: Steel perforate 1-2" x ½" hole 1-2" x ¼" hole	size from 80 to	124	r less	
AQUIFERS: Soil, sand, cla	y, mud and grav	rel		
WATER LEVEL: 30-feet				
PUMPING EQUIPMENT: Ty Capacity350C	peBerkeley J.P.M.	Turbina		H.P. 15
WELL TESTS: Drawdown 15				
Drawdown	t. after	hours		G.P.M
USE OF WATERIRIGS SOURCE OF INFORMATION DRILLER or DIGGER	tion GR-2528	Temp	°F	, 19
ADDITIONAL DATA: Log X Water Level				

REMARKS:

STATE ENGINEER Salem, Oregon

main 4558

State Well No.	7/2W-4D
County MAR	
Application No.	

Well Log

Pg 2 of 4

Owner's No			
Date Drilled			
(Feet below land surface) From To		Thickness (feet)	
	30	30	
	60	30	
	70	10	
	74	4	
	80	6	
	124	44	
	130	6	
	145	15	
, ,			
		-	
	Date Drille	Date Drilled	

STATE ENGINEER Salem, Oregon	Well Record	STATE WELL NO COUNTYAPPLICATION N	Marion
Salem, Oregon MAR 4558	MAILING	*	Pg 3 of 4
OWNER: Alvin Schwengel	ADDRESS:		7 2 . 1
LOCATION OF WELL: Owner's No		***************************************)+************************************
N. S., F. Bearing and distance from section or subdicorner	ivision		
Altitude at well 182		-	
TYPE OF WELL: <u>Drilled</u> Date Const Depth drilled <u>145</u> Depth cased		Section	····
CASING RECORD:			
10 inch FINISH:			
Casing perforated 80 to 1	24, 130 to 145		
AQUIFERS: Cemented gravel from 80 to	o 124, and from 130 to	145	
WATER LEVEL:			
PUMPING EQUIPMENT: Type	Turbine	I	H.P. 15
WELL TESTS: Drawdown ft. after	hours	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	G.P.M.
Drawdown ft. after			
USE OF WATER	,		
ADDITIONAL DATA: LogX Water Level Measurement			

REMARKS:

STATE ENGINEER Salem, Oregon

mari 12558

State Well No. 7/2W-4D1
County Marion
·
Application No.

Well Log

riller:	(Feet below la		Thickness
CHARACTER OF MATERIAL	From	То	(feet)
Soil and sand	0	30	30
Soil and sand, water-bearing	30	60	30
Clay, brown, sandy	60	70	1.0
Gravel, sandy, water-bearing	70	74	ļ <i>'</i>
Sand, muddy	74	80	
Gravel, comented, water-bearing	80	124	4
Clay, dark-gray, sandy	124	130	
Gravel, cemented, water-bearing	130	145	
Casing: 10-inch to 145 feet; perforated 80 to 124 feet, and 130 to 145			
feet.			
			-
		 	
		1	